启用或禁用本地用户和组功能

ONTAP 9

NetApp
June 30, 2022

This PDF was generated from https://docs.netapp.com/zh-cn/ontap/smb-admin/enable-disable-local-users-groups-concept.html on June 30, 2022. Always check docs.netapp.com for the latest.

目录

启用或禁用本地用户和组功能 1
启用或禁用本地用户和组功能概述 1
启用或禁用本地用户和组 1
启用或禁用本地用户身份验证 2

启用或禁用本地用户和组功能

启用或禁用本地用户和组功能概述

在使用本地用户和组访问 NTFS 安全模式数据之前，必须启用本地用户和组功能。此外，如果要使用本地用户进行 SMB 身份验证，则必须启用本地用户身份验证功能。

默认情况下，本地用户和组功能以及本地用户身份验证处于启用状态。如果未启用它们，则必须先启用它们，然后才能配置和使用本地用户和组。您可以随时禁用本地用户和组功能。

除了显式禁用本地用户和组功能之外，如果集群中的任何节点还原到不支持本地用户和组功能的 ONTAP 版本，则 ONTAP 还会禁用此功能。只有当集群中的所有节点都运行支持本地用户和组功能的 ONTAP 版本时，才会启用此功能。

修改本地用户帐户

修改本地组

向本地或域用户或组添加权限

启用或禁用本地用户和组

您可以在 Storage Virtual Machine （ SVM ）上启用或禁用 SMB 访问的本地用户和组。默认情况下，本地用户和组功能处于启用状态。

您可以在配置 SMB 共享和 NTFS 文件权限时使用本地用户和组，也可以选择在创建 SMB 连接时使用本地用户进行身份验证。要使用本地用户进行身份验证，还必须启用本地用户和组身份验证选项。

步骤

1. 将权限级别设置为 advanced： `set -privilege advanced`
2. 执行以下操作之一：

希望本地用户和组 ...	输入命令 ...
enabled	`vserver cifs options modify -vserver` *`vserver_name`* `-is-local-users-and -groups-enabled true`
已禁用	`vserver cifs options modify -vserver` *`vserver_name`* `-is-local-users-and -groups-enabled false`

3. 返回到管理权限级别： `set -privilege admin`

以下示例将在 SVM vs1 上启用本地用户和组功能：

```
cluster1::> set -privilege advanced
Warning: These advanced commands are potentially dangerous; use them
only when directed to do so by technical support personnel.
Do you wish to continue? (y or n): y

cluster1::*> vserver cifs options modify -vserver vs1 -is-local-users-and
-groups-enabled true

cluster1::*> set -privilege admin
```

启用或禁用本地用户身份验证

启用或禁用本地用户帐户

启用或禁用本地用户身份验证

您可以为 Storage Virtual Machine （SVM）上的 SMB 访问启用或禁用本地用户身份验证。默认设置为允许本地用户身份验证，当 SVM 无法联系域控制器或您选择不使用域级别访问控制时，此功能非常有用。

必须在 CIFS 服务器上启用本地用户和组功能。

您可以随时启用或禁用本地用户身份验证。如果要在创建 SMB 连接时使用本地用户进行身份验证，则还必须启用 CIFS 服务器的本地用户和组选项。

步骤

1. 将权限级别设置为 advanced： `set -privilege advanced`
2. 执行以下操作之一：

本地身份验证的目标位置	输入命令 ...
enabled	`vserver cifs options modify -vserver` *`vserver_name`* `-is-local-auth-enabled true`
已禁用	`vserver cifs options modify -vserver` *`vserver_name`* `-is-local-auth-enabled false`

3. 返回到管理权限级别： `set -privilege admin`

以下示例将在 SVM vs1 上启用本地用户身份验证：

```
cluster1::>set -privilege advanced
Warning: These advanced commands are potentially dangerous; use them
only when directed to do so by technical support personnel.
Do you wish to continue? (y or n): y

cluster1::*> vserver cifs options modify -vserver vs1 -is-local-auth
-enabled true

cluster1::*> set -privilege admin
```

本地用户身份验证的工作原理

启用或禁用本地用户和组

版权信息

版权所有©2022 NetApp、Inc.。保留所有权利。Printed in the U.S.版权所涵盖的本文档的任何部分不得以任何形式或任何手段复制、包括影印、录制、 磁带或存储在电子检索系统中—未经版权所有者事先书面许可。

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

本软件由NetApp按"原样"提供、不含任何明示或默示担保、包括但不限于适销性和特定用途适用性的默示担保、特此声明不承担任何责任。IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice.NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp.The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S.patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

商标信息

NetApp、NetApp标识和中列出的标记 http://www.netapp.com/TM 是NetApp、Inc.的商标。其他公司和产品名称可能是其各自所有者的商标。