叢集管理基礎知識（僅限叢集管理員）
ONTAP 9

NetApp
May 13, 2022

This PDF was generated from https://docs.netapp.com/zh-tw/ontap/system-admin/display-nodes-cluster-task.html on May 13, 2022. Always check docs.netapp.com for the latest.

目錄

叢集管理基礎知識（僅限叢集管理員） 1
顯示叢集中節點的相關資訊 1
顯示叢集屬性 1
修改叢集屬性 2
顯示叢集複寫環的狀態 2
關於仲裁與epsilon 3
什麼是系統磁碟區 4

叢集管理基礎知識（僅限叢集管理員）

顯示叢集中節點的相關資訊

您可以顯示節點名稱、節點是否正常、以及節點是否符合參加叢集的資格。在進階權限層級、您也可以顯示節點是否保留epsilon。

步驟

1. 若要顯示叢集中節點的相關資訊、請使用「cluster show」命令。

   如果您希望輸出顯示某個節點是否保留epsilon、請在進階權限層級執行命令。

以下範例顯示四節點叢集中所有節點的相關資訊：

```
cluster1::> cluster show
Node                  Health  Eligibility
--------------------- ------- ------------
node1                 true    true
node2                 true    true
node3                 true    true
node4                 true    true
```

以下範例顯示進階權限層級中名稱為「'node1'」之節點的詳細資訊：

```
cluster1::> set -privilege advanced
Warning: These advanced commands are potentially dangerous; use them only
when directed to do so by support personnel.
Do you want to continue? {y|n}: y

cluster1::*> cluster show -node node1

       Node: node1
  Node UUID: a67f9f34-9d8f-11da-b484-000423b6f094
    Epsilon: false
Eligibility: true
     Health: true
```

顯示叢集屬性

您可以顯示叢集的唯一識別碼（UUID）、名稱、序號、位置和聯絡資訊。

步驟

1. 若要顯示叢集的屬性、請使用「cluster identity show」命令。

下列範例顯示叢集的名稱、序號、位置和聯絡資訊。

```
cluster1::> cluster identity show

          Cluster UUID: 1cd8a442-86d1-11e0-ae1c-123478563412
          Cluster Name: cluster1
 Cluster Serial Number: 1-80-123456
      Cluster Location: Sunnyvale
       Cluster Contact: jsmith@example.com
```

修改叢集屬性

您可以視需要修改叢集的屬性、例如叢集名稱、位置和聯絡資訊。

您無法變更建立叢集時所設定的叢集UUID。

步驟

1. 若要修改叢集屬性、請使用「cluster identity modify」命令。

   「-name」參數會指定叢集的名稱。"cluster identity modify"（叢集身分修改）手冊頁說明指定叢集名稱的規則。

   "-location（位置）"參數指定叢集的位置。

   「-contacts」參數指定聯絡資訊、例如姓名或電子郵件地址。

下列命令會將目前的叢集（「cluster1」）重新命名為「cluster2」：

```
cluster1::> cluster identity modify -name cluster2
```

顯示叢集複寫環的狀態

您可以顯示叢集複寫環的狀態、以協助診斷整個叢集的問題。如果叢集發生問題、支援人員可能會要求您執行此工作、以協助進行疑難排解。

步驟

1. 若要顯示叢集複寫環的狀態、請在進階權限層級使用「cluster環show」命令。

下列範例顯示名稱為node0之節點上VLDB複寫環的狀態：

```
cluster1::> set -privilege advanced
Warning: These advanced commands are potentially dangerous; use them only
when directed to do so by support personnel.
Do you wish to continue? (y or n): y

cluster1::*> cluster ring show -node node0 -unitname vldb
          Node: node0
     Unit Name: vldb
        Status: master
         Epoch: 5
   Master Node: node0
    Local Node: node0
      DB Epoch: 5
DB Transaction: 56
 Number Online: 4
      RDB UUID: e492d2c1-fc50-11e1-bae3-123478563412
```

關於仲裁與epsilon

仲裁和epsilon是叢集健全狀況和功能的重要衡量標準、可一起指出叢集如何因應潛在的通訊和連線挑戰。

_Quorum _是完整運作叢集的先決條件。當叢集達到仲裁數時、大多數的節點都很正常、可以彼此通訊。當仲裁遺失時、叢集便無法完成正常的叢集作業。由於所有節點共同共用資料的單一檢視、因此任何時候只有一個節點集合可以有仲裁。因此、如果允許兩個非通訊節點以不同方式修改資料、就無法再將資料協調成單一資料檢視。

叢集中的每個節點都會參與投票傳輸協定、選擇一個節點_master_；其餘每個節點都是_secondary _。主節點負責跨叢集同步處理資訊。當達到法定人數時、它會透過持續投票來維持。如果主節點離線且叢集仍處於仲裁狀態、則會由保持連線的節點選取新的主節點。

由於叢集內有一個節點數量偶數的關聯、因此一個節點有一個額外的分數投票權重稱為_epsilon_。如果大型叢集的兩個等部分之間的連線失敗、則包含epsilon的節點群組會維持仲裁、假設所有節點都正常運作。例如、下圖顯示其中兩個節點發生故障的四節點叢集。但是、由於其中一個可用節點保留了epsilon、即使沒有簡單多數的正常節點、叢集仍會維持在仲裁中。



在建立叢集時、Epsilon會自動指派給第一個節點。如果擁有epsilon的節點變得不健全、接管其高可用度合作夥伴、或由其高可用度合作夥伴接管、則epsilon會自動重新指派至不同HA配對中的正常節點。

使節點離線可能會影響叢集保持仲裁狀態的能力。因此ONTAP 、如果您嘗試將叢集從仲裁中移出、或是將叢集從仲裁中移出一次中斷、就會發出警告訊息。您可以在進階權限層級使用「cluster quorum service options modify」命令來停用仲裁警告訊息。

一般而言、假設叢集節點之間的連線可靠、較大型的叢集比較小的叢集更穩定。在24個節點的叢集中、只需簡單多數節點加上epsilon、就能比在兩個節點的叢集內更容易維護仲裁需求。

雙節點叢集在維護仲裁方面帶來一些獨特的挑戰。雙節點叢集使用_叢集HA _、其中兩個節點都不保留epsilon；而是會持續輪詢兩個節點、以確保當一個節點故障時、另一個節點擁有對資料的完整讀寫存取權、以及對邏輯介面和管理功能的存取權。

什麼是系統磁碟區

系統磁碟區FlexVol 是包含特殊中繼資料的功能區、例如檔案服務稽核記錄的中繼資料。這些磁碟區可在叢集中看到、因此您可以充分考慮叢集中的儲存設備使用量。

系統磁碟區由叢集管理伺服器（也稱為管理SVM）擁有、當檔案服務稽核啟用時、系統就會自動建立這些磁碟區。

您可以使用「volume show」命令來檢視系統磁碟區、但其他大部分的磁碟區作業則不允許。例如、您無法使用「volume modify」命令來修改系統磁碟區。

此範例顯示管理SVM上的四個系統磁碟區、當叢集中的資料SVM啟用檔案服務稽核時、系統會自動建立這些磁碟區：

```
cluster1::> volume show -vserver cluster1
Vserver   Volume       Aggregate    State      Type       Size  Available
Used%
--------- ------------ ------------ ---------- ---- ---------- ----------
-----
cluster1  MDV_aud_1d0131843d4811e296fc123478563412
                       aggr0        online     RW          2GB     1.90GB
5%
cluster1  MDV_aud_8be27f813d7311e296fc123478563412
                       root_vs0     online     RW          2GB     1.90GB
5%
cluster1  MDV_aud_9dc4ad503d7311e296fc123478563412
                       aggr1        online     RW          2GB     1.90GB
5%
cluster1  MDV_aud_a4b887ac3d7311e296fc123478563412
                       aggr2        online     RW          2GB     1.90GB
5%
4 entries were displayed.
```

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.