管理檔案鎖定
ONTAP 9

NetApp
May 19, 2022

This PDF was generated from https://docs.netapp.com/zh-tw/ontap/smb-admin/file-locking-between-protocols-concept.html on May 19, 2022. Always check docs.netapp.com for the latest.

目錄

管理檔案鎖定 1
關於在傳輸協定之間鎖定檔案 1
如何處理唯讀位元ONTAP 1
在處理共用路徑元件上的鎖定時、此功能與Windows有何ONTAP 不同 2
顯示鎖定的相關資訊 2
中斷鎖定 4

管理檔案鎖定

關於在傳輸協定之間鎖定檔案

檔案鎖定是用戶端應用程式用來防止使用者存取先前由其他使用者開啟的檔案的方法。如何鎖定檔案取決於用戶端的傳輸協定。ONTAP

如果用戶端是NFS用戶端、則鎖定為建議事項；如果用戶端是SMB用戶端、則鎖定為必要項目。

由於NFS與SMB檔案鎖定之間的差異、NFS用戶端可能無法存取先前由SMB應用程式開啟的檔案。

當NFS用戶端嘗試存取SMB應用程式鎖定的檔案時、會發生下列情況：

- 在混合或NTFS磁碟區中、像是「rm」、「rmdir」和「mv」等檔案處理作業、可能會導致NFS應用程式失敗。
- SMB拒絕讀取和拒絕寫入開啟模式會分別拒絕NFS讀取和寫入作業。
- 當檔案的寫入範圍遭專屬SMB bytelock鎖定時、NFS寫入作業會失敗。

在UNIX安全型磁碟區中、NFS取消連結和重新命名作業會忽略SMB鎖定狀態、並允許存取檔案。UNIX安全型磁碟區上的所有其他NFS作業都會遵守SMB鎖定狀態。

如何處理唯讀位元ONTAP

唯讀位元是逐一檔案設定、以反映檔案是可寫入（停用）或唯讀（啟用）。

使用Windows的SMB用戶端可以設定每個檔案的唯讀位元。NFS用戶端不會設定每個檔案的唯讀位元、因為NFS用戶端沒有任何使用每個檔案唯讀位元的傳輸協定作業。

當使用Windows的SMB用戶端建立檔案時、可以在檔案上設定唯讀位元。ONTAP在NFS用戶端和SMB用戶端之間共用檔案時、也可以設定唯讀位元。ONTAP有些軟體在NFS用戶端和SMB用戶端使用時、需要啟用唯讀位元。

為了在NFS用戶端和SMB用戶端之間共用的檔案上保留適當的讀取和寫入權限、它會根據下列規則來處理唯讀位元：ONTAP

- NFS會將任何啟用唯讀位元的檔案視為未啟用寫入權限位元。
- 如果NFS用戶端停用所有寫入權限位元、且至少有一個位元先前已啟用、ONTAP 則會啟用該檔案的唯讀位元。
- 如果NFS用戶端啟用任何寫入權限位元、ONTAP 則無法使用該檔案的唯讀位元。
- 如果已啟用檔案的唯讀位元、且NFS用戶端嘗試探索檔案的權限、則檔案的權限位元不會傳送至NFS用戶端；ONTAP 而是將權限位元傳送至NFS用戶端、並遮罩寫入權限位元。
- 如果已啟用檔案的唯讀位元、且SMB用戶端停用唯讀位元、ONTAP 則會啟用檔案的擁有者寫入權限位元。
- 啟用唯讀位元的檔案只能由root寫入。

> 檔案權限的變更會立即在SMB用戶端上生效、但如果NFS用戶端啟用屬性快取、則可能不會立即在NFS用戶端上生效。

在處理共用路徑元件上的鎖定時、此功能與Windows有何ONTAP 不同

不像Windows、ONTAP 在檔案開啟時、不會鎖定開啟檔案路徑的每個元件。此行為也會影響SMB共用路徑。

由於無法鎖定路徑的每個元件、因此可以重新命名開啟檔案或共用區上方的路徑元件、這可能會對某些應用程式造成問題、也可能導致SMB組態中的共用路徑無效。ONTAP這可能導致無法存取共用區。

為了避免重新命名路徑元件所造成的問題、您可以套用安全性設定、防止使用者或應用程式重新命名重要目錄。

顯示鎖定的相關資訊

您可以顯示目前檔案鎖定的相關資訊、包括鎖定的類型、鎖定狀態、位元組範圍鎖定、共用鎖定模式、委派鎖定及投機鎖定的詳細資料、以及鎖定是以耐久或持續的控點開啟。

無法針對透過NFSv4或NFSv4.1建立的鎖定顯示用戶端IP位址。

依預設、命令會顯示所有鎖定的相關資訊。您可以使用命令參數來顯示特定儲存虛擬機器（SVM）的鎖定資訊、或是根據其他條件篩選命令的輸出。

「vserver Locks show」命令會顯示四種鎖定類型的相關資訊：

- 位元組範圍鎖定、僅鎖定部分檔案。
- 共用鎖定、可鎖定開啟的檔案。
- 投機鎖定、可控制SMB上的用戶端快取。
- 委派：透過NFSv4.x控制用戶端快取

藉由指定選用參數、您可以決定每種鎖定類型的重要資訊。如需詳細資訊、請參閱命令的手冊頁。

步驟

1. 使用「vserver Locks show」命令顯示有關鎖定的資訊。

以下範例顯示NFSv4鎖定檔案路徑為「/vol1/file1」的摘要資訊。共享鎖定存取模式為WRITE拒絕_nONE、且鎖定是以寫入委派授予的：

```
cluster1::> vserver locks show

Vserver: vs0
Volume  Object Path                LIF         Protocol  Lock Type   Client
------- ------------------------- ----------- --------- -----------
-------
vol1    /vol1/file1                lif1        nfsv4     share-level -
               Sharelock Mode: write-deny_none
                                                          delegation  -
               Delegation Type: write
```

下列範例顯示檔案路徑為「/data2/data2_2/intro.pptx」的SMB鎖定詳細oplock與共享鎖定資訊。對於IP位址為10.3.1.3的用戶端、檔案上會以寫入拒絕的共用鎖定存取模式授予可持久使用的控制代碼。批次oplock層級的租賃oplock已授予：

```
cluster1::> vserver locks show -instance -path /data2/data2_2/intro.pptx

                    Vserver: vs1
                     Volume: data2_2
         Logical Interface: lif2
               Object Path: /data2/data2_2/intro.pptx
                 Lock UUID: 553cf484-7030-4998-88d3-1125adbba0b7
             Lock Protocol: cifs
                 Lock Type: share-level
   Node Holding Lock State: node3
                Lock State: granted
  Bytelock Starting Offset: -
    Number of Bytes Locked: -
     Bytelock is Mandatory: -
     Bytelock is Exclusive: -
     Bytelock is Superlock: -
          Bytelock is Soft: -
              Oplock Level: -
   Shared Lock Access Mode: write-deny_none
       Shared Lock is Soft: false
           Delegation Type: -
            Client Address: 10.3.1.3
             SMB Open Type: durable
         SMB Connect State: connected
SMB Expiration Time (Secs): -
         SMB Open Group ID:
78a90c59d45ae211998100059a3c7a00a007f70da0f8ffffcd445b0300000000

                    Vserver: vs1
                     Volume: data2_2
```

```
          Logical Interface: lif2
                Object Path: /data2/data2_2/test.pptx
                  Lock UUID: 302fd7b1-f7bf-47ae-9981-f0dcb6a224f9
             Lock Protocol: cifs
                 Lock Type: op-lock
    Node Holding Lock State: node3
                  Lock State: granted
   Bytelock Starting Offset: -
     Number of Bytes Locked: -
      Bytelock is Mandatory: -
      Bytelock is Exclusive: -
      Bytelock is Superlock: -
           Bytelock is Soft: -
               Oplock Level: batch
    Shared Lock Access Mode: -
        Shared Lock is Soft: -
            Delegation Type: -
             Client Address: 10.3.1.3
              SMB Open Type: -
          SMB Connect State: connected
 SMB Expiration Time (Secs): -
          SMB Open Group ID:
78a90c59d45ae211998100059a3c7a00a007f70da0f8ffffcd445b0300000000
```

中斷鎖定

當檔案鎖定阻礙用戶端存取檔案時、您可以顯示目前保留的鎖定資訊、然後中斷特定鎖定。您可能需要中斷鎖定的案例包括偵錯應用程式。

「vserver Locks Break」命令僅適用於進階權限層級及更高層級。命令的手冊頁包含詳細資訊。

步驟

1. 若要尋找解除鎖定所需的資訊、請使用「vserver Locks show」命令。

   命令的手冊頁包含詳細資訊。

2. 將權限等級設為進階：「et -priv榮幸advanc進 階」
3. 執行下列其中一項動作：

如果您要指定...來中斷鎖定	輸入命令...
SVM名稱、Volume名稱、LIF名稱及檔案路徑	"Vserver Locks Break -vserver vserver_name -volume volume volume volume volume名稱-path path -liflif"

如果您要指定...來中斷鎖定	輸入命令...
鎖定ID	"Vserver Locks中斷鎖定ID UUUID"

4. 返回管理員權限等級：「et -priv. admin」

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.