AWS S3做為雲端層

ONTAP 9

NetApp
May 17, 2022

This PDF was generated from https://docs.netapp.com/zh-tw/ontap/fabricpool/setup-aws-s3-cloud-tier-task.html on May 17, 2022. Always check docs.netapp.com for the latest.

目錄

將AWS S3設定為雲端層 1
將AWS S3設定為雲端層 1
將AWS S3附加為FabricPool 不支援的雲端層（影片） 2

將AWS S3設定為雲端層

如果您執行ONTAP 的是版本2、9.2或更新版本、您可以將AWS S3設定為FabricPool 適用的雲端層。如果您執行ONTAP 的是更新版本的版本、則可以設定AWS商業雲端服務（C2S）FabricPool 以供使用。

步驟

1. 使用「sorage Aggregate object-store config create」命令搭配「-provider-type」「AWs_S3」參數、指定AWS S3組態資訊。

   - 您可以使用「-auth-type」「cap」參數來取得用於C2S存取的認證資料。

     當您使用「-auth-type」「cap」參數時、必須使用「-cap」參數來指定完整的URL、以要求C2S存取的暫用認證資料。

   - 如果無法使用提供的資訊存取AWS S3、則「儲存Aggregate object-store config create」命令會失敗ONTAP 。
   - 您可以使用「-access-key」參數來指定存取金鑰、以授權要求存取AWS S3物件存放區。
   - 您可以使用「-secret密碼」參數來指定密碼（秘密存取金鑰）、以驗證AWS S3物件存放區的要求。
   - 如果AWS S3密碼已變更、您應該ONTAP 立即更新儲存在BIOS中的對應密碼。

     如此一來、即可讓支援中心不中斷地存取AWS S3中的資料。ONTAP

```
cluster1::> storage aggregate object-store config create
-object-store-name my_aws_store -provider-type AWS_S3
-server s3.amazonaws.com -container-name my-aws-bucket
-access-key DXJRXHPXHYXA9X31X3JX
```

+

```
cluster1::> storage aggregate object-store config create -object-store
-name my_c2s_store -provider-type AWS_S3 -auth-type CAP -cap-url
https://123.45.67.89/api/v1/credentials?agency=XYZ&mission=TESTACCT&role
=S3FULLACCESS -server my-c2s-s3server-fqdn -container my-c2s-s3-bucket
```

2. 使用「儲存Aggregate object-store config show」命令來顯示及驗證AWS S3組態資訊。

   使用「儲存Aggregate object-store config modify」命令、您可以修改AWS S3組態資訊FabricPool 以供使用。

將AWS S3設定為雲端層

如果您執行ONTAP 的是版本2、9.2或更新版本、您可以將AWS S3設定為FabricPool 適用的雲端層。如果您執行ONTAP 的是更新版本的版本、則可以設定AWS商業雲端服務

（C2S）FabricPool 以供使用。

步驟

1. 使用「sorage Aggregate object-store config create」命令搭配「-provider-type」「AWs_S3」參數、指定AWS S3組態資訊。

   - 您可以使用「-auth-type」「cap」參數來取得用於C2S存取的認證資料。

     當您使用「-auth-type」「cap」參數時、必須使用「-cap」參數來指定完整的URL、以要求C2S存取的暫用認證資料。

   - 如果無法使用提供的資訊存取AWS S3、則「儲存Aggregate object-store config create」命令會失敗ONTAP 。
   - 您可以使用「-access-key」參數來指定存取金鑰、以授權要求存取AWS S3物件存放區。
   - 您可以使用「-secret密碼」參數來指定密碼（秘密存取金鑰）、以驗證AWS S3物件存放區的要求。
   - 如果AWS S3密碼已變更、您應該ONTAP 立即更新儲存在BIOS中的對應密碼。

     如此一來、即可讓支援中心不中斷地存取AWS S3中的資料。ONTAP

```
cluster1::> storage aggregate object-store config create
-object-store-name my_aws_store -provider-type AWS_S3
-server s3.amazonaws.com -container-name my-aws-bucket
-access-key DXJRXHPXHYXA9X31X3JX
```

+

```
cluster1::> storage aggregate object-store config create -object-store
-name my_c2s_store -provider-type AWS_S3 -auth-type CAP -cap-url
https://123.45.67.89/api/v1/credentials?agency=XYZ&mission=TESTACCT&role
=S3FULLACCESS -server my-c2s-s3server-fqdn -container my-c2s-s3-bucket
```

2. 使用「儲存Aggregate object-store config show」命令來顯示及驗證AWS S3組態資訊。

   使用「儲存Aggregate object-store config modify」命令、您可以修改AWS S3組態資訊FabricPool 以供使用。

將AWS S3附加為FabricPool 不支援的雲端層（影片）

本影片快速概述如何使用System Manager附加AWS S3儲存區ONTAP 、以實現FabricPool 利用效益的整合。

"NetApp影片：將Amazon S3附加為FabricPool 外部容量層"

"NetApp TechCommTV：FabricPool 《支援目標清單"

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.