用于置克隆操作的参数

Snap Creator Framework

Zachary Wambold
August 04, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snap-creator-framework/administration/reference_parameters_to_set_up_cloning.html on October 27, 2021.
Always check docs.netapp.com for the latest.

目□

用于□置克隆操作的参数 1

用于□置克隆操作的参数

要□置 Snap Creator 服□器克隆操作，需要使用多个参数。

参数	正在□置 ...	Description
NTAP_VOL_clone_reserve	无	文件
volume	□是克隆卷的空□保□。	ntap_lun_clone_reservation
true	false	如果□置□ true ，□在□□ cloneLun 操作□，会□克隆的 LUN □留空□。否□，不会□留空□。
ntap_clone_igroup_map		指定存□系□，源卷和 igroup 。然后， igroup 会映射到源卷中的克隆 LUN 或卷克隆中的克隆 LUN （例如， `controller1 ： src_volume1/igroup1 ， src_volum2/igroup1 ， src_volume3/igroup1 ； controller2 ： src_volum1/igroup2 ， src_vol2 ， src_igroup2 ，` src_vol2 ， src_igroup2 ）。* 注： * • LUN 克隆的名称与其父卷或父 LUN 相同，并以 _clone □尾；也就是□，如果卷名□ myvol ，□克隆将□ myvol_clone 。 • 卷克隆以 cl_ □□，以 -YYYYMMDDHMMSS. □尾。
ntap_clone_for_backup	Y	不包括
如果□用此□□，□会□建克隆（卷和 LUN ），然后在其他操作完成后将其□除。否□，克隆将在操作完成之前被□除。* 注： * 如果要将克隆□□到磁□，□□将其□置□ Y如果正在□行数据□刷新，□□将其□置□ N	ntap_clone_secondary	Y

参数	正在□置 …	Description
不包括	如果□用此□□，□在 SnapMirror 更新完成后，将在 SnapMirror 目□上□建克隆。* 注： * 此□置□与 NTAP_snapmirror_use_snapshot ， NTAP_snapmirror_wait 和 NTAP_clone_secondary 卷以及 cloneVol 操作□合使用。	ntap_clone_secondary 卷
	□是主存□系□或二□存□系□与二□卷的映射。要使 Snap Creator 能□□到二□卷（例如， controller1 ： controller1-sec/vol1 ； controller1 ： controller1-sec/vol2 ），必□□行此操作。	NTAP_NUM_VOL_CLEN克 隆
	□是要保留的卷克隆的数量。□与 Snapshot 副本保留策略□似。* 注： * 此功能□□用于需要在存□控制器上安装 FlexClone □可□的卷克隆。	ntap_nfs_export_host
主机 IP	□□出克隆的主机名或 IP 地址。此主机是使用 NFS 挂□克隆卷的主机。	ntap_nfs_export_access
root	□写	只□
在 NTAP_NFS_export_host 中指定的主机可接收□克隆卷的□□□限或□限。 • root 已授予 root □□□限。 • 只□ 授予只□□□□限。 • □写 已授予□ / 写□□□限。	ntap_nfs_export_persistent	true
false	□定 NFS □出是否持久。如果□□ true ， □会□出克隆卷，并更新存□控制器上的 /etc/exports 文件。	ntap_cifs_export_enable

参数	正在□置 …	**Description**
Y	不包括	□置以使用 CIFS 共享克隆的卷。

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.