Adding commands to the backup and restore configuration

Snap Creator Framework

NetApp
August 04, 2021

This PDF was generated from https://docs.netapp.com/us-en/snap-creator-framework/domino-ops/concept_allowing_additional_commands_through_the_snap_creator_agent.html on August 04, 2021.
Always check docs.netapp.com for the latest.

Table of Contents

Adding commands to the backup and restore configuration . . . 1
Where to run supplemental commands . . . 1
Where to add supplemental commands . . . 1
Allowing supplemental commands on the Snap Creator Agent . . . 1
Adding supplemental commands to the configuration . . . 2

Adding commands to the backup and restore configuration

Occasionally, a backup or restore operation might need to run a command that is not available in Snap Creator. On Window hosts using FC or iSCSI, for example, you might prefer to use SnapDrive commands for backups instead of native Snap Creator commands, to ensure file system consistency at the OS level.

Where to run supplemental commands

By default, supplemental commands run on the Snap Creator Agent. You can run a supplemental command on the Server by prepending the command with the text SERVER, followed by a colon (:). For example, SERVER:C:\myscript.bat.

If you want to run a supplemental command on the Agent, you must explicitly permit the command to be executed by including it in the allowed_commands.config file on the Agent. There is no requirement to allow supplemental commands on the Server.

Where to add supplemental commands

You can use either the Snap Creator GUI or the Snap Creator CLI to add commands to your backup and restore configuration.

This guide shows how to use the GUI to add commands. For information on how to use the CLI, see the Snap Creator Framework 4.1.2 Administration Guide.

Related information

Allowing supplemental commands on the Snap Creator Agent Adding supplemental commands to the configuration

Allowing supplemental commands on the Snap Creator Agent

If you want to run a supplemental command on the Snap Creator Agent, you must explicitly permit the command to be executed by including it in the allowed_commands.config file on the Agent.

allowed_commands.config is located in the etc subdirectory of the Snap Creator Agent installation directory. For example:

- On UNIX hosts, /install/path/scAgent4.1.x/etc/allowed_commands.config
- On Windows hosts, C:\Program Files\NetApp\Snap_Creator_Framework\scAgent4.1.x\etc\allowed_commands.config

To allow supplemental commands on the Agent, open allowed_commands.config in an editor. Enter each command on its own line, exactly as you would enter the command at a command prompt. Case is significant. Make sure to specify the fully qualified pathname. Enclose the pathname in quotation marks if it contains

spaces. For example:

```
"C:\Program Files\NetApp\SnapDrive\sdcli.exe"
 myscript.bat
```

Restart the Agent for the changes to take effect.

For security reasons, you should not use a wildcard entry (*) to allow all commands.

Adding supplemental commands to the configuration

You can add supplemental commands to your configuration after you create the configuration file. You can run the commands on the Snap Creator Server or Agent.

To run a supplemental command on the Agent, you should already have added the command to the allowed_commands.config file on the Agent.

By default, supplemental commands run on the Agent. You can run a supplemental command on the Server by prepending the command with the text SERVER, followed by a colon (:). For example, SERVER:C:\myscript.bat. There is no requirement to allow the command on the Server.

You can use either the Snap Creator GUI or the Snap Creator CLI to add commands to your backup and restore configuration.

This guide shows how to use the GUI to add commands. For information on how to use the CLI, see the Snap Creator Framework 4.1.2 Administration Guide.

1. In the Profiles and Configurations pane, select the configuration file and click the **Commands** tab.

   The following command types are available:

Command type	Description
Application Quiesce	For non-plug-in use only. Ignore this command type.
Application Un-Quiesce	For non-plug-in use only. Ignore this command type.
Pre Exit	Use this type to run commands that tell Snap Creator what to do after a fatal error.
Snapshot Copy Create	Use this type to run your own Snapshot copy create commands.

   Only a subset of the supported commands are available in the GUI. For information on the APP, ARCHIVE, MOUNT/UNMOUNT, and POST commands, see the Snap Creator Framework 4.1.2 Administration Guide.

2. On the **Commands** tab, scroll to the section for the command type you want to use and click **Add**.

3. Type over the text **Add Command Here** to enter the command.

   To use SnapDrive for Windows to create a backup, you might enter the following in the section for the Snapshot Copy Create command type:

   ```
   "C:\Program Files\NetApp\SnapDrive\sdcli.exe" snap create -s %SNAME-
   %SNAP_TYPE_%SNAP_TIME -D F G H
   ```

   where:

   - "C:\Program Files\NetApp\SnapDrive\sdcli.exe" is the default installation path for the SnapDrive CLI.
   - %SNAME-%SNAP_TYPE_%SNAP_TIME specifies that the Snapshot copy name be formed from the configuration file name, the Snapshot policy (hourly, daily, or monthly), and the time and date the Snapshot copy was created.
   - D is the switch and F G H are the mount points for the data to be backed up. TIP: To run the command on the Server, prepend the command with the text SERVER, followed by a colon (:).
4. When you are satisfied with your entry, press **Enter**.
5. Repeat steps #STEP_3F9C83DD05D84075AD0277213FD67C56 through #STEP_FBEDD7AE105F42138EB35315EA9FA7CC to add another command.
6. Click **Save** in the Configuration Content pane to save your changes.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.