SnapDrive snap connect 命令的工作原理

Snapdrive for Unix

NetApp
August 06, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snapdrive-unix/solaris/concept_how_the_snapdrivesnap_connect_command_works.html on October 26, 2021. Always check docs.netapp.com for the latest.

目□

SnapDrive snap connect 命令的工作原理 1

SnapDrive snap connect 命令的工作原理

使用 SnapDrive snap connect` 命令□，它会克隆指定□体的存□并将其□入到主机：

- 如果□指定的 Snapshot 副本包含 LUN （` -lun` ），□ SnapDrive for UNIX 会将 LUN 的新副本映射到主机。□不能使用 SnapDrive snap connect` 命令在与其他存□□体（` -vg` ， ` -DG` ， ` -FS` ， ` -lvol` 或 ` - hostvol` ）相同的命令行上指定 LUN 。
- 如果□指定的文件系□直接□留在 LUN 上，□ SnapDrive for UNIX 会将 LUN 映射到主机并挂□文件系□。
- 如果在 `snap connect` 命令中将源挂□点指定□相□路径名，□ SnapDrive for UNIX 将忽略在命令行界面中指定的目□挂□点，并使用格式□ `ssource_mount_point_<N>` 的内部命名□定来命名目□挂□点。
- 如果□指定的 Snapshot 副本包含磁□□，或者主机卷或文件系□属于磁□□，□ SnapDrive snap connect` 命令会□接整个目□磁□□。□了建立□接， SnapDrive for UNIX 会重新激活目□磁□□的所有□□卷，并将所有文件系□挂□到□□卷上。
- 如果使用 snap connect 命令指定 `autorename` □□，□主机卷和文件系□始□会重命名。只有当磁□□已位于主机上□，才会□其□行重命名。
- 如果□指定的 Snapshot 副本包含 NFS 目□□，□ SnapDrive for UNIX 将□包含 NFS 目□□的 FlexVol 卷□建一个克隆。然后， SnapDrive for UNIX 会将卷□接到主机并挂□ NFS 文件系□。在目□□中， SnapDrive for UNIX 会□除□在□建 Snapshot 副本后□建的任何新 NFS 文件或目□。如果将 `snapconnect-nfs-removedirectories` 配置□□□置□ on ，□ SnapDrive for UNIX 将从 FlexVol 卷中□除□□接的 NFS 目□以外的任何文件或目□。
- 如果使用 ` readonly` □□□接包含 NFS 目□□的 Snapshot 副本，□ SnapDrive for UNIX 将直接挂□□目□的 Snapshot 副本，而不□建克隆。□不能使用 SnapDrive snap connect` 命令在与非 NFS □体相同的命令行上指定 NFS 挂□点，即使用□□ ` -vg` ， ` -DG` ， ` -FS` ， ` -lvol` 或 ` - hostvol` 。

Data ONTAP 7.3 及更高版本支持在 vFiler □境中使用 ` -split` □□□行 `snap connect` 操作。

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.