什□是 AutoSupport

Snapdrive for Unix

NetApp
October 26, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snapdrive-unix/aix/concept_how_snapdrive_forunix_usesautosupport.html on October 26, 2021. Always check docs.netapp.com for the latest.

目□

什□是 AutoSupport 1
SnapDrive for UNIX 如何使用 AutoSupport 1
AutoSupport 消息的内容 1
AutoSupport 消息示例 2

什□是 AutoSupport

AutoSupport 允□ SnapDrive for UNIX 将因 SnapDrive □送到存□系□的 EMS 日志□□中的 ` /etc/log/EMS` 文件而□生的任何操作故障□送到 EMS 日志□□。

SnapDrive for UNIX 如何使用 AutoSupport

如果在 `snapdrive.conf` 文件中将 ` napdrive.conf` □□□置□ on ， □ AutoSupport 消息将□□在存□系□的 EMS 日志□□中。默□情况下，在 `snapdrive.conf` 文件中，此□□□置□ ` *on*` 。SnapDrive for UNIX 会将 AutoSupport 消息□送到存□系□，而□些消息会□□在事件管理系□（ EMS ）中。

在以下任一情况下都会□送 AutoSupport 消息：

- 如果操作因操作失□而停止，□会向操作失□的存□系□□送 AutoSupport 消息。
- 如果将多个存□系□□接到主机，并且多个存□系□□生操作故障，□ SnapDrive for UNIX 会将 AutoSupport 消息□送到操作失□的特定存□系□。
- 使用 ` UNIX 配置集 < 用□名 > < 文件名 >_` 添加新存□控制器□， SnapDrive for AutoSupport 会向指定的存□系□□送 SnapDrive 消息。
- 重新□□或□□ SnapDrive 守□□程后， AutoSupport 消息将□送到配置的存□系□。
- □行 SnapDrive storage show -all` 命令后， AutoSupport 消息将□送到所有已配置的存□系□。
- 成功□行快照□建操作后， AutoSupport 消息将□送到存□系□。

AutoSupport 消息的内容

AutoSupport 消息包含以下信息。

- 事件源
- 事件 ID
- □用于 UNIX 的 SnapDrive 版本
- 消息状□：日志□□消息，例如 1 表示警□， 2 表示□重， 3 表示□□， 4 表示警告， 5 表示通知， 6 表示信息， 7 表示□□
- 主机名
- 主机操作系□
- 主机操作系□的版本
- 存□系□的名称
- 使用 Protection Manager/ 基于角色的□□控制
- □□□□
- AutoSupport 将消息条目□□□ false
- 主机多路径□型：将□□在 `snapdrive.conf` file 中配置的□。如果由于配置□不正□而未加□此助手，□不

会□□任何主机多路径□型。

- 主机虚□化已□用：此功能□□用于 VMware 子操作系□。
- protocol ：在 `snapdrive.conf` 文件中□ `默□□□ _` 配置的□。
- 保□已□用：如果 OnCommand Data Fabric Manager （ DFM ）配置了 SnapDrive for UNIX ， □会□□□ `*Yes*` 。

> SnapDrive for UNIX 不会□□是否正在使用 OnCommand DFM 。

□行 SnapDrive storage show -all` 命令□，可以使用以下追加信息：

- □□□型（ FCP/iSCSI ）：用于□建 LUN 的□□（如果有）。
- 已□接的 LUN 数量
- 磁□或卷□的数量
- 文件□□的数量
- 主机卷的数量

> 如果在 SnapDrive for UNIX 中□用了 AutoSupport ， □在□生任何操作失□□，事件管理系□（ Event Management System ， VM ）存□系□中会□□□□消息。如果□□消息包含任何特殊字符，例如（ < ， > ， & ， ' ， " ， \r ），在存□系□的 EMS 日志□□中会□示格式□□的□。

AutoSupport 消息示例

SnapDrive for UNIX 提供了□用于不同情形的示例。无□□的操作系□如何，所有示例中的 AutoSupport 消息内容都基本相同。

示例：添加新存□系□

以下示例是从名□ `*aix207-116*` 的主机□送的消息：

```
computerName="aix207-116"
        eventSource="snapdrive"
        appVersion="5.2 for UNIX"
        eventID="3"
        category="ohio configured"
        subject="host_name=aix207-116, host_os=AIX, host_os_release=1,
host_os_version=6, No of controller=1, PM/RBAC=native, Host
Virtualization=No, Multipath-type=nativempio, Protection Enabled=No,
Protocol=fcp"
```

示例：重新□□守□□程

重新□□守□□程□， SnapDrive for UNIX 会向存□系□□送以下 AutoSupport 消息：

```
computerName="aix207-116"
        eventSource="snapdrive"
        appVersion="5.2 for UNIX"
        eventID="2"
        category="daemon restarted"
        subject="host_name=aix207-116, host_os=AIX, host_os_release=1,
host_os_version=6, No of controller=1, PM/RBAC=native, Host
Virtualization=No, Multipath-type=nativempio, Protection Enabled=No,
Protocol=fcp"
```

当存□□接操作失□□， SnapDrive for UNIX 会向存□系□□送以下 AutoSupport 消息：

```
computerName="aix207-116"
        eventSource="snapdrive"
        appVersion="5.2 for UNIX"
        eventID="4"
        category="storage connect failed"
        subject="host_name=aix207-116, host_os=AIX, host_os_release=1,
host_os_version=6, No of controller=1, PM/RBAC=native, Host
Virtualization=No, Multipath-type=nativempio, Protection Enabled=No,
Protocol=fcp,1384: LUN /vol/vol0/test1 on storage system ohio already
mapped to initiators in igroup aix207-116_fcp_SdIg at ID 0."/
```

当 `snap create` 操作成功□， SnapDrive for UNIX 会向存□系□□送以下 AutoSupport 消息：

```
computerName="aix207-116"
        eventSource="snapdrive"
        appVersion="5.2 for UNIX"
        eventID="5"
        category="snap create successful"
        subject="host_name=aix207-116, host_os=AIX, host_os_release=1,
host_os_version=6, No of controller=1, PM/RBAC=native, Host
Virtualization=No, Multipath-type=nativempio, Protection Enabled=No,
Protocol=fcp, snapshot_name=snap1"
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.