SVM 的配置信息

Snapdrive for Unix

NetApp
July 19, 2022

This PDF was generated from https://docs.netapp.com/zh-cn/snapdrive-unix/aix/concept_login_information_for_vserver.html on July 19, 2022. Always check docs.netapp.com for the latest.

目录

SVM 的配置信息 1
SVM 的登录信息 1
指定 SVM 的登录信息 1
验证 SVM 的登录信息 1
从 SVM 中删除用户 2

SVM 的配置信息

要执行 SnapDrive 操作，您必须在 SnapDrive for UNIX 中配置 Vserver 。

要使用适用于 UNIX 的 SnapDrive 配置 SVM ，请在集群模式 Data ONTAP 中，确保 SVM 的管理逻辑接口（ LIF ）的 IP 地址已与 SVM 名称映射，可以在域名服务（ DNS ）或 ` /etc/hosts` 文件中进行映射。此外，还必须使用以下命令确保已在适用于 UNIX 的 SnapDrive 中配置 Vserver 名称：

` * SnapDrive 配置集 <vsadmin> <vserver name>*`

- 相关信息 *

支持 SVM

SVM 的登录信息

用户名和密码允许 SnapDrive for UNIX 访问 SVM 。它还提供了安全性，因为除了以 vsadmin 身份登录之外，您还必须运行 SnapDrive for UNIX ，并在出现提示时提供正确的用户名和密码。

指定 SVM 的登录信息

您必须指定 SVM 的用户登录信息。根据您在设置 Vserver 时指定的内容，每个 Vserver 都必须使用配置的 Vserver 用户名。如果您的 Vserver 名称发生更改，则必须确保已在适用于 UNIX 的 SnapDrive 中配置新的 Vserver 名称。

步骤

1. 输入以下命令：

   ` * SnapDrive 配置集 *user_name filename* [*filename*…]*`

   - ` *user_name*` 是首次设置 SVM 时为 SVM 指定的用户名。默认用户为 vsadmin 。` *filename*` 是 SVM 名称。
   - ` filer_name_` 允许您在一个命令行中输入多个 SVM ，前提是它们都具有相同的用户登录名或密码。必须至少输入一个 Vserver 名称。

     ```
     # snapdrive config set vsadmin clstr-vs2
     Password for vsadmin:
     Retype password:
     ```

验证 SVM 的登录信息

您可以使用 SnapDrive config list` 命令验证是否在适用于 UNIX 的 SnapDrive 中配置了 。

步骤

1. 输入以下命令： SnapDrive config list`

   此命令显示在适用于 UNIX 的 SnapDrive 中指定的用户名或 Vserver ，而不显示 Vserver 的密码。

   以下示例将 ` *vsadmin*` 显示为 ` *StorageSystem*` 。

```
# snapdrive config list
username    appliance name   appliance type
-------------------------------------------
vsadmin     clstr-vs2        StorageSystem
```

从 SVM 中删除用户

您可以通过执行 SnapDrive config delete` 命令从 SVM 中删除登录信息。

步骤

1. 输入以下命令：

   ` * SnapDrive 配置 delete *appliation_name**`

   ` 设备名称 _` 是要删除登录信息的 SVM 的名称。

```
# snapdrive config delete clstr-vs2
Deleted configuration for appliance: clstr-vs2
```

   SnapDrive for UNIX 将删除您指定的 SVM 的登录信息。

版权信息

版权所有©2022 NetApp、Inc.。保留所有权利。Printed in the U.S.版权所涵盖的本文档的任何部分不得以任何形式或任何手段复制、包括影印、录制、 磁带或存储在电子检索系统中—未经版权所有者事先书面许可。

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

本软件由NetApp按"原样"提供、不含任何明示或默示担保、包括但不限于适销性和特定用途适用性的默示担保、特此声明不承担任何责任。IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice.NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp.The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S.patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

商标信息

NetApp、NetApp标识和中列出的标记 http://www.netapp.com/TM 是NetApp、Inc.的商标。其他公司和产品名称可能是其各自所有者的商标。