Command-line arguments

Snapdrive for Unix

Ivana Devine, Aksel Davis
January 25, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapdrive-unix/solaris/reference_command_line_arguments.html on August 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Command-line arguments 1

Command-line arguments

The SnapDrive for UNIX takes arguments in a specific format.

The following table describes the arguments you can specify with the keywords.

Use the format `snapdrive type_name operation_name [<keyword/option> <arguments>]`; for example, if you wanted to create a Snapshot copy called *`snap_hr`* from the host file system `/mnt/dir`, you would enter the following command line:

`snapdrive snap create -fs/mnt/dir -snapnamesnap_hr`.

Argument	Description
dest_fspec	The name by which the target entity will be accessible after its disk groups or LUNs are connected.
dgname	The name of a disk group or volume group.
d_lun_name	Allows you to specify a destination name that SnapDrive for UNIX uses to make the LUN available in the newly-connected copy of the Snapshot copy.
filername	The name of a storage system.
filer_path	A path name to a storage system object. This name can contain the storage system name and volume, but it does not have to if SnapDrive for UNIX can use default values for the missing components based on values supplied in the previous arguments. The following are examples of path names: • `test_filer:/vol/vol3/qtree_2` • `/vol/vol3/qtree_2` • `qtree_2`

Argument	Description

file_spec	The name of a storage entity, such as a host volume, LUN, disk or volume group, file system, or NFS directory tree.
	
	In general, you use the file_spec argument as one of the following:
	
	• An object you want SnapDrive for UNIX to make a Snapshot copy of or to restore from a Snapshot copy
	• An object that you want to either create or use when provisioning storage
	
	The objects do not have to be all of the same type. If you supply multiple host volumes, they must all belong to the same volume manager.
	
	If you supply values for this argument that resolve to redundant disk groups or host volumes, the command fails.
	
	Example of incorrect usage: This example assumes dg1 has host volumes hv1 and hv2, with file systems fs1 and fs2. As a result, the following arguments would fail because they involve redundant disk groups or host volumes.
	
	`-dg dg1 -hostvol dg1/hv1`
	
	`-dg dg1`
	
	`-fs/fs1`
	
	`-hostvol dg1/hv1 -fs /fs1`
	
	Example of correct usage: This example shows the correct usage for this argument.
	
	`-hostvol dg1/hv1 dg1/hv2`
	
	`-fs /fs1 /fs2`
	
	`-hostvol dg1/hv1 -fs /fs2`

Argument	Description
fspec_set	Used with the snap connect command to identify: • A host LVM entity • A file system contained on a LUN The argument also lets you specify a set of destination names that SnapDrive for UNIX uses when it makes the entity available in the newly connected copy of the Snapshot copy. The format for fspec_set is: `{ -vg | -dg | -fs | -lvol | -hostvol } src_fspec [dest_fspec] [{ -destdg | -destvg } dg_name] [{ - destlv | -desthv } lv_name]`

Argument	Description
host_lvm_fspec	Lets you specify whether you want to create a file system, logical volume, or disk group when you are executing the storage create command. This argument might have any of the three formats as described in the following. The format you use depends on the entity you want to create. The `-dg` and `-vg` options are synonyms that reflect the fact that some operating systems refer to disk groups and others refer to volume groups. In addition, `-lvol` and `-hostvol` are also synonyms. This guide uses `-dg` to refer to both disk groups and volume groups and `-hostvol` to refer to both logical volumes and host volumes.
	To create a file system, use this format: `-fs file_spec [-fstype type] [-fsopts options] [-hostvol file_spec] [-dg dg_name]` To create a logical or host volume, use this format: `[-hostvol file_spec] [-dg dg_name] | -hostvol` To create a disk or volume group, use this format: `file_spec [-dg dg_name] | -dg dg_name` You must name the top-level entity that you are creating. You do not need to supply names for any underlying entities. If you do not supply names for the underlying entities, SnapDrive for UNIX creates them with internally generated names. If you specify that SnapDrive for UNIX create a file system, you must specify a type that SnapDrive for UNIX supports with the host LVM. These types include `vxfs` or `ufs`. The option `-fsopts` is used to specify options to be passed to the host operation that creates the new file system; for example, `mkfs`.
ig_name	The name of an initiator group.

Argument	Description

long_filer_path	A path name that includes the storage system name, volume name, and possibly other directory and file elements within that volume. The following are examples of long path names:
	
	`test_filer:/vol/vol3/qtree_2`
	
	`10.10.10.1:/vol/vol4/lun_21`

long_lun_name	A name that includes the storage system name, volume, and LUN name. The following is an example of a long LUN name: `test_filer:/vol/vol1/lunA`
long_snap_name	A name that includes the storage system name, volume, and Snapshot copy name. The following is an example of a long Snapshot copy name: `test_filer:/vol/account_vol:snap_20040202` With the `snapdrive snap show` and `snapdrive snap delete` commands, you can use the asterisk (*) character as a wildcard to match any part of a Snapshot copy name. If you use a wildcard character, you must place it at the end of the Snapshot copy name. SnapDrive for UNIX displays an error message if you use a wildcard at any other point in a name. Example: This example uses wildcards with both the snap show command and the snap delete command: snap show myfiler:/vol/vol2:mysnap* `myfiler:/vol/vol2:/yoursnap* snap show myfiler:/vol/vol1/qtree1:qtree_snap* snap delete 10.10.10.10:/vol/vol2:mysnap* 10.10.10.11:/vol/vol3:yoursnap* hersnap` Limitation for wildcards: You cannot enter a wildcard in the middle of a Snapshot copy name. For example, the following command line produces an error message because the wildcard is in the middle of the Snapshot copy name: banana:``/vol/vol1:my*snap`
lun_name	The name of a LUN. This name does not include the storage system and volume where the LUN is located. The following is an example of a LUN name: *`lunA`*

Argument	Description
path	Any path name.
prefix_string	prefix used in the volume clone's name generation
s_lun_name	Indicates a LUN entity that is captured in the Snapshot copy specified by `long_snap_name`.

Related information

Storage provisioning command lines

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.