SnapManager 如何保持安全性

SnapManager Oracle

NetApp
August 06, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snapmanager-oracle/unix-administration/concept_snapmanager_security.html on October 26, 2021. Always check docs.netapp.com for the latest.

目□

SnapManager 如何保持安全性 1

SnapManager 如何保持安全性

只有在具有相□凭据的情况下，才能□行 SnapManager 操作。SnapManager 中的安全性受用□身□□□和基于角色的□□控制（ Role-Based Access Control， RBAC ）的制□。通□ RBAC， 数据□管理□可以限制 SnapManager □数据□中存放数据文件的卷和 LUN □行的操作。

数据□管理□使用 SnapDrive □ SnapManager □用 RBAC 。然后，数据□管理□在 Operations Manager □形用□界面（ GUI ）或命令行界面（ CLI ）中□ SnapManager 角色分配□限，并将□些角色分配□用□。RBAC □限□□会在 DataFabric Manager 服□器中□行。

除了基于角色的□□之外， SnapManager □通□密□提示或□置用□凭据来□求用□身□□□，从而保持安全性。有效用□通□ SnapManager 服□器□行身□□□和授□。

SnapManager 凭据和用□身□□□与 SnapManager 3.0 截然不同：

- 在 SnapManager 3.0 之前的版本中，□可以在安装 SnapManager □□置任意服□器密□。任何要使用 SnapManager 服□器的用□都需要 SnapManager 服□器密□。需要使用 smo credential set -host 命令将 SnapManager 服□器密□添加到用□凭据中。
- 在 SnapManager （ 3.0 及更高版本）中， SnapManager 服□器密□已替□□□个用□操作系□（ OS ）身□□□。如果□□行的客□端与主机不在同一服□器上，□ SnapManager 服□器将使用□的操作系□用□名和密□□行身□□□。如果不希望系□提示□□入操作系□密□，可以使用 smo credential set -host 命令将数据保存到 SnapManager 用□凭据□存中。

> 当 SMO.config 文件中的 host.credentials.persist 属性□置□ true □， smo credential set -host 命令会□住□的凭据。

- 示例 *

用□ 1 和用□ 2 共享一个名□ Prof2 的配置文件。如果用□ 2 没有□□ Host1 的□限，□无法在 Host1 中□行 database1 的□□。如果用□ 1 没有□□ Host3 的□限，□无法将数据□克隆到 Host3 。

下表介□了分配□用□的不同□限：

□限□型	用□ 1	用□ 2.
主机密□	Host1， Host2	Host2， Host3
存□□密□	参考 1	参考 1
配置文件密□	Prof1， Prof2	2

如果用□ 1 和用□ 2 没有任何共享配置文件，□假定用□ 1 □名□ Host1 和 Host2 的主机具有□限，而用□ 2 □名□ Host2 的主机具有□限。用□ 2 甚至无法在 Host1 上□行非配置文件命令，例如 dump 和 system verify 。

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.