smo history set 命令

SnapManager Oracle

NetApp
August 06, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snapmanager-oracle/unix-administration/reference_the_smosmsap_history_set_command.html on October 26, 2021.
Always check docs.netapp.com for the latest.

目□

smo history set 命令 1
□法 1
Parameters 1
命令示例 2

smo history set 命令

□可以□行 history set 命令来配置要□看其□史□□的操作。

□法

```
        smo history set
-profile \{-name profile_name \[profile_name1, profile_name2\] \| -all
-repository
-login \[password repo_password\]
-username repo_username
-host repo_host
-dbname repo_dbname
-port repo_port}
-operation \{-operations operation_name \[operation_name1,
operation_name2\] \| -all\}
-retain
{-count retain_count \| -daily daily_count \| -monthly monthly_count \|
-weekly weekly_count}
[-quiet | -verbose]
```

Parameters

- * 配置文件配置文件 *

  指定配置文件的名称。此名称最□可□ 30 个字符，并且在主机中必□是唯一的。

- * 存□□ *

  指定存□配置文件的数据□的□□信息。

- * — dbname repo_dbname*

  指定存□配置文件的数据□的名称。□可以使用全局名称或系□□□符。

- * — host repo_host*

  指定存□□数据□所在主机的名称或 IP 地址。

- * —登□ *

  指定存□□登□□□信息。

- * 用□名 repo_username*

  指定□□存□□数据□所需的用□名。

- * 端口 repo_port*

  指定用于□□存□□数据□的□□控制□□（ Transmission Control Protocol， TCP ）端口号。

- * — operation ｛ -operationsoperation_name ｝ [operation_name1， operation_name2] | -all*

  指定要□其配置□史□□的 SnapManager 操作。

- * —保留 ｛ -countretain_count ｝ 个字： -dailydaily_count ； -monthly-monthly_count ； -weeklyweekly_count ｝ 个字

  指定□建□□，□□□□，□原和恢□以及□建和拆分克隆操作的保留□。保留□会根据操作□数，天数，周数或月数□行□置。

- * —静默 *

  在控制台中□□示□□消息。默□情况下会□示□□和警告消息。

- * —□□ *

  在控制台中□示□□，警告和信息性消息。

命令示例

以下示例□示了有□□□操作的信息：

```
smo history set -profile -name PROFILE1 -operation -operations backup
-retain -daily 6
 -verbose
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.