smo clone delete 命令

SnapManager Oracle

NetApp
August 06, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snapmanager-oracle/unix-administration/reference_the_smosmsapclone_delete_command.html on October 26, 2021.
Always check docs.netapp.com for the latest.

目□

smo clone delete 命令 1
□法 1
Parameters 1
示例 2

smo clone delete 命令

□可以□行 clone delete 命令□除克隆。如果克隆正在由任何操作使用，□不能□除□克隆。

□法

```
        smo clone delete
-profile profile_name
\[-id guid \| -label clone_name\]
[-login
\[-username db_username -password db_password -port db_port\]
 \[-asminstance -asmusername asminstance_username  -asmpassword
asminstance_password\]]
\[-syspassword syspassword\]
-force
\[-dump\]
\[-quiet \| -verbose\]
```

Parameters

- -profile profile_name*

  指定包含要□除的克隆的配置文件的名称。配置文件包含数据□的□□符和其他数据□信息。

- * —□制 *

  即使存在与克隆□□的□源，也会□除此克隆。

- * — id guid*

  指定要□除的克隆的 GUID 。GUID 由 SnapManager 在□建克隆□生成。□可以使用 smo clone list 命令□示□个克隆的 GUID 。

- * □□名称 *

  指定要□除的克隆的□□。

- * — asminstance*

  指定用于登□到自□存□管理（ Automatic Storage Management， ASM ）□例的凭据。

- * — asmusername asminstance_username*

  指定用于登□到 ASM □例的用□名。

- * — asmpassword asminstance_password*

  指定用于登□到 ASM □例的密□。

- * — sysspassword sysspassword*

  指定 sys 特□用□的密□。

  > 如果□ sys 特□用□提供的数据□凭据与□ sys 特□用□提供的数据□凭据不同，□必□□ sys 特□用□提供密□。

- * —登□ *

  用于□入数据□登□□□信息。

- * 用□名 db_username*

  指定□□数据□所需的用□名。

- * 密□ db_password*

  指定□□数据□所需的密□。

- * 端口 db_port*

  指定用于□□配置文件所述数据□的 TCP 端口号。

- * —□□ *

  指定在克隆□除操作后收集□□文件。

- * —静默 *

  在控制台中□□示□□消息。默□情况下会□示□□和警告消息。

- * —□□ *

  在控制台中□示□□，警告和信息性消息。

示例

以下示例将□除此克隆：

```
smo clone delete -profile SALES1 -label SALES_May
Operation Id [8abc01ec0e79004b010e79006da60001] succeeded.
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.