smo profile create 命令

SnapManager Oracle

NetApp
August 06, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/snapmanager-oracle/windows/reference_the_smosmsapprofile_create_command.html on October 26, 2021.
Always check docs.netapp.com for the latest.

目□

smo profile create 命令 1
□法 1
Parameters 2
示例 5

smo profile create 命令

□可以□行 profile create 命令在存□□中□建数据□的配置文件。在□行此命令之前，必□挂□数据□。

□法

```
        smo profile create
-profile profile
\[-profile-password profile_password\]
-repository
-dbname repo_service_name
-host repo_host
-port repo_port
-login -username repo_username
-database
-dbname db_dbname
-host db_host
[-sid  db_sid\]
[-login
\[-username db_username -password db_password -port db_port\]
 ]
[-rman \{-controlfile \| \{-login
-username  rman_username -password  rman_password\}
-tnsname  rman_tnsname\}\}]


[-retain
\[-hourly \[-count n\] \[-duration m\]\]
\[-daily \[-count n\] \[-duration m\]]
\[-weekly \[-count n\] \[-duration m\]]
\[-monthly \[-count n\] \[-duration m\]]]]
-comment comment
-snapname-pattern pattern
[]
[-summary-notification]
[-notification
\[-success
-email email_address1,email_address2
-subject subject_pattern\]
\[-failure
-email email_address1,email_address2
-subject subject_pattern]
[-separate-archivelog-backups
-retain-archivelog-backups
```

```
 -hours hours |
-days days |
-weeks weeks |
-months months
[]
[-include-with-online-backups \| -no-include-with-online-backups]]
[-dump]
[-quiet | -verbose]
```

Parameters

- * 配置文件配置文件 *

  指定配置文件的名称。此名称最□□ 30 个字符，并且在主机中必□是唯一的。

- -profile-password profile_password*

  指定配置文件的密□。

- * 存□□ *

  repository 后面的□□用于指定存□配置文件的数据□的□□信息。

- * — dbname repo_service_name*

  指定存□配置文件的数据□的名称。使用全局名称或 SID 。

- * — host repo_host*

  指定□行存□□数据□的主机□算机的名称或 IP 地址。

- * — SID db_sid*

  指定配置文件所描述的数据□的系□□□符。默□情况下， SnapManager 使用数据□名称作□系□□□符。如果系□□□符与数据□名称不同，□必□使用 -SID □□指定此□□符。

- * —登□ *

  指定存□□登□□□信息。

- * 用□名 repo_username*

  指定□□存□□数据□所需的用□名。

- * 端口 repo_port*

  指定用于□□存□□数据□的 TCP 端口号。

- * —数据□ *

  指定配置文件所描述的数据□的□□信息。□是要□□，□原或克隆的数据□。

- * — dbname db_dbname*

  指定配置文件所描述的数据□的名称。□可以使用全局名称或系□□□符。

- * — host db_host db_host*

  指定□行数据□的主机□算机的名称或 IP 地址。

- * —登□ *

  指定数据□登□□□信息。

- * 用□名 db_username*

  指定□□配置文件所述数据□所需的用□名。

- * 密□ db_password*

  指定□□配置文件所述数据□所需的密□。

- * 端口 db_port*

  指定用于□□配置文件所述数据□的 TCP 端口号。

- * — RMAN*

  指定 SnapManager 使用 Oracle Recovery Manager （ RMAN ）□□□□行目□□制□使用的□□信息。

- * —控制文件 *

  指定目□数据□控制文件，而不是目□作□ RMAN 存□□。

- * —登□ *

  指定 RMAN 登□□□信息。

- * 密□ RMAN_password*

  指定用于登□到 RMAN 目□的密□。

- * 用□名 RMAN_USERS*

  指定用于登□到 RMAN 目□的用□名。

- * — tnsname tnsname*

  指定 tnsnamname □接名称（在 tsname.ora 文件中定□）。

- * —保留□□□：□小□（ -hourly， -count n ），（ -duration m ），（ -daily， -count n ），（ -duration m ），（ -weekly， -count n ），（ -monthly， -count n ），（ -duration m ）， *

  指定□□的保留策略，其中一个或□个保留□数以及保留□的保留期限（□小□，□天，□周，□月）。

  □于□个保留□，可以指定保留□数或保留持□□□中的一个或□个。持□□□以□的□位□□位（例如，小□表示

□小□，天表示□天）。例如，如果用□□□日□□指定的保留期限□□ 7 ， □ SnapManager 不会限制配置文件的□日□□数（因□保留数量□ 0 ），但 SnapManager 会自□□除 7 天前□建的□日□□。

- * —注□注□ *

  指定用于描述配置文件域的配置文件的注□。

- * — snapname-pattern 模式 *

  指定 Snapshot 副本的命名模式。□□可以在所有 Snapshot 副本名称中包括自定□文本，例如，用于高可用性操作的 HAOPS 。□可以在□建配置文件□或□建配置文件后更改 Snapshot 副本命名模式。更新后的模式□□用于尚未□建的 Snapshot 副本。已存在的 Snapshot 副本会保留先前的 Snapname 模式。□可以在模式文本中使用多个□量。

- * —摘要通知 *

  指定□新配置文件□用摘要□子□件通知。

- -notification -success □子□件 e-mail_address1 ， □子□件地址 2 -Subject Subject_Pattern*

  指定□新配置文件□用□子□件通知，以便在 SnapManager 操作成功□收件人可以收到□子□件。□必□□新配置文件□入一个或多个□子□件地址以□送□子□件警□，并□入□子□件主□模式。

  □□可以□新配置文件包含自定□主□文本。□可以在□建配置文件□或□建配置文件后更改主□文本。更新后的主□□□用于未□送的□子□件。□可以□□子□件主□使用多个□量。

- -notification -failure -email e-mail_address1 ， e-mail2 -Subject Subject_Pattern*

  指定□新配置文件□用□子□件通知，以便在 SnapManager 操作失□□收件人可以接收□子□件。□必□□新配置文件□入一个或多个□子□件地址以□送□子□件警□，并□入□子□件主□模式。

  □□可以□新配置文件包含自定□主□文本。□可以在□建配置文件□或□建配置文件后更改主□文本。更新后的主□□□用于未□送的□子□件。□可以□□子□件主□使用多个□量。

- **-separate archivelog-backups**

  指定□□日志□□与数据文件□□分□。□是一个可□参数，□可以在□建配置文件□提供。使用此□□分□□□后，□可以□行□数据文件□□或□□□日志□□。

- -retain-archivelog-backups -hours | -daysdays | -weeksweeksweeks| -monthsmonths*

  指定根据□□日志保留期限（□小□，□天，□周，□月）保留□□日志□□。

- * —静默 *

  在控制台中□□示□□消息。默□情况下会□示□□和警告消息。

- * —□□ *

  在控制台中□示□□，警告和信息性消息。

- 加入□机□□ *

  指定□□日志□□与□机数据□□□一起包含。

- **-no-include-with -online-backups**

  指定□□日志□□不会与□机数据□□□一起包含。

- * —□□ *

  指定在成功□行配置文件□建操作后收集□□文件。

示例

以下示例□示了使用□小□保留策略和□子□件通知□建配置文件的□程：

```
smo profile create -profile test_rbac -profile-password netapp -repository
-dbname SMOREP -host hostname.org.com -port 1521 -login -username smorep
-database -dbname
RACB -host saal -sid racb1 -login -username sys -password netapp -port
1521 -rman -controlfile -retain -hourly -count 30 -verbose
Operation Id [8abc01ec0e78ebda010e78ebe6a40005] succeeded.
```

- 相□信息 *

管理配置文件以□□高效□□

Snapshot 副本命名

SnapManager 如何在本地存□上保留□□

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.