The smo clone split command

SnapManager Oracle

Aksel Davis
January 29, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapmanager-oracle/unix-administration/reference_the_smosmsap_clone_split_command.html on August 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

The smo clone split command 1
Syntax 1
Parameters 3

The smo clone split command

You can run the clone split command to split a clone. The split clone becomes independent of the original clone. SnapManager generates a new profile after the clone split operation and you can use this profile to manage the split clone.

Syntax

```
        smo clone split
-profile clone-profile
\[-host hostname\]
\{-label clone-label | -id clone-id\} \[-split-label split-
operation_label\]
\[-comment comment\]
-new-profile new-profile-name \[-profile-password new-profile_password\]
-repository -dbname repo_service_name
-host repo_host
-port repo_port
-login -username repo_username
-database -dbname db_dbname
-host db_host \[-sid db_sid\] \[-login -username db_username -password
db_password
-port db_port\]
\[-rman \{\{-controlfile \| \{-login -username rman_username
-password rman_password\} -tnsname rman_tnsname\}\}\]
-osaccount osaccount
-osgroup osgroup
\[-retain
\[-hourly \[-count n\] \[-duration  m\]\]
\[-daily \[-count n\] \[-duration m\]\]
\[-weekly  \[-count n\] \[-duration m\]\]
\[-monthly \[-count n\] \[-duration m\]\] \]
\[-profile-comment profile-comment\]
\[-snapname-pattern pattern\]
\[-protect \[-protection-policy policy_name\]\] \| \[-noprotect\]\]
\[-summary-notification
\[-notification
\[-success -email email_address1,email_address2
-subject subject-pattern\]
\[failure -email email_address1,email_address2
-subject subject-pattern\] \]
[-separate-archivelog-backups
-retain-archivelog-backups
 -hours  hours |
-days days |
-weeks weeks |
-months months
[-protect \[-protection-policy policy_name \| -noprotect]
[-include-with-online-backups \| -no-include-with-online-backups]]
[-dump]
\[-quiet \| -verbose\]
```

Parameters

- **-profile clone-profile**

  Specifies the profile name from which the clone is created.

- **-host hostname**

  Specifies the host name in which the clone exists.

- **-label clone-label**

  Specifies the label name generated by the clone operation.

- **-id clone-id**

  Specifies the unique ID generated by the clone operation.

- **-split-label split-operation_label**

  Specifies the label name generated by the clone operation.

- **-new-profile new-profile_name**

  Specifies the new profile name that SnapManager will generate after a successful split operation.

- **-profile-password new-profile_password**

  Specifies the password for the profile.

- **-repository**

  Specifies the details of the database for the repository.

- **-dbname repo_service_name**

  Specifies the name of the database that stores the repository. You can use either the global name or system identifier.

- **-host repo_host**

  Specifies the name or IP address of the host computer on which the repository database resides.

- **-port repo_port**

  Specifies the Transmission Control Protocol (TCP) port number used to access the host on which the repository database resides.

- **-login**

  Specifies the repository login details. This is optional. If not specified, SnapManager defaults to OS Authentication Connection Mode.

- **-username repo_username**

  Specifies the user name required to access the host on which the repository database resides.

- **-database**

  Specifies the details of the database that will be backed up, restored, or cloned.

- **-dbname db_dbname**

  Specifies the name of the database that the profile describes. You can use either the global name or system identifier.

- **-host db_host**

  Specifies the name or IP address of the host computer on which the database resides.

- **-sid db_sid**

  Specifies the system identifier of the database that the profile describes. By default, SnapManager uses the database name as the system identifier. If the system identifier is different from the database name, you must specify it using the -sid option.

  For example, if you are using Oracle Real Application Clusters (RAC), you must specify the system identifier of the RAC instance on the RAC node from which SnapManager is executed.

- **-login**

  Specifies the database login details.

- **-username db_username**

  Specifies the user name needed to access the database that the profile describes.

- **-password db_password**

  Specifies the password needed to access the database that the profile describes.

- **-rman**

  Specifies the details that SnapManager uses to catalog backups with Oracle Recovery Manager (RMAN).

- **-controlfile**

  Specifies the target database control files as the RMAN repository instead of a catalog.

- **-login**

  Specifies the RMAN login details.

- **-password rman_password**

  Specifies the password used to log in to the RMAN catalog.

- **-username rman_username**

  Specifies the user name used to log in to the RMAN catalog.

- **-tnsname tnsname**

Specifies the tnsname connection name (this is defined in the tsname.ora file).

- **-osaccount osaccount**

  Specifies the name of the Oracle database user account. SnapManager uses this account to perform the Oracle operations such as startup and shutdown. It is typically the user who owns the Oracle software on the host, for example, oracle.

- **-osgroup osgroup**

  Specifies the name of the Oracle database group name associated with the oracle account.

  > The -osaccount and -osgroup variables are required for UNIX but not allowed for databases running on Windows.

- **-retain [-hourly [-count n] [-duration m]] [-daily [-count n] [-duration m]] [-weekly [-count n] [-duration m]] [-monthly [-count n] [-duration m]]**

  Specifies the retention policy for a backup.

  For each retention class, either or both the retention count or retention duration might be specified. The duration is in units of the class (for example, hours for hourly, days for daily). For instance, if you specify only a retention duration of 7 for daily backups, then SnapManager will not limit the number of daily backups for the profile (because the retention count is 0), but SnapManager will automatically delete daily backups created over 7 days ago.

- **-profile-comment profile-comment**

  Specifies the comment for a profile describing the profile domain.

- **-snapname-pattern pattern**

  Specifies the naming pattern for Snapshot copies. You can also include custom text, for example, HAOPS for highly available operations, in all Snapshot copy names. You can change the Snapshot copy naming pattern when you create a profile or after the profile has been created. The updated pattern applies only to Snapshot copies that have not yet been created. Snapshot copies that exist retain the previous Snapname pattern. You can use several variables in the pattern text.

- **-protect -protection-policy policy_name**

  Specifies whether the backup should be protected to secondary storage.

  > If -protect is specified without -protection-policy, then the dataset will not have a protection policy. If -protect is specified and -protection-policy is not set when the profile is created, then it may be set later by the smo profile update command or set by the storage administrator by using the Protection Manager's console.

- **-summary-notification**

  Specifies the details for configuring summary email notification for multiple profiles under a repository database. SnapManager generates this email.

- **-notification**

  Specifies the details for configuring email notification for the new profile. SnapManager generates this

email. The email notification enables the database administrator to receive emails on the succeeded or failed status of the database operation that is performed by using this profile.

- **-success**

  Specifies that email notification is enabled for a profile for when the SnapManager operation succeeds.

- **-email email address 1 email address 2**

  Specifies the email address of the recipient.

- **-subject subject-pattern**

  Specifies the email subject.

- **-failure**

  Specifies that email notification is enabled for a profile for when the SnapManager operation fails.

- **-separate-archivelog-backups**

  Specifies that the archive log backup is separated from the datafile backup. This is an optional parameter, which you can provide while creating the profile. After the backups are separated by using this option, you can either create datafiles-only backup or archive logs-only backup.

- **-retain-archivelog-backups -hours hours | -daysdays | -weeksweeks| -monthsmonths**

  Specifies that the archive log backups are retained based on the archive log retention duration (hourly, daily, weekly, or monthly).

- **protect [-protection-policypolicy_name] | -noprotect**

  Specifies that the archive log files is protected based on the archive log protection policy.

  Specifies that the archive log files are not protected by using the -noprotect option.

- **-include-with-online-backups | -no-include-with-online-backups**

  Specifies that the archive log backup is included along with the online database backup.

  Specifies that the archive log backups are not included along with the online database backup.

- **-dump**

  Specifies that the dump files are not collected after the successful profile create operation.

- **-quiet**

  Displays only error messages in the console. The default setting displays error and warning messages.

- **-verbose**

  Displays error, warning, and informational messages in the console.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.