The smo clone create command

SnapManager Oracle

Aksel Davis
January 29, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapmanager-oracle/unix-administration/reference_the_smosmsapclone_create_command.html on August 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

The smo clone create command 1
Syntax 1
Parameters 1
Example 4

The smo clone create command

You can run the clone create command to create a clone of a backed-up database. You can clone a backup from primary or secondary storage.

Syntax

```
        smo clone create
-profile profile_name
[-backup-id backup_guid \| -backup-label backup_label_name \| -current\]
-newsid new_sid
\[-host target_host\]
[-label clone_label]
\[-comment string\]
-clonespec full_path_to_clonespec_file
\[-asminstance -asmusername asminstance_username  -asmpassword
asminstance_password\]]
\[-syspassword syspassword\]
\[-reserve \{yes \| no \| inherit\}\]
\[-from-secondary \{-copy-id id\}\]
\[-no-resetlogs \| -recover-from-location path1 \[, path2\]\]\[-taskspec
taskspec\]
\[-dump\]
\[-quiet \| -verbose\]
```

Parameters

- **-profile name**

  Specifies the database that you want to clone. The profile contains the identifier of the database and other database information.

- **-backup-id guid**

  Clones the backup with the specified GUID. The GUID is generated by SnapManager when you create a backup. You can use the smo backup list-verbose command to display the GUID for each backup.

- **-backup-label backup_label_name**

  Specifies to clone the backup with the specified label name.

- **-current**

  Specifies to create backup and clone from the current state of the database.

  If the database is in the noarchivelog mode, SnapManager will create an offline backup.

- **-newsid new_sid**

  Specifies a new, unique Oracle system identifier for the cloned database. The system identifier value is a maximum of eight characters. Oracle does not allow running two databases with the same system identifier on the same host simultaneously.

- **-host target_host**

  Specifies the host on which the clone should be created.

- **-label clone_label**

  Specifies a label for the clone.

- **-comment string**

  Specifies an optional comment to describe this clone. You must enclose the string within single quotation marks.

  > Some shells delete the quotation marks. If that is true for your shell, you must escape the quotation with a backslash (\). For example, you might need to enter: \' this is a comment\'

- **-clonespec full_path_to_clonespec_file**

  Specifies the path to the clone specification XML file. This can be a relative or an absolute path name.

- **-asminstance**

  Specifies the credentials that are used to log in to the ASM instance.

- **-asmusername asminstance_username**

  Specifies the user name that is used to log in to the ASM instance.

- **-asmpassword asminstance_password**

  Specifies the password that is used to log in to ASM instance.

- **-syspassword syspassword**

  Specifies the password for the sys privileged user.

  > You must provide the password for the sys privileged user if the database credentials that are provided are not the same for the sys privileged user.

- **-reserve**

  Setting the -reserve option to yes ensures that the volume guarantee space reserve is turned on for the new clone volumes. Setting the -reserve option to no ensures that the volume guarantee space reserve is turned off for the new clone volumes. Setting the -reserve option to inherit ensures that the new clone inherits the space reservation characteristics of the parent Snapshot copy. The default setting is no.

  The following table describes the cloning methods and their effect on the clone create operation and its -reserve option. A LUN can be cloned by using either method.

Cloning method	Description	Result
`LUN cloning`	`A new clone LUN is created within the same volume.`	`When the -reserve option for a LUN is set to yes, space is reserved for the full LUN size within the volume.`
`Volume cloning`	`A new FlexClone is created, and the clone LUN exists within the new clone volume. Uses the FlexClone technology.`	`When the -reserve option for a volume is set to yes, space is reserved for the full volume size within the aggregate.` +

- **-from-secondary [-copy-idcopy_id]**

  Specifies that SnapManager should clone a copy of a backup that has been protected to secondary storage. If this option is not specified, SnapManager clones the copy from primary storage.

  You must specify the -copy-id option whenever you specify the -from-secondary option. If there is more than one backup on the secondary storage system, the -copy-id option is used to specify which backup copy on the secondary storage should be used for cloning.

  > If you are using Data ONTAP operating in 7-Mode, you must specify a valid value for the -copy-id option. However, if you are using clustered Data ONTAP, the -copy-id option is not required.

- **-no-resetlogs**

  Specifies to skip recovering the database, executing the DBNEWID utility, and not opening the database with the resetlogs while creating the clone.

- **-recover-from-location**

  Specifies the external archive log location of the archive log backups where SnapManager takes the archive log files from the external location and uses them for cloning.

- **-taskspec**

  Specifies the task specification XML file for preprocessing activity or post-processing activity of the clone operation. You must provide the complete path of the task specification XML file.

- **-dump**

  Specifies to collect the dump files after the clone create operation.

- **-quiet**

  Displays only error messages in the console. The default setting is to display error and warning messages.

- **-verbose**

  Displays error, warning, and informational messages in the console.

Example

The following example clones the backup by using a clone specification that is created for this clone:

```
smo clone create -profile SALES1 -backup-label full_backup_sales_May
-newsid
CLONE -label sales1_clone -clonespec
/opt/<path>/smo/clonespecs/sales1_clonespec.xml
```

```
Operation Id [8abc01ec0e794e3f010e794e6e9b0001] succeeded.
```

Related information

Creating clone specifications

Cloning databases from backups

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.