Updating profiles

SnapManager Oracle

Aksel Davis
February 05, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapmanager-oracle/unix-administration/task_updating_profiles.html on August 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Updating profiles 1

Updating profiles

You can update the profiles to modify the profile password, the number of backups to retain, access to the database, the operating system (OS) authentication to database authentication and vice versa, and information about the host. If the Oracle database password information changes, you must also change that information in the profile.

If protection policy is enabled on the profile, you cannot change the policy by using SnapManager. The storage administrator must change the policy by using the Protection Manager's console.

SnapManager (3.2 or later) enables you to update the profile to separate archive log backups from the data file backups by using the -separate-archivelog-backups option. You can specify separate retention durationand protection policy for the archive log backup. SnapManager enables you to include the archive log backup along with online database backup. You can also create an online datafile backup and archive log backup together for cloning. When you create an online data files backup, the archive logs backups are immediately created along with the data files.

1. Enter the following command: `smo profile update -profileprofile [-new-profilenew_profile_name] [-profile-passwordprofile_password][-database-dbnamedb_dbname-host db_host [-siddb_sid] [-login -usernamedb_username -password db_password-port db_port][-asminstance-asmusernameasminstance_username-asmpasswordasminstance_password]] [{-rman{-controlfile | {-login -usernamerman_username-password rman_password-tnsname rman_tnsname}}} | -remove-rman]-osaccountosaccount-osgrouposgroup [-retain [-hourly [-countn] [-durationm]] [-daily [-countn] [-durationm]] [-weekly [-countn] [-durationm]] [-monthly [-countn] [-durationm]]] [-commentcomment][-snapname-patternpattern][[-protect [-protection-policypolicy_name]]| [[-noprotect]] [-summary-notification] [-notification [-success-emailemail_address1, email_address2-subjectsubject_pattern] [-failure-emailemail_address1, email_address2-subjectsubject_pattern]] [-separate-archivelog-backups-retain-archivelog-backups-hourshours | -daysdays | -weeksweeks| -monthsmonths [-protect [-protection-policypolicy_name] | -noprotect] [-include-with-online-backups | -no-include-with-online-backups]] [-dump]`

   Other options for this command are as follows:

   [-force] [-noprompt]

If you want to…	Then…
Change the profile to use operating system authentication	Instead of adding the user name, password, and port, specify the following: • -osaccountaccount_name as the name of the operating system account • -osgrouposgroup as the group associated with the operating system account, typically the account used to install Oracle

If you want to…	Then…
Use Automatic Storage Management (ASM) instance authentication to create the profile	Specify the credentials for ASM instance authentication. • -asmusernameasminstance_username is the user name used to log in to the ASM instance. • -asmpasswordasminstance_password is the password used to log in to the ASM instance.
Use a catalog as the Oracle Recovery Manager (RMAN) repository, or you want to remove RMAN	Specify the following options and variables: • -tnsname tnsname as the tnsname defined in the tnsnames.ora file. • -login -username username as the user name required to connect to the RMAN catalog. If not specified, SnapManager uses the operating system authentication information. You cannot use operating system authentication with Real Application Clusters (RAC) databases. • -passwordpassword as the RMAN password required to connect to the RMAN catalog. • -controlfile if you are using the control file as the RMAN repository. • -remove-rman to remove RMAN.
Change the backup retention policy for backups of the database in the profile	Specify either the retention count or retention duration for a retention class, or both to change the retention policy. The duration is in units of the class (for example, hours for hourly, days for daily). • -hourly is the hourly retention class, for which [-countn] [-durationm]] are the retention count and retention duration, respectively. • -daily is the daily retention class, for which [-countn] [-durationm]] are the retention count and retention duration, respectively. • -weekly is the weekly retention class, for which [-countn] [-durationm]] are the retention count and retention duration, respectively. • -monthly is the monthly retention class, for which [-countn] [-durationm]] are the retention count and retention duration, respectively.

If you want to…	Then…
Disable backup protection for the profile	Specify -noprotect to not protect the database backups created by using the profile. For a profile that had -protect enabled, if you want to disable protect, a warning message is displayed stating that this action will delete the dataset and you will not be able to restore or clone backups for this profile.
Enable email notifications for the completion status of the database operations	Specify the following options and variables: • -summary-notification enables you to configure a summary email notification for multiple profiles under a repository database. • -notification enables you to receive an email notification on the completion status of the database operation for a profile. • -success-emailemail_address2 enables you to receive an email notification following the completion of a successful database operation performed by using a new or an existing profile. • -failure-emailemail_address2 enables you to receive an email notification on a failed database operation performed by using a new or an existing profile. • -subjectsubject_text specifies subject text for the email notification while creating a new profile or an existing profile. If the notification settings are not configured for the repository and you are trying to configure profile or summary notifications by using the command-line interface (CLI), the following message is logged in the console log: SMO-14577: Notification Settings not configured. If you have configured the notification settings and you are trying to configure summary notification by using the CLI without enabling summary notification for the repository, the following message is logged in the console log: SMO-14575: Summary notification configuration not available for this repository**

If you want to…	Then…
Update the profile to create backup of the archive log files separately	Specify the following options and variables: • -separate-archivelog-backups enables you to create a backup of the archive log files separately from the database files. After you specify this option, you can either create a data files-only backup or an archivelogs-only backup. You cannot create a full backup. Also, you cannot revert the profile settings by separating the backup. SnapManager retains the backups based on the retention policy for the backups that were created before taking archivelogs-only backup. • -retain-archivelog-backups sets the retention duration for archive log backups. If you are updating the profile for the first time, you can separate the archive log backups from the data files backup by using the -separate -archivelog-backups option; you must provide the retention duration for the archive log backups by using the -retain-archivelog -backups option. Setting the retention duration is optional when you later update the profile. • -protect creates an application dataset in the Data Fabric Manager (DFM) server and adds members related to the database, data file, control files, and archive logs. If the dataset exists, it is reused when a profile is created. • -protection-policy sets the protection policy to the archive log backups. • -include-with-online-backups specifies that the archive log backup is included along with the database backup. • -no-include-with-online-backups specifies the archive log file backup is not included along with the database backup.

If you want to…	Then…
Change the host name of the target database	Specify -hostnew_db_host to change the host name of the profile.
Collect the dump files after the profile update operation	Specify the -dump option.

2. To view the updated profile, enter the following command: `smo profile show`

Related information

How to collect dump files

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.