Troubleshooting known issues

SnapManager Oracle

Aksel Davis, Zachary Wambold
February 24, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapmanager-oracle/windows/reference_troubleshooting_known_issues.html on August 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Troubleshooting known issues . . . 1
SnapManager for Oracle fails to identify Cluster-Mode profiles . . . 1
The server fails to start . . . 1
Unable to manage archive log file destination names if the destination names are part of other destination names . . . 2
Repository database size grows with time and not with the number of backups . . . 2
The SnapManager GUI cannot be accessed and SnapManager operations fail when the repository database is down . . . 2
Unable to create temporary files for the cloned database . . . 3
Back up of Data Guard Standby database fails . . . 4

Troubleshooting known issues

You should be aware of some known issues that might occur when you use SnapManager, and how to work around them.

SnapManager for Oracle fails to identify Cluster-Mode profiles

If the Cluster-Mode profile name is not present in the cmode_profiles.config file in the SnapManager for Oracle installation directory, the following error message might trigger:

Please configure DFM server using snapdrive config set -dfm user_name appliance_name.

Also, while upgrading the SnapManager for Oracle, if you delete the /opt/NetApp/smo/* folder, then the cmode_profiles.config file that has the Cluster-Mode profile names also get deleted. This issue also triggers the same error message.

Workaround

Update the profile: smo profile update-profile <profile_name>

> If SnapManager for Oracle is installed in the /opt/NetApp/smo/ path, then the file location is /opt/NetApp/smo/cmode_profile/cmode_profiles.config.

The server fails to start

When starting the server, you might see an error message similar to the following:

SMO-01104: Error invoking command: SMO-17107: SnapManager Server failed to start on port 8074 because of the following errors: java.net.BindException: Address already in use

This might be because the SnapManager listening ports (27214 and 27215, by default) are currently in use by another application.

This error can also occur if the smo_server command is already running, but SnapManager does not detect the existing process.

Workaround

You can reconfigure either SnapManager or the other application to use different ports.

To reconfigure SnapManager, edit the following file: C:\Program Files\NetApp\SnapManager for Oracle\properties\smo.config

You assign the following values:

- SMO Server.port=27214
- SMO Server.rmiRegistry.port=27215
- remote.registry.ocijdbc.port= 27215

  The remote.registry.ocijdbc.port must be the same as Server.rmiRegistry.port.

To start the SnapManager server, perform the following steps:

1. Click **Start** > **Control Panel** > **Administrative Tools** > **Services**.
2. You can start the server in one of three ways:
    - In the left panel, click **Start**.
    - Right-click NetApp SnapManager 3.3 for Oracle and select **Start** from the drop-down menu.
    - Double-click NetApp SnapManager 3.3 for Oracle and in the Properties window that opens, click **Start**.

Unable to manage archive log file destination names if the destination names are part of other destination names

While creating an archive log backup, if the user excludes a destination that is part of other destination names, then the other destination names are also excluded.

For example, assume that there are three destinations available to be excluded: E:\\arch, G:\\arch, and H:\\arch. While creating the archive log file backup, if you exclude E:\\arch by using the command

```
smo backup create -profile almsamp1 -data -online -archivelogs  -exclude
-dest E:\\arch
```

, SnapManager for Oracle excludes all the destinations starting with E:\\arch.

Workaround

- Add a path separator after destinations are configured in v$archive_dest. For example, change the E:\\arch to E:\\arch\.
- While creating a backup, include destinations instead of excluding any destination.

Repository database size grows with time and not with the number of backups

The repository database size grows with time because SnapManager operations insert or delete data within the schema in the repository database tables, which results in high index space usage.

Workaround

You must monitor and rebuild the indexes according to the Oracle guidelines to control the space consumed by the repository schema.

The SnapManager GUI cannot be accessed and SnapManager operations fail when the repository database is down

SnapManager operations fail and you cannot access the GUI when the repository database is down.

The following table lists the different actions you might want to perform, and their exceptions:

Operations	Exceptions
Opening a closed repository	The following error message is logged in sm_gui.log: [WARN]: SMO-01106: Error occurred while querying the repository: Closed Connection java.sql.SQLException: Closed Connection.
Refreshing an opened repository by pressing F5	A repository exception is displayed in the GUI and also logs a NullPointerException in the sm_gui.log file.
Refreshing the host server	A NullPointerException is logged in the sumo_gui.log file.
Creating a new profile	A NullPointerException is displayed in the Profile Configuration window.
Refreshing a profile	The following SQL exception is logged in sm_gui.log: [WARN]: SMO-01106: Error occurred while querying the repository: Closed Connection.
Accessing a backup	The following error message is logged in sm_gui.log: Failed to lazily initialize a collection.
Viewing clone properties	The following error message is logged in sm_gui.log and sumo_gui.log: Failed to lazily initialize a collection.

Workaround

You must ensure that the repository database is running when you want to access the GUI or want to perform any SnapManager operations.

Unable to create temporary files for the cloned database

When temporary tablespace files of the target database are placed in mount points different from the mount point of the data files, the clone create operation is successful but SnapManager fails to create temporary files for the cloned database.

Workaround

You must perform either of the following:

- Ensure that the target database is laid out so that temporary files are placed in the same mount point as that of the data files.
- Manually create or add temporary files in the cloned database.

Back up of Data Guard Standby database fails

If any archive log location is configured with the service name of the primary database, the back up of Data Guard Standby database fails.

Workaround

In the GUI, you must clear **Specify External Archive Log location** corresponding to the service name of the primary database.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.