Creating database backups

SnapManager Oracle

Aksel Davis, Zachary Wambold
February 24, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapmanager-oracle/windows/task_creating_database_backups.html on August 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Creating database backups 1
Example 8

Creating database backups

You can create backups of entire databases or portions of databases, including tablespaces, data files, or control files.

Administrators can optionally register backups with Oracle RMAN, which facilitates the use of RMAN to restore and recover the database at finer granularities such as blocks.

While defining the profile, you can customize the names of the Snapshot copies created by backups of that profile. For example, you might insert a prefix string of HOPS to denote High Operations backups.

In addition to defining unique names for Snapshot copies created by backups, you can also create unique labels for the backups themselves. When you create a backup, it is a good practice to supply a name for the backup so you have an easy way to identify it by using the -label parameter. This name must be unique for all backups created within a particular profile. The name can contain letters, numbers, underscore (_), and hyphen (-). It cannot start with a hyphen. Labels are case-sensitive. You might want to append information such as operating system environment variables, system date, and backup type.

If you do not supply a label, SnapManager creates a default label name in the form scope_mode_datestring, where scope is full or partial and mode is offline, online, or automatic (the letter c for cold, h for hot, or a for automatic).

From SnapManager 3.4, you can provide your own backup label by overriding the default backup label created by SnapManager. You must set the value of the override.default.backup.pattern parameter to true and specify the new backup label in the new.default.backup.pattern parameter. The backup label pattern can contain keywords such as database name, profile name, scope, mode and hostname, which has to be separated by underscore. For example, new.default.backup.pattern=dbname_profile_hostname_scope_mode.

The timestamp will be included automatically at the end of the generated label.

When you enter a comment, you can include spaces and special characters. In contrast, when you enter a label, do not include spaces or special characters.

For each backup, SnapManager automatically generates a GUID, which is a 32-character HEX string. To determine the GUID, you must run the backup list command with the -verbose option.

You can create a full backup of a database while it is online or offline. To let SnapManager handle backing up a database regardless of whether it is online or offline, you should use the -auto option.

While creating a backup, if you have enabled pruning and the summary notification was enabled in the profile, two separate emails are triggered. One email is for the backup operation and the other for the pruning. You can correlate these emails by comparing the backup name and backup ID contained in these emails.

You can create a cold backup when the database is in the shutdown state. If the database is in a mounted state, change it to a shutdown state and perform the offline backup (cold backup).

SnapManager (3.2 or later) enables you to back up the archive log files separately from the data files, enabling you to manage the archive log files efficiently.

To create the archive log backups separately, you must create a new profile or update the existing profile to separate the archive log backups by using the -separate-archivelog-backups option. Using the profile, you can perform the following SnapManager operations:

- Create an archive log backup.
- Delete an archive log backup.
- Mount an archive log backup.
- Free an archive log backup.

The backup options vary depending on the profile settings:

- Using a profile that is not separated to take archive log backups separately allows you to do the following:
  - Create a full backup.
  - Create a partial backup.
  - Specify archive log destinations to be backed up for archive log files.
  - Specify archive log destinations to be excluded from the backup.
  - Specify the pruning options for deleting the archive log files from the archive log destinations.
- Using a profile that is separated to take archive log backups allows you to do the following:
  - Create a data files-only backup.
  - Create an archivelogs-only backup.
  - While creating a data files-only backup, include the archive log backup along with the online data files only backup for cloning.

    If you have included archive log backups along with data files in the **Profile Settings** page of the **Profile Create** wizard from the SnapManager GUI, and if you have not selected the **Archivelogs** option in the **Backup Create** wizard, SnapManager always creates the archive log backup along with data files for all online backups.

    In such a situation, from the SnapManager CLI, you can consider all the archive log destinations for backup except for the exclude destinations specified in the SnapManager configuration file. But you cannot prune these archive log files. However, you can still use the -archivelogs option to specify the archive log file destination and prune the archive log files from the SnapManager CLI.

    If you are creating the backup using the -auto option and specify the --archivelogs option, SnapManager creates either an online or offline backup based on the current status of the backup.

    - SnapManager creates an offline backup when the database is offline and does not include the archive log files in the backup.
    - SnapManager creates an online backup including archive log files when the database is online.
  - While creating the archivelogs-only backup:
    - Specify the archive log destination to be backed up along with the archivelogs-only backup
    - Specify the archive log destinations to be excluded from the archive logs-only backup
    - Specify the pruning options for deleting the archive log files from the archive log destinations
- **Scenarios not supported**
  - You cannot create the archivelog-only backup along with an offline data files-only backup.
  - You cannot prune the archive log files when the archive log files are not backed up.
  - You cannot prune the archive log files when Flash Recovery Area (FRA) is enabled for archive log files.

    If you specify the archive log location in Flash Recovery Area, you must ensure that you also specify

the archive log location in the archive_log_dest parameter.

> While creating archive log backups, you must enter the full archive log destinations paths within double quotation marks and the destination paths separated by commas. The path separator should be given as two backslashes (\\) instead of one.

When you specify the label for online data files backup with included archive log backup, the label is applied for data files backup, and the archive log backup will be suffixed with (_logs). This suffix can be configured by changing the parameter suffix.backup.label.with.logs parameter in the SnapManager configuration file.

For example, you can specify the value as suffix.backup.label.with.logs=arc so that the _logs default value is changed to _arc.

If you have not specified any archive log destinations to be included in the backup, then SnapManager includes all the archive log destinations configured in the database.

If any archive log files are missing in any one of the destinations, SnapManager skips all these archive log files created before the missing archive log files even if these files are available in other archive log destination.

While creating archive log backups, you must specify the archive log file destinations to be included in the backup, and can set the configuration parameter to include the archive log files always beyond the missing files in the backup.

> By default, this configuration parameter is set to true to include all the archive log files, beyond missing files. If you are using your own archive log pruning scripts or manually deleting archive log files from the archive log destinations, you can disable this parameter, so that SnapManager can skip the archive log files and proceed further with the backup.

SnapManager does not support the following SnapManager operations for archive log backups:

- Clone the archive log backup
- Restore archive log backup
- Verify archive log backup

SnapManager also supports backing up the archive log files from the flash recovery area destinations.

1. Enter the following command: smo backup create -profile profile_name {[-full {-online | -offline | -auto} [-retain {-hourly | -daily | -weekly | -monthly | -unlimited}] [-verify] | [-data [[-filesfiles [files]] | [-tablespaces-tablespaces [-tablespaces]] [-datalabellabel] {-online | -offline | -auto} [-retain {-hourly | [-daily | -weekly | -monthly | -unlimited]} [-verify] | [-archivelogs [-labellabel] [-commentcomment] [-backup-destpath1 [,[path2]]] [-exclude-destpath1 [,path2]]] [-prunelogs {-all | -untilSCNuntilSCN | -until-date yyyy-MM-dd:HH:mm:ss | -before {-months | -days | -weeks | -hours}} -prune-destprune_dest1,[prune_dest2]] [-taskspectaskspec]} [-dump] [-force] [-quiet | -verbose]

If you want to…	Then…
Specify whether you want to take a backup of an online or offline database, rather than allowing SnapManager to handle whether it is online or offline	Specify -offline to take a backup of the offline database. Specify -online to take a backup of the online database. + If you use these options, you cannot use the -auto option.

Specify whether you want to let SnapManager handle backing up a database regardless of whether it is online or offline	Specify the -auto option. If you use this option, you cannot use the --offline or -online option.

Specify whether you want to perform a partial backup of specific files	`Specify the -data-files option and then list the files, separated by commas. For example, list the file names f1, f2, and f3 after the option.`
	
	+ Example for creating a partial datafile backup on Windows
	
	+
	
	`smo backup create -profile nosep -data -files "J:\\mnt\\user\\user.dbf" -online -label partial_datafile_backup -verbose`

Specify whether you want to perform a partial backup of specific tablespaces	`Specify the -data-tablespaces option and then list the tablespaces, separated by commas. For example, use ts1, ts2, and ts3 after the option.`
	
	+ SnapManager supports backing up of read-only tablespaces. While creating the backup, SnapManager changes the read-only table spaces to read-write. After creating the backup, the tablespaces are changed to read-only.
	
	+ Example for creating a partial tablespace backup
	
	+
	
	`smo backup create -profile nosep -data -tablespaces tb2 -online -label partial_tablespace_bkup -verbose`

Specify whether you want to create a unique label for each backup in the following format: full_hot_mybackup_label	`For Windows, you might enter this example:`
	
	+
	
	`smo backup create -online -full -profile targetdb1_prof1 -label full_hot_my_backup_label -verbose`

Specify whether you want to create backup of the archive log files separately from the data files	`Specify the following options and variables:`
	
	• -archivelogs creates a backup of the archive log files.
	• -backup-dest specifies the archive log file destinations to be backed up.
	• -exclude-dest specifies the archive log destinations to be excluded.
	• -label specifies the label for the archive log file backup. **Note:** You must provide either the -backup-dest option or the -exclude-dest option.
	
	Providing both these options together along with the backup displays error message You have specified an invalid backup option. Specify any one of the options: -backup-dest, or exclude-dest.
	
	Example for creating archive log file backups separately on Windows
	
	`smo backup create -profile nosep -archivelogs -backup -dest "J:\\mnt\\archive_dest_2\\" -label archivelog_backup -verbose`

Specify whether you want to create backup of data files and archive log files together	`Specify the following options and variables:`
	
	• -data option to specify the data files.
	• -archivelogs option to specify the archive log files. Example for backing up data files and archive log files together on Windows
	
	`smo backup create -profile nosep -data -online -archivelogs -backup-dest "J:\\mnt\\archive_dest_2\\" -label data_arch_backup -verbose`

Specify whether you want to prune the archive log files while creating a backup	`Specify the following options and variables:`
	
	• -prunelogs specifies to delete the archive log files from the archive log destinations.
	  ◦ -all specifies to delete all the archive log files from the archive log destinations.
	  ◦ -until-scnuntil-scn specifies to delete the archive log files until a specified SCN.
	  ◦ -until-dateyyyy-MM-dd:HH:mm:ss specifies to delete the archive log files until the specified time period.
	  ◦ -before option specifies to delete the archive log files before the specified time period (days, months, weeks, hours).
	  ◦ -prune-destprune_dest1,[prune_dest2 specifies to delete the archive log files from the archive log destinations while creating the backup. **Note:** You cannot prune the archive log files when Flash Recovery Area (FRA) is enabled for archive log files.
	Example for pruning all archive log files while creating a backup on Windows
	+
	`smo backup create -profile nosep -archivelogs -label archive_prunebackup1 -backup -dest "E:\\oracle\\MDV\\oraarch\\MDVarch,J:\\" -prunelogs -all -prune-dest "E:\\oracle\\MDV\\oraarch\\MDVarch,J:\\" -verbose`

Specify whether you want to add a comment about the backup	Specify -comment followed by the description string.
Specify whether you want to force the database into the state you have specified to back it up, regardless of the state it is currently in	Specify the -force option.

Specify whether you want to verify the backup at the same time you create it	Specify the -verify option.
Specify whether you want to collect the dump files after the database backup operation	Specify -dump option at the end of the backup create command.

Example

```
smo backup create -profile targetdb1_prof1 -full -online -force  -verify
```

Related information

Snapshot copy naming

Creating pretask, post-task, and policy scripts

Creating task scripts

Storing the task scripts

The smo backup create command

Creating or updating the post scripts

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.