



# Deployments

## Virtual Desktop Service

NetApp  
July 20, 2021

This PDF was generated from [https://docs.netapp.com/us-en/virtual-desktop-service/Management.Deployments.provisioning\\_collections.html](https://docs.netapp.com/us-en/virtual-desktop-service/Management.Deployments.provisioning_collections.html) on July 20, 2021. Always check [docs.netapp.com](https://docs.netapp.com) for the latest.

# Table of Contents

- Deployments ..... 1
  - Provisioning Collections ..... 1
  - VDS Logical Hierarchy Overview ..... 10

# Deployments

## Provisioning Collections


### Overview

Provisioning Collections is a function of VDS related to the creation and management of VM images.

**At a high level, the Provisioning Collection workflow is as follows:**

1. A temporary VM (e.g. "CWT1") is built based on an existing image (either a stock image or a previously saved Provisioning Collection).
2. The VDS Administrator customizes the temporary VM to match their requirements using [Scripted Events](#), [Connect to Server](#) and/or 3rd party management tools.
3. Once customized, the VDS Admin click **Validate** and triggers a validation process that automates finalizing the image, running SysPrep, deleting the temporary VM and making the image available for deployment throughout VDS.

### Video Demo - Managing VM images for VDI Session Hosts



### Provisioning Collection Types

There are two distinct types of collection with specific use cases, **Shared** and **VDI**.

#### Shared


The **Shared** type is a collection of VM images(s) designed to deploy an entire environment with multiple, distinct VM images and VM roles.

## VDI

The **VDI** type is a single VM image designed to be used and reused to deploy multiple identical VMs, typically used for hosting user sessions. For all types of AVD session hosts, the **VDI** type should be selected, even for hosts that run multiple sessions per VM.

### Creating a new Provisioning Collection

Provisioning Collections are found in the VDS interface within each deployment, under the **Provisioning Collections** sub-tab.



#### To create a new collection

1. Click the **+ Add Collection** button.
2. Complete the following fields:
  - a. **Name**
  - b. **Description**(Optional)
  - c. **Type** - Shared or VDI
  - d. **Operating System**
  - e. **Share Drive** - If this VM will be used to host users profiles or company share data, pick the drive letter on which is will be hosted. If not, leave as "C"
  - f. **Minimum Cache** - IF you and VDS to create VMs to hold for instant deployment, specify the minimum number of cached VMs that should be maintained. If deploying new VMs can wait for as long as it takes the hypervisor to build a VM, this can be set to "0" to save costs.
  - g. **Add Servers**
    - i. **Role** (If "Shared" type is selected)
      - A. **TS** - This VM will act only as a session host
      - B. **Data** - This VM will not host any user sessions
      - C. **TSDData** - This VM will be both the session host and the storage host (Maximum: one TSDData per workspace)
    - ii. **VM Template** - Select from the available list, both stock hypervisor images and previously saved Provisioning Collections are available to select.
      - A. NOTE: Windows 7 images from the Azure Marketplace do not have PowerShell Remoting enabled. To use a Windows 7 image, you'll need to provide a custom image in your shared image gallery with powerShell Remoting enabled.
      - B. NOTE: By using an existing Provisioning Collection you can update and re-deploy existing images as part of a planned image upgrade process.
    - iii. **Storage Type** - Select the speed of the OS disk considering cost and performance
    - iv. **Data Drive** - Optionally enable a 2nd disk attached to this image, typically for the data storage layer referenced above in 2.e.
      - A. **Data Drive Type** - Select the speed of the 2nd (data) disk considering cost and performance

B. **Data Drive Size (GB)** - Define the size of the 2nd (data) disk considering capacity, cost and performance

h. **Add Applications** - Select any application from the Application Library that will be (1) installed on this image and (2) managed by VDS application entitlement. (This is only applicable to RDS deployments. It should remain empty for AVD workspaces)

## Customizing the Temporary VM

VDS includes functionality that will allow remove VM access from within the VDS web interface. By default a local Windows admin account is created with a rotating password and passed through to the VM allowing the VDS admin local admin access without needing to know local admin credentials.



The Connect to Server function has an alternative setting where the VDS admin will be prompted for credentials with each connection. This setting can be enabled/disabled by editing the VDS admin account from within the "Admin" section of VDS. the functionality is called *Tech Account* and checking the box will require credential to be entered when using Connect to Server, unchecking this box will enable the automatic injection of local Windows admin credentials at each connection.

The VDS Admin simply needs to connect to the temporary VM using Connect to Server or another process and make the changes required to meet their requirements.

## Validating the Collection

Once customization is complete, the VDS Admin can close the image and SysPrep it by clicking **Validate** from the Actions icon.

VDS Documentation  
Virtual Desktop  
Service

Home  
Organizations  
Deployments  
Workspaces  
App Services  
Service Board  
Scripted Events  
Admins  
Reports  
Applications  
Cost Estimator  
SaaS Backup

Search

TV Toby

Home > Deployments > VDSazuredemo... > Provisioning Collections

**VDSazuredemo.onmicros...**  
Deployment

Refresh Stop Delete

Overview Sites Task History Resource Defaults Provisioning Collections

**Provisioning Collections**


Filter By  
Q Windows 10 WVD Notepad++ Refresh Add Collection

| Name                     | Type | Operating System | Servers | Apps | Min. Cache | Current Cache | Status  | Actions                                   |
|--------------------------|------|------------------|---------|------|------------|---------------|---------|-------------------------------------------|
| Windows 10 WVD Notepad++ | VDI  |                  | 1       | 0    | 0          | 0             | Pending | Edit Delete Validate Delete Servers Cache |

Previous Page 1 of 1 Next

## Using the Collection

After validation has completed, the Status of the Provisioning Collection will change to **Available**. From within the Provisioning Collection the VDS Admin can identify the **VM Template** name which is used to identify this provisioning collection throughout VDS.



### New Server

From the Workspace > Servers page, a new server can be created and the dialog box will prompt for the VM Template. The template name from above will be found on this list:



VDS provides for an easy way to update session hosts in an RDS environment by using Provisioning Collections and the **Add Server** functionality. This process can be done without impacting end users and repeated over and over with subsequent image updates, building on previous image iterations. For a detailed workflow on this process, see the [RDS Session Host Update Process](#) section below.

### New AVD Host Pool

From the Workspace > AVD > Host Pools page, new AVD Host Pool can be created by clicking **+ Add Host Pool** and the dialog box will prompt for the VM Template. The template name from above will be found on this list:

VDS Documentation  
Virtual Desktop  
Service

Search

Tv Toby

Home > Workspaces > Azure WVD > WVD > Host Pools > Add Host Pool

### Add Host Pool

Basic Info

Name

Required

Name...

Friendly Name

Friendly Name...

Site

Required

Select a site...

Workspace

Required

Select a site first

Host Pool Type

Required

Select a host pool type...

Custom Profile Path

Custom Profile Path...

☐ Validation Environment

Included Session Hosts

OS Disk Type

☐ Ephemeral ☒ Persistent

VM Template

Required

windows10

Windows10EVD3497ver1

Windows10EVDwi3500ver1

Machine Size Type

Required

Select machine size type...

Number of Instances

1

Cancel

Save

## New AVD Session Host(s)

From the Workspace > AVD > Host Pool > Session Hosts page, new AVD session host(s) can be created by clicking **+ Add Session Host** and the dialog box will prompt for the VM Template. The template name from above will be found on this list:

VDS Documentation  
Virtual Desktop  
Service

Search

Tv Toby

Home > Workspaces > Azure WVD > WVD > Host Pools > Shared WVD Pool > Session Hosts

### Shared WVD Pool

Host Pool

Edit

Delete

Overview

Session Hosts

App Groups

Active Users

Filter By

Refresh

+ Add Session Host

| Name             | OS Disk Type | VM Template | Machine Size Type | Number of Instances | Actions   |
|------------------|--------------|-------------|-------------------|---------------------|-----------|
| 525WTS12.VDSazu  | ✓            | 0           | Online            | ✓                   | Available |
| redemo.amiicroso |              |             |                   |                     |           |
| tl.com           |              |             |                   |                     |           |

Add Session Host

OS Disk Type

☐ Ephemeral ☒ Persistent

VM Template

Required

Windows10

Windows10EVD3497ver1

Windows10EVDwi3500ver1

Machine Size Type

Required

Standard\_E2as\_v4

Number of Instances

1

Cancel

Save



VDS provides for an easy way to update session hosts in a AVD Host Pool by using Provisioning Collections and the **Add Session Host** functionality. This process can be done without impacting end users and repeated over and over with subsequent image updates, building on previous image iterations. For a detailed workflow on this process, see the [AVD Session Host Update Process](#) section below.

## New Workspace

From the Workspaces page, a new workspace can be created by clicking **+ New Workspace** and the dialog box will prompt for the Provisioning Collection. The Shared Provisioning Collection name will be found on this list.

VDS Documentation  
Virtual Desktop  
Service

Home > Workspaces > Add Workspace

### Add Workspace

Configure Users Applications Review

Is this a new client?  
☒ Yes ☐ No

Company Name Required Login Identifier Required  
Omega Fuel @ omegafuel

Notification Email Required Phone Number Required  
notify@omegafuel.abc 5555555555

Country Required  
United States

Address 1 Required Address 2  
555 Main St Address 2...

City Required State Required Zip Code Required  
Olympia Washington 98501

Website Internal Customer Number  
Website... Customer number...

#### Provisioning Info

Deployment Required Operating System Required  
VDSGCPDemo (kok) Windows Server 2019

Provisioning Collection Required  
Default PC  
Default PC

#### Application Settings

☐ Enable Remote App  
☐ Enable App Locker  
☐ Enable Application Usage Tracking

#### Device Settings

☐ Disable Printing Access  
☐ Enable User Profile Disk  
☒ Enable User Workspace Data Storage  
☐ Permit Access to Task Manager

#### Security Settings


☐ Require Complex User Password  
☐ File Auditing Enabled  
☐ Migration Mode Enabled  
☐ Enable MFA for All Users

Cancel Next

## New Provisioning Collection

From the Deployment > Provisioning Collection page, a new Provisioning Collection can be created by clicking **+ Add Collection**. When adding servers to this collection the dialog box will prompt for the VM Template. The template name from above will be found on this list:





## Addendum 1 - RDS Session Hosts

### RDS Session Host Update Process

VDS provides for an easy way to update session hosts in a RDS environment by using Provisioning Collections and the **Add Server** functionality. This process can be done without impacting end users and repeated over and over with subsequent image updates, building on previous image iterations.

The RDS Session Host update process is as follows:


1. Build a new VDI Provisioning Collection, customize and validate the collection per the instructions above.
  - a. Generally this Provisioning Collection will be built on the previous VM Template, emulating an "Open, Save As" process.
2. Once the Provisioning Collection has validated, navigate to the *Workspace > Servers* page, click **+ Add Server**

### Add Server


|                                                                                 |          |                        |
|---------------------------------------------------------------------------------|----------|------------------------|
| Server Role                                                                     | Required | VM Template            |
| TS                                                                              | ×        | Windows10EVDwi3500ver1 |
| Machine Size Type                                                               | Required | Storage Type           |
| Standard_E8as_v4                                                                | ×        | StandardSSD_LRS        |
| <input type="checkbox"/> Data Drive                                             |          |                        |
| <input type="button" value="Cancel"/> <input type="button" value="Add Server"/> |          |                        |

3. Select **TS** as the **Server Role**
4. Select the latest **VM Template**. Make the appropriate **Machine Size** and **Storage Type** selections based on your requirements. Leave **Data Drive** unchecked.
5. Repeat this for the total number of Session Hosts required for the environment.
6. Click **Add Server**, the session hosts will build based on the selected VM Template and starting coming online in as soon as 10-15 minutes (depending on the hypervisor).

- a. Note that the Session Hosts currently in the environment will ultimately be decommissioned after these new host come online. Plan to build enough new hosts to be sufficient to support the entire workload in this environment.
7. When a new host comes online, the default setting is to stay in **Disallow New Sessions**. For each session host, the **Allow New Sessions** toggle can be used to manage which hosts can receive new user sessions. This setting is accessed by editing the settings of each individual session host server. Once sufficient new hosts have been built and functionality has been confirmed, this setting can be managed on both the new and old hosts to route all new sessions to the new hosts. The old hosts, with **Allow New Sessions** set to **disabled**, can continue to run and host existing user sessions.



8. As users log off of the old host(s), and with no new user sessions joining the old host(s), the old host(s) where **Sessions = 0** can be deleted by clicking the **Actions** icon and selecting **delete**.



## Addendum 2 - AVD Session Hosts

### AVD Session Host Update Process

VDS provides for an easy way to update session hosts in a AVD Host Pool by using Provisioning Collections and the **Add Session Host** functionality. This process can be done without impacting end users and repeated

over and over with subsequent image updates, building on previous image iterations.

**The AVD Session Host update process is as follows:**

1. Build a new VDI Provisioning Collection, customize and validate the collection per the instructions above.
  - a. Generally this Provisioning Collection will be built on the previous VM Template, emulating an "Open, Save As" process.
2. Once the Provisioning Collection has validated, navigate to the *Workspace > AVD > Host Pools* page and click the name of the Host Pool
3. From within the *Host Pool > Session Hosts* page, click **+ Add Session Host**

**Add Session Host**

**OS Disk Type**  
☐ Ephemeral ☒ Persistent

**VM Template** Required  
Windows10EVDwi3500ver1 ✕


**Machine Size Type** Required  
Standard\_E8as\_v4 ✕

**Machine Storage Type** Required  
StandardSSD\_LRS ✕


**Number of Instances**  
12

Cancel Save

4. Select the latest **VM Template**. Make the appropriate **Machine Size** and **Storage Type** selections based on your requirements.
5. Enter the **Number of Instances** equal to the total number of required Session Hosts. Typically this will be the same number as are currently in the Host Pool but it can be any number.
  - a. Note that the Session Hosts currently in the Host pool will ultimately be decommissioned after these new host come online. Plan for the **Number of Instances** entered to be sufficient to support the entire workload in this Host Pool.
6. Click **Save**, the session hosts will build based on the selected VM Template and starting coming online in as soon as 10-15 minutes (depending on the hypervisor).
7. When a new host comes online, the default setting is to stay in **Disallow New Sessions**. For each session host, the **Allow New Sessions** toggle can be used to manage which hosts can receive new user sessions. Once sufficient new hosts have been built and functionality has been confirmed, this setting can be managed on both the new and old hosts to route all new sessions to the new hosts. The old hosts, with **Allow New Sessions** set to **disabled**, can continue to run and host existing user sessions.



8. As users log off of the old host(s), and with no new user sessions joining the old host(s), the old host(s) where **Sessions = 0** can be deleted by clicking the **Actions** icon and selecting **delete**.



## VDS Logical Hierarchy Overview

### Overview

VDS organizes concepts into various layers of a logical hierarchy. This article helps to outline how they fit together.

### VDS Organizational Scheme

The VDS management portal is found at <https://manage.vds.netapp.com>. This web interface is a single pane of glass for managing all VDS-related objects. Within the VDS web UI, the following hierarchy of components and logical containers exist.

## VDS Deployment

The *Deployment* is a VDS concept that organized and contains *VDS Workspace(s)*. In certain deployment architectures a deployment can contain multiple VDS Workspaces.



Running multiple VDS Workspaces within a single Deployment is called "Multi-Tenancy" and is only an option in RDS deployments, AVD deployments do not support this approach.

A deployment is defined by its Active Directory domain and there is a 1:1 relationship between the AD domain and a Deployment.

There are certain VM resources that are deployed to support a deployment that are shared across all VDS Workspaces in the deployment. E.g. every Deployment contains a VM named "CWMGR1" which is a server that run VDS applications, a SQL Express database and facilitates management of the VDS Workspace(s) (and the contained resources) within the Deployment.

## VDS Workspace



There is a difference between a "**VDS Workspace**" and a "**AVD Workspace**".

A VDS Workspace is a logical container inside the deployment for the client (end user) resources. These resources include Virtual Machines (for session hosts, application servers, database servers, file servers etc.), virtual networking, storage and other hypervisor infrastructure.

The VDS Workspace also contains management functionality to manage Users, Security Groups, Workload Scheduling, Applications, Automation, VMs, and AVD configuration.

Typically a VDS Workspace is aligned with a single company, or (in enterprise deployments), a business unit.

## VDS Sites

Within a deployment, multiple Sites can be created to represent different infrastructure providers, all managed within a single deployment.

This is helpful when a single company or business unit needs to host users and apps across multiple physical locations (e.g North America and EMEA), hypervisor subscriptions (to align costs to business units)and even hypervisors (E.g. users in Azure, Google Compute and on-premises HCI on vSphere).

## AVD Workspaces



There is a difference between a "**VDS Workspace**" and a "**AVD Workspace**".

A AVD Workspace is a logical container that sits inside a VDS Workspace and VDS Site. It that can be used similarly to a VDS Site for segmenting management and operational policies in the same deployment.

## AVD Host Pools

AVD Host Pools are logical container that sit inside a AVD Workspace and hold the Session Hosts and App Groups users to server the user sessions and control access to individual resources.

## AVD App Groups

Each AVD Host Pool starts with a single "Desktop" App Group. Users and/or groups can be assigned to this (or other) App Group to allow access to the resources in the App Group to the assigned users.

Additional App Groups can be created within a host pool in VDS. All Additional App Groups are "RemoteApp" App Groups and serve RemoteApp resources as opposed to a full windows desktop experience.

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.