配置 Storage Replication Adapter 以进行灾难恢复

VSC, VASA Provider, and SRA 9.7

NetApp
June 03, 2022

This PDF was generated from https://docs.netapp.com/zh-cn/vsc-vasa-provider-sra-97/deploy/task-configure-storage-replication-adapter-for-san-environment.html on June 03, 2022. Always check docs.netapp.com for the latest.

目录

配置 Storage Replication Adapter 以进行灾难恢复 1
为 SAN 环境配置 Storage Replication Adapter 1
为 NAS 环境配置 Storage Replication Adapter 1
为高度扩展的环境配置Storage Replication Adapter 2

配置 Storage Replication Adapter 以进行灾难恢复

如果要配置vCenter Server以进行灾难恢复、则必须在部署Virtual Storage Console (VSC)、VASA Provider和Storage Replication Adapter (SRA)虚拟设备后启用Storage Replication Adapter (SRA)。默认情况下、部署虚拟设备时会安装VSC。在部署虚拟设备后、您必须为vCenter Server启用SRA。

- 相关信息 *

启用 Storage Replication Adapter

为 SAN 环境配置 Storage Replication Adapter

在运行适用于 Site Recovery Manager （ SRM ）的 Storage Replication Adapter （ SRA ）之前，必须先设置存储系统。

您必须已在受保护站点和恢复站点上安装以下程序：

- SRM

  有关安装 SRM 的文档位于 VMware 站点上。

  "VMware Site Recovery Manager 文档"

- SRA

  此适配器安装在 SRM 上。

步骤

1. 验证主 ESXi 主机是否已连接到受保护站点上主存储系统中的 LUN 。
2. 验证LUN是否位于主存储系统上已将`* osttype*`选项设置为_vmware_的igroup中。
3. 验证恢复站点上的ESXi主机是否与具有适当的FC或iSCSI连接。

   为此、您可以验证ESXi主机是否已在上连接本地LUN、也可以在上使用`fcp show initiators`命令或`iscsi show initiators`命令。

为 NAS 环境配置 Storage Replication Adapter

在运行适用于 VMware vCenter Site Recovery Manager （ SRM ）的 Storage Replication Adapter （ SRA ）之前，必须配置存储系统。

您必须已在受保护站点和恢复站点上安装以下程序：

- SRM

  有关安装 SRM 的文档，请参见 VMware 站点。

"VMware Site Recovery Manager 文档"

- SRA

  适配器安装在 SRM 和 SRA 服务器上。

步骤

1. 验证受保护站点上的数据存储库是否包含已向 vCenter Server 注册的虚拟机。
2. 验证受保护站点上的ESXi主机是否已从挂载NFS导出卷。
3. 使用*阵列管理器*向导向SRM添加阵列时、验证是否在* NFS地址*字段中指定了有效地址、例如存在NFS导出的IP地址、主机名或FQDN。
4. 在恢复站点的每个ESXi主机上使用`ping`命令验证主机是否具有可从访问用于提供NFS导出的IP地址的VMkernel端口。

"NetApp 支持"

为高度扩展的环境配置Storage Replication Adapter

您必须根据建议的设置配置存储超时间隔，以使 Storage Replication Adapter （ SRA ）能够在高度扩展的环境中以最佳性能运行。

存储提供程序设置

- 您必须将`StorageProvider.resignatureTimeout`设置的值从900秒增加到12000秒。
- 您必须启用`StorageProvider.autoResignatureMode`选项。

有关修改存储提供程序设置的详细信息，请参见 VMware 文档。

"VMware vSphere 文档：更改存储提供程序设置"

存储设置

对于高度扩展的环境、必须将`storage.commandTimeout`超时间隔值设置为12、000秒。

> 指定的超时间隔为最大值。您无需等待达到最大超时值。大多数命令都会在设置的最大超时间隔内完成。

"NetApp 知识库问题解答 1001111 ：《适用于 ONTAP 的 NetApp 存储复制适配器 4.0/7.X 规模估算指南》"

有关修改 SAN Provider 设置的 VMware 文档提供了更多信息。

"VMware Site Recovery Manager文档：更改存储设置"

版权信息

版权所有©2022 NetApp、Inc.。保留所有权利。Printed in the U.S.版权所涵盖的本文档的任何部分不得以任何形式或任何手段复制、包括影印、录制、 磁带或存储在电子检索系统中—未经版权所有者事先书面许可。

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

本软件由NetApp按"原样"提供、不含任何明示或默示担保、包括但不限于适销性和特定用途适用性的默示担保、特此声明不承担任何责任。IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice.NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp.The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S.patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

商标信息

NetApp、NetApp标识和中列出的标记 http://www.netapp.com/TM 是NetApp、Inc.的商标。其他公司和产品名称可能是其各自所有者的商标。