在 Active IQ 数据中心管理器上配置数据库用户

OnCommand Workflow Automation 5.0

NetApp
May 03, 2022

This PDF was generated from https://docs.netapp.com/zh-cn/workflow-automation-50/windows-install/task-configure-a-database-user-by-running-ocsetup-on-windows.html on May 03, 2022. Always check docs.netapp.com for the latest.

目录

在 Active IQ 数据中心管理器上配置数据库用户 1
通过在 Windows 上运行 ocsetup 来配置数据库用户 1
通过在 Linux 上运行 ocsetup 来配置数据库用户 1

在 Active IQ 数据中心管理器上配置数据库用户

您必须在 Active IQ Data Center Manager 6.0 之前的版本上创建一个数据库用户，才能配置对 OnCommand Workflow Automation 的 Active IQ Data Center Manager 数据库的只读访问权限。

通过在 Windows 上运行 ocsetup 来配置数据库用户

您可以在 Active IQ 数据中心管理器服务器上运行 `ocsetup` 文件，以配置 Active IQ 数据中心管理器数据库对 OnCommand Workflow Automation 的只读访问。

步骤

1. 从以下位置将 `WFA_ocsetup.exe` 文件下载到 Active IQ 数据中心管理器服务器中的目录：` https://WFA_Server_IP/download/wfa_ocsetup.exe.`

   WFA_SERVER_IP 是 WFA 服务器的 IP 地址（ IPv4 或 IPv6 地址）。

   如果为 WFA 指定了非默认端口，则必须包括以下端口号：

   ` + https://wfa_server_ip:port/download/wfa_ocsetup.exe.+`

   port 是您在安装期间用于 WFA 服务器的 TCP 端口号。

   如果要指定 IPv6 地址，则必须将其用方括号括起来。

2. 双击 `WFA_ocsetup.exe` 文件。
3. 阅读设置向导中的信息，然后单击 * 下一步 * 。
4. 浏览或键入 JRE 位置，然后单击 * 下一步 * 。
5. 输入用户名和密码以覆盖默认凭据。

   此时将创建一个可访问 Active IQ 数据中心管理器数据库的新数据库用户帐户。

   > 如果不创建用户帐户，则会使用默认凭据。出于安全考虑，您必须创建一个用户帐户。

6. 单击 * 下一步 * 并查看结果。
7. 单击 * 下一步 * ，然后单击 * 完成 * 完成向导。

通过在 Linux 上运行 ocsetup 来配置数据库用户

您可以在 Active IQ 数据中心管理器服务器上运行 ocsetup 文件，以配置对 OnCommand Workflow Automation 的 Active IQ 数据中心管理器数据库的只读访问权限。

步骤

1. 在终端中使用以下命令将 `WFA_ocsetup.sh` 文件下载到 Active IQ 数据中心管理器服务器上的主目录：` wget https://WFA_Server_IP/download/wfa_ocsetup.sh`[]

`WFA_SERVER_IP` 是 WFA 服务器的 IP 地址（ IPv4 或 IPv6 地址）。

如果为 WFA 指定了非默认端口，则必须包括以下端口号：

` wget https://wfa_server_ip:port/download/wfa_ocsetup.sh`[]

port 是您在安装期间用于 WFA 服务器的 TCP 端口号。

如果要指定 IPv6 地址，则必须将其用方括号括起来。

2. 在终端中使用以下命令将 wfa_ocsetup.sh 文件更改为可执行文件：

   `chmod +x wfa_ocsetup.sh`

3. 在终端中输入以下命令以运行此脚本：

   ` 。 /wfa_ocsetup.sh jre_path`

   jre_path 是 JRE 的路径。

   - 示例 *

     ` /opt/NTAPdfm/Java`

     终端中将显示以下输出，表示设置成功：

```
Verifying archive integrity... All good.
Uncompressing WFA OnCommand Setup.....
*** Welcome to OnCommand Setup Utility for Linux ***
    <Help information>
*** Please override the default credentials below ***
Override DB Username [wfa] :
```

4. 输入用户名和密码以覆盖默认凭据。

   此时将创建一个可访问 Active IQ 数据中心管理器数据库的新数据库用户帐户。

   > 如果不创建用户帐户，则会使用默认凭据。出于安全考虑，您必须创建一个用户帐户。

   终端中将显示以下输出，表示设置成功：

```
***** Start of response from the database *****
>>> Connecting to database
<<< Connected
*** Dropped existing 'wfa' user
=== Created user 'username'
>>> Granting access
<<< Granted access
***** End of response from the database *****
***** End of Setup *****
```

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.