Troubleshoot XCP File Analytics errors

XCP 1.6.2

Barb Einarsen, Ciaran McNamara, Paula Carrigan
January 22, 2021

This PDF was generated from https://docs.netapp.com/us-en/xcp/xcp-troubleshoot-xcp-file-analytics-errors.html on March 06, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Troubleshoot XCP File Analytics errors 1

Troubleshoot XCP File Analytics errors

Review the solutions to troubleshoot your issue.

Issue	Solution

PostgreSQL installation or service failed	Run configure again and select the installation option. If the previous installation was successful, you can select the repair option. If you are still getting the error, try manual steps as follows:
	
	1. Run PostgreSQL on the Linux system
	
	`sudo yum -y install postgresql-serversudo systemctl start postgresq`
	
	2. Create a data directory for the PostgreSQL database:
	
	`sudo mkdir /var/lib/postgres/data`
	
	3. Initialize the database:
	
	`sudo -i -u postgres initdb -D '/var/lib/pgsql/data`
	
	4. Open the following file using an appropriate Linux file editor:
	
	`/var/lib/pgsql/data/pg_hba.conf`
	
	5. Remove the following entry:
	
	`# host all all 127.0.0.1/32 trust`
	
	6. Add the following entry:
	`# host all all 0.0.0.0/0 password`
	7. Open the file `/var/lib/pgsql/data/postgresql.conf`
	8. Add the following entry:
	
	`# listen_addresses='*'`
	
	9. Start the PostgreSQL service:
	
	`sudo systemctl start postgresql.service`

Issue	Solution

HTTPD installation or service failed	Run configure again and select the installation option. If the previous installation was successful, you can select the repair option. If you are still getting the error, try manual steps as follows:
	
	1. Install HTTPD on the Linux system:
	
	`sudo yum -y install httpd`
	
	2. Open the following configuration file to rewrite the rules:
	
	`/etc/httpd/conf/httpd.conf`
	
	3. Add the following entries to the file:
	
	`RewriteEngine On`
	`RewriteOptions Inherit`
	`<Directory "/var/www/html/">`
	`AllowOverride None`
	`Require all granted`
	`RewriteCond %{REQUEST_FILENAME} -f [OR]`
	`RewriteCond %{REQUEST_FILENAME} -d`
	`RewriteRule ^ - [L]`
	`RewriteRule ^ xcp/index.html [L]`
	`</Directory>`
	
	4. Start the HTTPD services:
	
	`sudo systemctl start httpd`

Issue	Solution

SSL installation failed	Run configure again and select the installation option. If the previous installation was successful, you can select the repair option. If you are still getting the error, try manual steps as follows:
	
	1. Install `mod_ssl`:
	
	`yum install mod_ssl -y`
	
	2. Generate the Secure Sockets Layer (SSL) certificate:
	
	`yum openssl req -x509 -nodes -days 365 -newkey rsa:2048 -keyout /etc/ssl/private/apache-selfsigned.key -out /etc/ssl/certs/apache-selfsigned.crt`
	
	3. Enable the HTTPS services:
	
	`yum openssl dhparam -out /etc/ssl/certs/dhparam.pem 2048`
	
	4. Restart the HTTPD services:
	
	`sudo systemctl restart httpd`
	
	5. Copy the SSL certificate to an appropriate location:
	
	`sudo cp -pr /etc/pki/tls/certs/localhost.crt /opt/NetApp/xFiles/xcp/server.crt`
	`sudo cp -pr /etc/pki/tls/private/localhost.key /opt/NetApp/xFiles/xcp/server.key`

Not able to open login page after successful install	Make sure your system is able to ping the Linux machine where XCP File Analytics is installed and HTTPD is running. If the services are not running, run `configure` and choose the repair option. Make sure that you are using supported version of browser. See the IMT: https://mysupport.netapp.com/matrix/

Issue	Solution
User login failed	• Make sure that you are using a supported version of the browser. See the IMT: https://mysupport.netapp.com/matrix/ • Check the user is “admin” and the password is correct • Make sure the XCP service is running by issuing “xcp service status” • Verify that port 5030 is open on Linux. Open the application at **https:// <linux ip> :5030/api/xcp**, and confirm that the messagereads msg: `Missing Authorization Header` • Check whether the `xcp.ini` file is present in the `/opt/NetApp/xFiles/xcp/` location. To reset the `xcp.ini` file, run the configuration script and select the **Repair** option. Next, select the menu option to **rebuild xcp.ini file**
XCP GUI is not showing updated pages.	Clear the cache and try again
XCP service is not starting	To run the `xcp` service, use the `sudo systemctl start xcp` command. Alternatively, run the configuration script and select the **Repair** option to start the services that are stopped
Failed to scan file share	File share/volume might not be readable. Check manually whether the file share is accessible/readable by running the `xcp show` command
Could not load file servers	Try a page refresh. If the problem persists, manually run the `xcp show` command on the prompt and check whether you can scan the file server. If successful, raise a ticket with NetApp customer support. If unsuccessful, check manually to see if the file server is active Check whether the `xcp.ini` file and license files are in the correct location. To reset the `xcp.ini` file, run the configuration script and select the **Repair** option. Next, select the menu option to **rebuild xcp.ini file.** Check the `xcpfalogs` logs to see if the license needs renewal
XCP File Analytics page is not displayed after system reboot	XCP services might be down. Run the configuration script and select the option to **Repair**. This will restart all the services that are stopped
The total space for an exported file system on a given file server might show more space compared to the allocated physical storage.	This can happen when there are qtree level exports inside the volume. For example, if the volume size is 10 GB that is exported as `/vol1` and there is a qtree inside the volume `/vol1/qtree1`, then the `xcp show` command will show the `vol1` size as `10 GB` and the `qtree1` size as `10 GB`. XCP File Analytics sums the space of both exports and gives the total space, in this case, `20 GB`. It does not understand that `qtree1` is a logical space.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.