

# Cinching Wrist Cuff

## Installation and Usage Instructions

### IMPORTANT NOTES:

- Wrist strap end should only be used on the wrist.
- Carabiner end should be attached to a suitable attachment point (options sold separately).
- Tool attachment points should be free of sharp edges and should always have fully closed loops.
- If duct tape is required, the hook and loop has lost its grip and lanyard should be discarded.
- Do not intentionally suspend a tool by its lanyard.
- Remove and replace if:
  - there is any evidence of wear.
  - tether experiences a drop.
  - any doubt to product's integrity.

### RATINGS

PART NO.	REACH	WEIGHT LIMIT
DRWS	12"	6 lbs
DRWSSTRAP	N/A	6 lbs
DRWSTETH	12"	6 lbs

### WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS NOTED, PRODUCT REPLACEMENT IS REQUIRED.



# INSTALLATION



Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103  
 www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113

**THE DROP STOPS HERE**