

300lb Zip Top Dual Load Rated Tool Bucket

Installation and Usage Instructions
TTB300BNLBZP

Please read instructions carefully and fully before installation and/or usage.



IMPORTANT NOTES

- Inspect prior to every use
- Inspect connections prior to every lift
- Ensure bucket is in a secure location prior to manipulating contents
- User is responsible for determining safe lifting techniques
- Ensure bucket is closed when transferring to/ from height and when not actively being used
- To increase product life, when lowering, avoid dropping to the ground
- Ensure bucket is always attached to a truly secure attachment point

DO NOT

- Do not shock load
- Do not load with sharp objects (figure 1) (unless properly shielded to prevent puncture)
- Do not use objects that interfere with bucket closure (figure 2)
- Do not use handles near zipper for lifting, transporting, or attaching lanyards
- Do not attach to your body



Figure 1



Figure 2

INSTR- TTB300BNLBZP -R1

LOADING BUCKET



Use snap hooks to attach tools directly.



Use D-rings to attach tool lanyards.


*Only attach one tool to each strap



Fully close zipper once all items are inside.



Lock snap hook through the zipper pull to prevent unintentional opening.



The carabiner is the only appropriate lifting point. Lift the bucket with an appropriate lifting apparatus.



Handles near the zipper are for adjusting only.

*Do not lift more than one bucket at a time on the same lifting rope/strap/chain.

WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS ARE NOTED, PRODUCT REPLACEMENT IS REQUIRED.

Weight Ratings:

300lb Load Rated
100lb Drop Tested

TY-FLÖT

Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103
www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113

CUTTING-EDGE PREVENTION™