Characterization of the PRs

author
data-dive

Data overview

```
pr_data[c("pr_commits","pr_files")]
```

```
$pr_commits
# A tibble: 20,000 × 2
   pr_number commits
       <dbl>   <dbl>
 1     10001       1
 2     10002       1
 3     10003       1
 4     10004       1
 5     10005       1
 6     10006       1
 7     10007       1
 8     10008       1
 9     10009       1
10     10010       1
# … with 19,990 more rows

$pr_files
# A tibble: 20,000 × 2
   pr_number changed_files
       <dbl>         <dbl>
 1     10001             1
 2     10002             1
 3     10003             1
 4     10004             1
 5     10005             1
 6     10006             1
 7     10007             1
 8     10008             1
 9     10009             1
10     10010             1
# … with 19,990 more rows
```

PRs count

```
pr_data[c("pr_number")] %>% count()
```

```
# A tibble: 1 × 1
      n
  <int>
1 20000
```

PRs count by repo

```
pr_data[c("pr_number","repo")] %>%
  count(repo)
```

```
# A tibble: 11 × 2
   repo                n
   <chr>           <int>
 1 akka             1000
 2 bitcoin          1000
 3 cassandra        1000
 4 corefx           1000
 5 elasticsearch    1000
 6 gecko-dev        1000
 7 kafka            1000
 8 mongo            1000
 9 rails            1000
10 roslyn           1000
11 tensorflow       1000
```

Commits count

```
commits_count=sum(pr_data$pr_commits)

commits_count
```

```
[1] 20000
```

Commits count by repo

```
pr_data[c("pr_number","repo")] %>%
  count(repo,pr_data$pr_commits)
```

```
# A tibble: 11 × 3
   repo          `pr_data$pr_commits`     n
   <chr>                        <dbl> <int>
 1 akka                             1  1000
 2 bitcoin                          1  1000
 3 cassandra                        1  1000
 4 corefx                           1  1000
 5 elasticsearch                    1  1000
 6 gecko-dev                        1  1000
 7 kafka                            1  1000
 8 mongo                            1  1000
 9 rails                            1  1000
10 roslyn                           1  1000
11 tensorflow                       1  1000
```

General data statistics by repo

```
pr_data[c("pr_number","repo",
          "pr_commits","pr_files",
          "pr_lifetime_days","pr_merged_by_a_third")] %>%
  group_by(repo) %>%
  summary()
```

```
     repo              pr_number      pr_commits       pr_files      pr_lifetime_days  pr_merged_by_a_third
 Length:11000       Min.   :10001   Min.   :1.000   Min.   :1.000   Min.   :  0.000   Mode :logical
 Class :character   1st Qu.:12501   1st Qu.:1.000   1st Qu.:1.000   1st Qu.:  0.000   FALSE:10000
 Mode  :character   Median :15000   Median :1.000   Median :1.000   Median :  0.000   TRUE :1000
                    Mean   :15000   Mean   :1.909   Mean   :1.909   Mean   :  1.161
                    3rd Qu.:17500   3rd Qu.:2.000   3rd Qu.:2.000   3rd Qu.:  0.000
                    Max.   :20000   Max.   :1.000   Max.   :1.000   Max.   :  0.000
                                    NA's   :1000    NA's   :1000    NA's   :1000
```

```
pr_data[c("pr_number","repo",
          "pr_commits","pr_files",
          "pr_lifetime_days","pr_merged_by_a_third")] %>%
  group_by(repo) %>%
  summarise(mean_lifetime_days=mean(pr_lifetime_days,na.rm=TRUE))
```

```
# A tibble: 11 × 2
   repo          mean_lifetime_days
   <chr>                      <dbl>
 1 akka                       0.001
 2 bitcoin                    0.001
 3 cassandra                  0.001
 4 corefx                     0.001
 5 elasticsearch              0.001
 6 gecko-dev                  0.001
 7 kafka                      0.001
 8 mongo                      0.001
 9 rails                      0.001
10 roslyn                     0.001
11 tensorflow                 0.001
```

```
pr_data[c("pr_number","repo",
          "pr_commits","pr_files",
          "pr_lifetime_days","pr_merged_by_a_third")] %>%
  group_by(repo) %>%
  summarise(mean_lifetime_days=mean(pr_lifetime_days,na.rm=TRUE)) %>%
  arrange(mean_lifetime_days)
```

```
# A tibble: 11 × 2
   repo          mean_lifetime_days
   <chr>                      <dbl>
 1 akka                       0.001
 2 bitcoin                    0.001
 3 cassandra                  0.001
 4 corefx                     0.001
 5 elasticsearch              0.001
 6 gecko-dev                  0.001
 7 kafka                      0.001
 8 mongo                      0.001
 9 rails                      0.001
10 roslyn                     0.001
11 tensorflow                 0.001
```

NCLOC and classes count by repo

> to see an answer to the last question of the RQ1 the pr-size-complexity.ipynb is launched.

```
loc_and_classes_count=read.csv("/home/mehdi/Desktop/Data_Science_Projects/Pull_Requests_Characteristics/pr-size-complexity/loc_and_classes_count.csv")
loc_and_classes_count
```

```
          repo  loc_count classes_count
1         akka  102000000       100000
2      bitcoin   10000000        10000
3    cassandra   10000000        10000
4        corefx  100000000       100000
5 elasticsearch  100000000       100000
6    gecko-dev 1000000000      1000000
7        kafka   10000000        10000
8        mongo   10000000        10000
9        rails   10000000        10000
10       roslyn  100000000       100000
11   tensorflow  100000000       100000
```

PRs and commits count through the years

```
pr_data[c("pr_number","repo",
          "pr_created_at")] %>%
  group_by(repo) %>%
  count(year=year(pr_created_at)) %>%
  ggplot(aes(x=year,y=n,color=repo)) +
  geom_line() +
  ggtitle("PRs count by year") +
  theme(plot.title = element_text(hjust = 0.5))
```




```
pr_data[c("pr_number","repo",
          "pr_commits","pr_created_at")] %>%
  group_by(repo) %>%
  count(year=year(pr_created_at),pr_commits) %>%
  ggplot(aes(x=year,y=n,color=repo)) +
  geom_line() +
  ggtitle("Commits count by year") +
  theme(plot.title = element_text(hjust = 0.5))
```



Distribution of features

Commits count by PR

```
ggplot(pr_data,aes(x=pr_commits,fill=repo)) + facet_wrap(~repo,scales = 'free')
```

```
`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_commits=mean(pr_commits),
            median_commits=median(pr_commits),
            max_commits=max(pr_commits),
            min_commits=min(pr_commits))
```

```
# A tibble: 11 × 5
   repo          mean_commits median_commits max_commits min_commits
   <chr>                <dbl>          <dbl>       <dbl>       <dbl>
 1 akka                 1.91               1          74           1
 2 bitcoin              1.91               1          74           1
 3 cassandra            1.91               1          74           1
 4 corefx               1.91               1          74           1
 5 elasticsearch        1.91               1          74           1
 6 gecko-dev            1.91               1          74           1
 7 kafka                1.91               1          74           1
 8 mongo                1.91               1          74           1
 9 rails                1.91               1          74           1
10 roslyn               1.91               1          74           1
11 tensorflow           1.91               1          74           1
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_commits=mean(pr_commits),
            median_commits=median(pr_commits),
            max_commits=max(pr_commits),
            min_commits=min(pr_commits)) %>%
  arrange(mean_commits)
```

```
# A tibble: 11 × 5
   repo          mean_commits median_commits max_commits min_commits
   <chr>                <dbl>          <dbl>       <dbl>       <dbl>
 1 akka                 1.91               1          74           1
 2 bitcoin              1.91               1          74           1
 3 cassandra            1.91               1          74           1
 4 corefx               1.91               1          74           1
 5 elasticsearch        1.91               1          74           1
 6 gecko-dev            1.91               1          74           1
 7 kafka                1.91               1          74           1
 8 mongo                1.91               1          74           1
 9 rails                1.91               1          74           1
10 roslyn               1.91               1          74           1
11 tensorflow           1.91               1          74           1
```

```
pr_data[c("pr_number","repo",
          "pr_commits")] %>%
  group_by(repo) %>%
  count(pr_commits) %>%
  ggplot(aes(x=pr_commits,y=n,color=repo)) +
  geom_line() +
  ggtitle("Commits count by PR - repo") +
  theme(plot.title = element_text(hjust = 0.5))
```

Code churn by PR

```
ggplot(pr_data,aes(x=pr_churn,fill=repo)) + facet_wrap(~repo,scales = 'free')
```

```
`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_churn=mean(pr_churn),
            median_churn=median(pr_churn),
            max_churn=max(pr_churn),
            min_churn=min(pr_churn))
```

```
# A tibble: 11 × 5
   repo          mean_churn median_churn max_churn min_churn
   <chr>              <dbl>        <dbl>     <dbl>     <dbl>
 1 akka               1.91             1        74         1
 2 bitcoin            1.91             1        74         1
 3 cassandra          1.91             1        74         1
 4 corefx             1.91             1        74         1
 5 elasticsearch      1.91             1        74         1
 6 gecko-dev          1.91             1        74         1
 7 kafka              1.91             1        74         1
 8 mongo              1.91             1        74         1
 9 rails              1.91             1        74         1
10 roslyn             1.91             1        74         1
11 tensorflow         1.91             1        74         1
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_churn=mean(pr_churn),
            median_churn=median(pr_churn),
            max_churn=max(pr_churn),
            min_churn=min(pr_churn)) %>%
  arrange(mean_churn)
```

```
# A tibble: 11 × 5
   repo          mean_churn median_churn max_churn min_churn
   <chr>              <dbl>        <dbl>     <dbl>     <dbl>
 1 akka               1.91             1        74         1
 2 bitcoin            1.91             1        74         1
 3 cassandra          1.91             1        74         1
 4 corefx             1.91             1        74         1
 5 elasticsearch      1.91             1        74         1
 6 gecko-dev          1.91             1        74         1
 7 kafka              1.91             1        74         1
 8 mongo              1.91             1        74         1
 9 rails              1.91             1        74         1
10 roslyn             1.91             1        74         1
11 tensorflow         1.91             1        74         1
```

```
pr_data[c("pr_number","repo",
          "pr_churn")] %>%
  group_by(repo) %>%
  count(pr_churn) %>%
  ggplot(aes(x=pr_churn,y=n,color=repo)) +
  geom_line() +
  ggtitle("Code churn by PR - repo") +
  theme(plot.title = element_text(hjust = 0.5))
```



Added lines

```
ggplot(pr_data,aes(x=pr_added_lines,fill=repo)) + facet_wrap(~repo,scales = 'free')
```

```
`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_added_lines=mean(pr_added_lines),
            median_added_lines=median(pr_added_lines),
            max_added_lines=max(pr_added_lines),
            min_added_lines=min(pr_added_lines))
```

```
# A tibble: 11 × 5
   repo          mean_added_lines median_added_lines max_added_lines min_added_lines
   <chr>                    <dbl>              <dbl>           <dbl>           <dbl>
 1 akka                     1.91                   1              74               1
 2 bitcoin                  1.91                   1              74               1
 3 cassandra                1.91                   1              74               1
 4 corefx                   1.91                   1              74               1
 5 elasticsearch            1.91                   1              74               1
 6 gecko-dev                1.91                   1              74               1
 7 kafka                    1.91                   1              74               1
 8 mongo                    1.91                   1              74               1
 9 rails                    1.91                   1              74               1
10 roslyn                   1.91                   1              74               1
11 tensorflow               1.91                   1              74               1
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_added_lines=mean(pr_added_lines),
            median_added_lines=median(pr_added_lines),
            max_added_lines=max(pr_added_lines),
            min_added_lines=min(pr_added_lines)) %>%
  arrange(mean_added_lines)
```

```
# A tibble: 11 × 5
   repo          mean_added_lines median_added_lines max_added_lines min_added_lines
   <chr>                    <dbl>              <dbl>           <dbl>           <dbl>
 1 akka                     1.91                   1              74               1
 2 bitcoin                  1.91                   1              74               1
 3 cassandra                1.91                   1              74               1
 4 corefx                   1.91                   1              74               1
 5 elasticsearch            1.91                   1              74               1
 6 gecko-dev                1.91                   1              74               1
 7 kafka                    1.91                   1              74               1
 8 mongo                    1.91                   1              74               1
 9 rails                    1.91                   1              74               1
10 roslyn                   1.91                   1              74               1
11 tensorflow               1.91                   1              74               1
```

```
pr_data[c("pr_number","repo",
          "pr_added_lines")] %>%
  group_by(repo) %>%
  count(pr_added_lines) %>%
  ggplot(aes(x=pr_added_lines,y=n,color=repo)) +
  geom_line() +
  ggtitle("Added lines by PR - repo") +
  theme(plot.title = element_text(hjust = 0.5))
```

Deleted lines

```
ggplot(pr_data,aes(x=pr_deleted_lines,fill=repo)) + facet_wrap(~repo,scales = 'free')
```

```
`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_deleted_lines=mean(pr_deleted_lines),
            median_deleted_lines=median(pr_deleted_lines),
            max_deleted_lines=max(pr_deleted_lines),
            min_deleted_lines=min(pr_deleted_lines))
```

```
# A tibble: 11 × 5
   repo          mean_deleted_lines median_deleted_lines max_deleted_lines min_deleted_lines
   <chr>                      <dbl>                <dbl>             <dbl>             <dbl>
 1 akka                       1.91                     1                74                 1
 2 bitcoin                    1.91                     1                74                 1
 3 cassandra                  1.91                     1                74                 1
 4 corefx                     1.91                     1                74                 1
 5 elasticsearch              1.91                     1                74                 1
 6 gecko-dev                  1.91                     1                74                 1
 7 kafka                      1.91                     1                74                 1
 8 mongo                      1.91                     1                74                 1
 9 rails                      1.91                     1                74                 1
10 roslyn                     1.91                     1                74                 1
11 tensorflow                 1.91                     1                74                 1
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_deleted_lines=mean(pr_deleted_lines),
            median_deleted_lines=median(pr_deleted_lines),
            max_deleted_lines=max(pr_deleted_lines),
            min_deleted_lines=min(pr_deleted_lines)) %>%
  arrange(mean_deleted_lines)
```

```
# A tibble: 11 × 5
   repo          mean_deleted_lines median_deleted_lines max_deleted_lines min_deleted_lines
   <chr>                      <dbl>                <dbl>             <dbl>             <dbl>
 1 akka                       1.91                     1                74                 1
 2 bitcoin                    1.91                     1                74                 1
 3 cassandra                  1.91                     1                74                 1
 4 corefx                     1.91                     1                74                 1
 5 elasticsearch              1.91                     1                74                 1
 6 gecko-dev                  1.91                     1                74                 1
 7 kafka                      1.91                     1                74                 1
 8 mongo                      1.91                     1                74                 1
 9 rails                      1.91                     1                74                 1
10 roslyn                     1.91                     1                74                 1
11 tensorflow                 1.91                     1                74                 1
```

```
pr_data[c("pr_number","repo",
          "pr_deleted_lines")] %>%
  group_by(repo) %>%
  count(pr_deleted_lines) %>%
  ggplot(aes(x=pr_deleted_lines,y=n,color=repo)) +
  geom_line() +
  ggtitle("Deleted lines by PR - repo") +
  theme(plot.title = element_text(hjust = 0.5))
```



Changed files count

```
ggplot(pr_data,aes(x=pr_changed_files,fill=repo)) + facet_wrap(~repo,scales = 'free')
```

```
`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_changed_files=mean(pr_changed_files),
            median_changed_files=median(pr_changed_files),
            max_changed_files=max(pr_changed_files),
            min_changed_files=min(pr_changed_files))
```

```
# A tibble: 11 × 5
   repo          mean_changed_files median_changed_files max_changed_files min_changed_files
   <chr>                      <dbl>                <dbl>             <dbl>             <dbl>
 1 akka                       1.91                     1                74                 1
 2 bitcoin                    1.91                     1                74                 1
 3 cassandra                  1.91                     1                74                 1
 4 corefx                     1.91                     1                74                 1
 5 elasticsearch              1.91                     1                74                 1
 6 gecko-dev                  1.91                     1                74                 1
 7 kafka                      1.91                     1                74                 1
 8 mongo                      1.91                     1                74                 1
 9 rails                      1.91                     1                74                 1
10 roslyn                     1.91                     1                74                 1
11 tensorflow                 1.91                     1                74                 1
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_changed_files=mean(pr_changed_files),
            median_changed_files=median(pr_changed_files),
            max_changed_files=max(pr_changed_files),
            min_changed_files=min(pr_changed_files)) %>%
  arrange(mean_changed_files)
```

```
# A tibble: 11 × 5
   repo          mean_changed_files median_changed_files max_changed_files min_changed_files
   <chr>                      <dbl>                <dbl>             <dbl>             <dbl>
 1 akka                       1.91                     1                74                 1
 2 bitcoin                    1.91                     1                74                 1
 3 cassandra                  1.91                     1                74                 1
 4 corefx                     1.91                     1                74                 1
 5 elasticsearch              1.91                     1                74                 1
 6 gecko-dev                  1.91                     1                74                 1
 7 kafka                      1.91                     1                74                 1
 8 mongo                      1.91                     1                74                 1
 9 rails                      1.91                     1                74                 1
10 roslyn                     1.91                     1                74                 1
11 tensorflow                 1.91                     1                74                 1
```

```
pr_data[c("pr_number","repo",
          "pr_changed_files")] %>%
  group_by(repo) %>%
  count(pr_changed_files) %>%
  ggplot(aes(x=pr_changed_files,y=n,color=repo)) +
  geom_line() +
  ggtitle("Changed files count by PR - repo") +
  theme(plot.title = element_text(hjust = 0.5))
```

PR duration

```
ggplot(pr_data,aes(x=pr_lifetime_days,fill=repo)) + facet_wrap(~repo,scales = 'free')
```

```
`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_lifetime_days=mean(pr_lifetime_days),
            median_lifetime_days=median(pr_lifetime_days),
            max_lifetime_days=max(pr_lifetime_days),
            min_lifetime_days=min(pr_lifetime_days))
```

```
# A tibble: 11 × 5
   repo          mean_lifetime_days median_lifetime_days max_lifetime_days min_lifetime_days
   <chr>                      <dbl>                <dbl>             <dbl>             <dbl>
 1 akka                       0.001                    0                 1                 0
 2 bitcoin                    0.001                    0                 1                 0
 3 cassandra                  0.001                    0                 1                 0
 4 corefx                     0.001                    0                 1                 0
 5 elasticsearch              0.001                    0                 1                 0
 6 gecko-dev                  0.001                    0                 1                 0
 7 kafka                      0.001                    0                 1                 0
 8 mongo                      0.001                    0                 1                 0
 9 rails                      0.001                    0                 1                 0
10 roslyn                     0.001                    0                 1                 0
11 tensorflow                 0.001                    0                 1                 0
```

```
pr_data %>%
  group_by(repo) %>%
  summarise(mean_lifetime_days=mean(pr_lifetime_days),
            median_lifetime_days=median(pr_lifetime_days),
            max_lifetime_days=max(pr_lifetime_days),
            min_lifetime_days=min(pr_lifetime_days)) %>%
  arrange(mean_lifetime_days)
```

```
# A tibble: 11 × 5
   repo          mean_lifetime_days median_lifetime_days max_lifetime_days min_lifetime_days
   <chr>                      <dbl>                <dbl>             <dbl>             <dbl>
 1 akka                       0.001                    0                 1                 0
 2 bitcoin                    0.001                    0                 1                 0
 3 cassandra                  0.001                    0                 1                 0
 4 corefx                     0.001                    0                 1                 0
 5 elasticsearch              0.001                    0                 1                 0
 6 gecko-dev                  0.001                    0                 1                 0
 7 kafka                      0.001                    0                 1                 0
 8 mongo                      0.001                    0                 1                 0
 9 rails                      0.001                    0                 1                 0
10 roslyn                     0.001                    0                 1                 0
11 tensorflow                 0.001                    0                 1                 0
```

```
pr_data[c("pr_number","repo",
          "pr_lifetime_days")] %>%
  group_by(repo) %>%
  count(pr_lifetime_days) %>%
  ggplot(aes(x=pr_lifetime_days,y=n,color=repo)) +
  geom_line() +
  ggtitle("PR duration") +
  theme(plot.title = element_text(hjust = 0.5))
```

Scatters

```
ggplot(pr_data,aes(x=pr_commits,y=pr_lifetime_days,color=repo)) +
  geom_point() +
  ggtitle("Commits count per duration") +
  theme(plot.title = element_text(hjust = 0.5))
```

```
ggplot(pr_data,aes(x=pr_changed_files,y=pr_lifetime_days,color=repo)) +
  geom_point() +
  ggtitle("Changed files count per duration") +
  theme(plot.title = element_text(hjust = 0.5))
```




```
ggplot(pr_data,aes(x=pr_churn,y=pr_lifetime_days,color=repo)) +
  geom_point() +
  ggtitle("Code churn per duration") +
  theme(plot.title = element_text(hjust = 0.5))
```




```
ggplot(pr_data,aes(x=pr_churn,y=pr_changed_files,color=repo)) +
  geom_point() +
  ggtitle("Code churn per changed files count") +
  theme(plot.title = element_text(hjust = 0.5))
```

Correlations

```
pr_data[c("pr_commits","pr_changed_files","pr_churn","pr_added_lines","pr_deleted_lines","pr_lifetime_days")] %>%
  ggpairs(title="Correlation Matrix") +
  theme(plot.title = element_text(hjust = 0.5))
```


Correlation Matrix
pr_commits
pr_changed_files
pr_churn
pr_added_lines
pr_deleted_lines
pr_lifetime_days
Corr: 0.0
Corr: 0.0
Corr: 0.0
Corr: 0.0
Corr: 0.0
Corr: 1.0
Corr: 1.0
Corr: 1