Backend brief: integration endpoints and the credits route

Rankoya · Frontend → Laravel team · 10 November 2026 · Backend reviewed at `ai-seo-project` `main` (`8328cb1`)

The frontend now has connect flows for **Wix** (installing the Rankoya Wix app), **Make**, **Lovable**, **Replit** (all three by webhook) and an **RSS / JSON feed**. Next only runs the browser-facing steps: redirects, test sends and signed feed links. **Laravel stores every connection and does every publish**, through the existing Publishing module.

Right now none of these flows can save a connection. This brief lists exactly what each endpoint needs. It starts with a live bug.

#	Item	Type	Unblocks
1	`GET /api/credits/balance` returns 404 in production	Deploy / bug	Credit balance in the app header and settings
2	`POST /sites/{site}/publishing/connections`: accept the Wix app and webhook shapes	Change	Saving Wix, Make, Lovable, Replit
3	`POST /sites/{site}/publishing/connections/{id}/test`: Wix app and webhook tests	Change	Activating those connections
4	`POST /sites/{site}/publishing/articles/{article}/publish`: two new providers	Change	Publishing to Wix Blog and to webhooks
5	`GET /internal/sites/{site}/feed`	New	RSS and JSON feeds
6	Optional: Wix "App Removed" webhook handling	Change	Marking a connection broken on uninstall

1 Bug: `/credits/balance` returns 404 in production

Observed:

```
GET https://api.rankoya.uk/api/credits/balance      (Accept: application/json)
→ 404 {"message": "The route api/credits/balance could not be found.",
       "exception": "Symfony\\...\\NotFoundHttpException", "file": "/var/www/ai-seo-
project/vendor/...", "trace": [...]}

GET https://api.rankoya.uk/api/sites                → 401   (server is up, routing works)
```

Effect: the credit balance in the app header shows a loading shape for a few seconds and then disappears, on every page. The credits tab in settings can't load either.

The route exists in the repo and is pushed to `origin/main`:

```
// routes/api.php (line ~55)
Route::middleware('auth:sanctum')->group(function () {
    Route::get('/credits/balance', [CreditWalletController::class, 'show']);   //
App\Http\Controllers\Api
});
```

So production is either not on the latest `main`, or the route cache was built before this route was added.

Fix

```
cd /var/www/ai-seo-project
git pull origin main
composer install --no-dev --optimize-autoloader
php artisan migrate --force                          # credit_wallets / api_usage_logs, if not run yet
php artisan optimize:clear && php artisan optimize   # rebuild route + config cache
```

Done when

- `curl -H "Accept: application/json" https://api.rankoya.uk/api/credits/balance` returns **401**, not 404.
- With a user token it returns `{ success: true, data: { balance_credits, reserved_credits, usd_per_credit, total_api_cost_usd, total_credits_charged, recent_usage, top_up_url } }`.

> **Security, same server:** the 404 response includes a full stack trace and server paths, so `APP_DEBUG=true` is on in production. Please set `APP_DEBUG=false` and run `php artisan config:cache`. Debug pages can expose environment details.

---

2 Create connection: accept the new shapes

POST `/api/sites/{site}/publishing/connections` EXISTING · AUTH:SANCTUM

Called by Next with the signed-in user's own token, so workspace scoping stays as it is. Today it refuses both new shapes:

- `PublishingProviderManager` doesn't register `WixPublishingProvider`, and nothing supports `method: webhook`. Both get "*This publishing integration is not available yet.*" (422).
- For Wix, validation requires `credentials.access_token` and `config.collection_id`. The app install has neither.

2a. Wix, installed through the Rankoya Wix app

```
{
  "name": "Wix",
  "platform": "wix",
  "method": "api",
  "credentials": { "instance_id": "<uuid from Wix signedInstance>", "site_id": "<wix site id, may
be empty>" },
  "config": { "auth": "app" }
}
```

Validation when `platform = wix` and `config.auth = app`:

- `credentials.instance_id`: required, string, max 255.

- `credentials.access_token` and `config.collection_id`: **not** required. Keep the API-key rules for the old shape (no `config.auth`).
- `config.auth`: `in:app`.

Next has already checked the Wix signature, made a token and confirmed Wix Blog exists before calling this, so the instance ID can be trusted. Next stores no token: tokens last 4 hours and Laravel makes a fresh one per publish (section 4).

2b. Webhook: Make, Lovable, Replit

```
{
  "name": "Make · example.com",
  "platform": "custom",
  "method": "webhook",
  "credentials": { "webhook_url": "https://hook.us2.make.com/...", "secret": "whsec_..." },
  "config": { "provider": "make" }          // make | lovable | replit
}
```

Validation when `method = webhook`:

- `credentials.webhook_url`: required, url, https only, max 2048.
- `credentials.secret`: required, string, `regex:/^whsec_[A-Za-z0-9_-]{20,}$/`.
- `config.provider`: required, `in:make,lovable,replit`.

Credentials are already cast `encrypted:array`, which is fine. Before calling this, Next has sent a signed test to the URL and got a 2xx back.

Response (unchanged)

```
201 { "success": true, "message": "...", "data": PublishingConnection }   // credentials never
serialised
```

The frontend finds webhook connections by `method = webhook` plus `config.provider`, so `config` must stay in the response.

---

3 Test connection

POST `/api/sites/{site}/publishing/connections/{connection}/test` EXISTING · AUTH:SANCTUM

No change to the request or response. The frontend calls it right after creating a connection, to turn it `active`. New behaviour per provider:

Connection	Test
Wix, `config.auth = app`	Make a token with `WixOAuthService::createAccessToken(instance_id)` (already in the repo), then `GET https://www.wixapis.com/blog/v3/categories` with `Authorization: <token>` (no "Bearer"). Pass on a 2xx. A 403 or 404 means Wix Blog isn't installed.
`method = webhook`	Send the signed request from section 4 with `event: "test"` and a sample article. Pass on a 2xx.

4 Publish: two new providers

POST `/api/sites/{site}/publishing/articles/{article}/publish` EXISTING · AUTH:SANCTUM

No change to the route. Register two providers in `PublishingProviderManager`.

4a. `WixPublishingProvider`, app mode

- `supports('wix', 'api')`. Register it in the manager.
- When `config.auth = app`, get a token per call from `createAccessToken(instance_id)`.
- Publish to **Wix Blog**, not Wix CMS. The current provider writes to `/wix-data/v2/items`. Use the Blog API instead: create a draft post, then publish it. The post body is Wix rich content, so the article HTML needs converting.
- Set a member as the post author if Wix requires one (for example the site owner).
- Save the Wix post ID as `external_id` and the live URL as `published_url`.
- **Laravel env:** `WIX_CLIENT_ID` = the Wix App ID, `WIX_CLIENT_SECRET` = the App Secret Key. These are the same values the frontend uses. We'll share them privately.

4b. `WebhookPublishingProvider` (new)

- `supports(*, 'webhook')`.
- When an article is published, send `article.published`. When an already-published article is updated, send `article.updated`.
- A 2xx response means published. Store the HTTP status in `response_metadata`.
- Retry 5xx and timeouts from the queue with backoff (for example 1, 5 and 30 minutes). Don't retry 4xx.
- Don't follow redirects. Timeout 10 s. At send time, refuse private, loopback, link-local and metadata IPs: DNS can change after the test.

The request. This must match exactly, because Lovable and Replit apps verify it. The frontend's reference implementation is `src/lib/integrations/webhook.ts`.

```
POST {webhook_url}
Content-Type: application/json
User-Agent: Rankoya-Webhooks/1.0
X-Rankoya-Event: test | article.published | article.updated
X-Rankoya-Timestamp: {unix seconds}
X-Rankoya-Signature: sha256={hex HMAC-SHA256 of "{timestamp}.{raw body}", key = credentials.secret}

{
  "event": "article.published",
  "sent_at": "2026-11-10T12:00:00Z",
  "site":    { "id": 12, "name": "Example", "url": "https://example.com" },
  "article": { "id": 345, "title": "...", "slug": "...", "meta_title": "...", "meta_description":
"...",
               "content_html": "<h2>...", "language": "en", "featured_image": "https://... | null",
               "published_at": "...", "updated_at": "..." }
}
```

```
// PHP: sign exactly the bytes you send
$body = json_encode($payload, JSON_UNESCAPED_SLASHES | JSON_UNESCAPED_UNICODE);
$ts   = time();
$sig  = 'sha256=' . hash_hmac('sha256', $ts . '.' . $body, $connection->credentials['secret']);
Http::withHeaders([...])->withBody($body, 'application/json')->withoutRedirecting()->timeout(10)-
>post($url);
```

5 New: feed data for RSS / JSON feeds

GET `/api/internal/sites/{site}/feed` NEW · SERVER-TO-SERVER ONLY

Next serves public feed links like `https://app.rankoya.uk/api/feeds/{siteId}.{signature}`. They're read by feed readers, Make's RSS module and Lovable / Replit pages, with nobody logged in. Next checks the signature, so only real links reach Laravel. It then needs to read that site's published articles **without a user token**.

A normal token can't do that: `SiteController@show` and the article list are limited to the token owner's active workspace.

Auth, one of:

- a shared secret header, `X-Internal-Token: {FEED_INTERNAL_TOKEN}`, compared in constant time. This is the simplest option. Or
- a Sanctum token for a service account with a single ability, `feeds:read`, checked with `tokenCan`.

Either way, send the value to the frontend privately. It becomes `BACKEND_SERVICE_TOKEN` in Vercel. No workspace check on this route. Read-only.

Query: `limit` (default 50, max 100).

Response:

```
200 {
  "success": true,
  "data": {
    "site": { "id": 12, "name": "Example", "url": "https://example.com", "language": "en" },
    "articles": [
      { "id": 345, "title": "...", "slug": "...", "meta_title": "...", "meta_description": "...",
        "content": "<html>", "language": "en", "media": [...], "metadata": { "published_url":
"https://..." },
        "published_at": "...", "updated_at": "...", "created_at": "..." }
    ]                                                  // newest first
  }
}
404 site not found · 401 bad or missing token
```

Please confirm:

1. Which article status belongs in the feed? We assume `published`, but sites without an API connection may never reach it.
2. Can each article expose its live URL (`metadata.published_url`, or a field)? Without it, feed items have no link.

---

6 Optional: Wix uninstall

`POST /api/publishing/wix/webhook` already verifies Wix's signed events (`WIX_PUBLIC_KEY`). When `eventType` is App Removed, find connections whose `credentials.instance_id` matches and set `status = error`, with `last_error = "The Rankoya app was removed from this Wix site."`. The app then offers Reconnect.

`GET /api/publishing/wix/callback` (currently 501) can stay as it is: the install callback runs in Next.

Laravel environment

Variable	Value
`WIX_CLIENT_ID`	Wix App ID (shared privately)
`WIX_CLIENT_SECRET`	Wix App Secret Key (shared privately)
`WIX_PUBLIC_KEY`	From the Wix app's webhooks page, only for section 6
`FEED_INTERNAL_TOKEN`	New. 32+ random bytes, sent to the frontend privately, only for section 5
`APP_DEBUG`	`false` in production

Done when

1. `GET /api/credits/balance` returns 401 without a token, and the balance with one.
2. Integrations → Make → Send test → Save leaves a Make connection that is `active`. Publishing an article runs the Make scenario once, with a valid `X-Rankoya-Signature`.
3. Installing the Wix app from Integrations ends on "Wix connected". Publishing an article creates a live post on that site's Wix Blog.

4. `GET /api/internal/sites/{site}/feed` with the internal token returns the site and its published articles. Without the token it returns 401.

Frontend references: `docs/integrations-explained.md` (how each flow works), `docs/integrations-testing.md` (test steps), `src/lib/integrations/webhook.ts` (signing). Questions to the frontend team.