# **EVERUN ER 425Common Rail (ny modell)**



### Kr.: 299.900 ex. mva

#### **Standard utstyr:**

- -Standard skuffe
- -Elektrisk joystick med gir, høy og lavserie
- -Konstant firehjulsdrift og reduksjons nav
- -Quick shift av redskap
- -Hydraulisk converter
- -Euro III standard motor, 95 hk
- -Flyt funksjon,
- -Ekstra hydraulikk, totalt fire funksjoner
- -Led kjøre/arbeidslys forover og bakover
- -Luksus hytte, tiltbar med ryggekamera og varmeapparat
- -Justerbart ratt og sete med setebelte
- -Hydrauliske skivebremse alle hjul og park brems
- -Dekk 16/70-20
- -Lås for løft og styresylinder
- -Hydraulisk trykk sjekk system
- -Varta batteri type vinter
- -Hovedstrøms bryter
- -Motorvarmer

### Tilbehørsliste:

hydraulisk, rett k snøskjær med V-blad	Kr.: 17.900,-
k snøskjær med V-blad	Mii 17.300,-
	Kr.: 24.900,-
, hydrauliak	Kr.: 29.900,-
	Kr.: 11.900,-
med hydrauliske vinger, 3m	Kr.: 19.900,-
<b>e</b>	Kr.: 14.900,-
uffe (Mixer bucket)	Kr.: 16.900,-
i <b>e</b>	Kr.: 9.900,-
fe	Kr.: 14.900,-
pr par	Kr.: 7.900,-
der front	Kr.: 19.900,-
der bak m/hydraulikk	Kr.: 26.900,-
lo 360 grader	Kr.: 26.900,-
in	Kr.: 26.900,-
in med oppsamler	Kr.: 28.900,-
in med vanntank	Kr.: 32.900,-
00mm	Kr.: 15.900,-
00mm	Kr.: 17.900,-
lafter	Kr.: 9.900,-
	Kr.: 9.900,-
	JOmm løfter er

## **Spesifikasjoner**

1.0 Engine Details

(1) Model: Xinchai 4DX22-96(EuroIII Standard)

(2) Engine Type: In-line Arrangement, Water-cooled, Four-cycle

Diesel Engine

(3) Rated Power: 70.0 KW

(4) Rated Speed: 2500 r/min(rpm) (5)Fuel Consumption Ration in Standard 260g/kw.H

**Working Condition** 

2.0 Transmission System

(1) Type: Fixed-spindle Power Shift

(2) Shift Gear Control Oil Pressure(3) Rated Input Speed2500(rpm)

3.0 Bucket

(1) Bucket Capacity:0.72 m3(2) Bucket Width:20400mm

(3) Bucket Type: Heavy-duty Bolt on Teeth

(4) Rated Load: 2500kg(5) Operating Weight 5200kg

4.0 Overall Dimensions

(1) Overall Length(bucket on ground); 5710mm

(2) Overall Height;

(3) Ground to Cab Top:2840mm(4) Dumping Height:2850mm(5) Min. Base to the Ground275mm(6) Overall Width2040mm

**5.0 Operating Specifications** 

(1) Steering System: Articulated Frame with Hydraulic Power Steering

(2) Min. Turning Radius: 5460mm

(3) Driving System: Hydraulic Converter

6.0 Brake System

(1) Service Brake Four wheel Hydraulic Spread-shoed Brake

(2) Parking Brake Hand Operated















