

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 8.6 Revision Date 15.04.2023 Print Date 28.08.2023

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : DPX Mountant for histology

Product Number : 44581 Brand : Sigma

REACH No. : This product is a mixture. REACH Registration Number see

section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Scientific research and development

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Israel Ltd. Tel Aviv

3 PARK RABIN, PLAUT 76100 REHOVOT

ISRAEL

Telephone : +972 972 8948-4222 Fax : +972 972 8948-4200

1.4 Emergency telephone

Emergency Phone # : +972 (8) 948-4222

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Skin irritation (Category 2), H315

Eye irritation (Category 2), H319

Reproductive toxicity (Category 1B), H360FD

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous

system, Liver, Kidney, H373

Aspiration hazard (Category 1), H304

Long-term (chronic) aquatic hazard (Category 3), H412

Sigma- 44581 Page 1 of 16



For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Hazard statement(s)

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways. H312 + H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H360FD May damage fertility. May damage the unborn child.

H373 May cause damage to organs (Central nervous system, Liver,

Kidney) through prolonged or repeated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P331 Do NOT induce vomiting.

Supplemental Hazard

Statements

none

Restricted to professional users.

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard statement(s)

H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.
H360FD May damage fertility. May damage the unborn child.

Precautionary statement(s)

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Supplemental Hazard none

Sigma- 44581 Page 2 of 16

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration		
Xylene					
CAS-No. EC-No. Index-No. Registration number	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32- XXXX	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Chronic 3; H226, H332, H312, H315, H319, H335, H373, H304, H412	>= 90 - <= 100 %		
dibutyl phthalate Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)					
CAS-No. EC-No. Index-No.	84-74-2 201-557-4	Repr. 1B; Aquatic Acute 1; Aquatic Chronic 2; H360FD, H400, H411 M-Factor - Aquatic Acute: 1	>= 10 - < 20 %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Sigma- 44581 Page 3 of 16



4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

Sigma- 44581 Page **4** of **16**

A

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Fluorinated rubber Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Sigma- 44581 Page 5 of 16

M

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 30 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state liquid

b) Color
 c) Odor
 d) Melting point/freezing point

No data available
No data available

e) Initial boiling point and boiling range

No data available

f) Flammability (solid,

No data available

gas)

g) Upper/lower flammability or explosive limits

No data available

h) Flash point 28 °C

i) Autoignition No data available

Sigma- 44581 Page 6 of 16



temperature

j) Decomposition No data available temperature

k) pH No data available

I) Viscosity Viscosity, kinematic: No data available

Viscosity, dynamic: No data available

m) Water solubilityNo data availablen) Partition coefficient:No data available

n-octanol/water

o) Vapor pressure No data available

p) Density 1 g/cm3

Relative density No data available q) Relative vapor No data available

density

r) Particle No data available

characteristics

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Bases, Strong oxidizing agents, acids, Chlorine, Nitrates

10.6 Hazardous decomposition products

In the event of fire: see section 5

Sigma- 44581 Page 7 of 16



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and

gastrointestinal tract.

Symptoms: Possible symptoms:, mucosal irritations, Cough, Shortness of breath, Possible

damages:, damage of respiratory tract

Acute toxicity estimate Inhalation - 4 h - 11,1 mg/l - vapor(Calculation method)

Acute toxicity estimate Dermal - 1.101 mg/kg (Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes skin irritation.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye irritation.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

May harm the unborn child.

May impair fertility.

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Mixture may cause damage to organs through prolonged or repeated exposure.

- Central nervous system, Liver, Kidney

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment This substance/mixture contains components

considered to have endocrinedisrupting properties affecting human health, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated

Regulation (EU) 2017/2100.

Sigma- 44581 Page 8 of 16

A

Exposure can cause damage to the:, Central nervous system depression, Dermatitis, Anorexia., Bronchitis., Tremors, Blurred vision, Incoordination., Headache, Vomiting, Dizziness, Weakness, anemia, Prolonged or repeated exposure to skin causes defatting and dermatitis.

Central nervous system depression, Dermatitis, Anorexia., Shortness of breath, Bronchitis., Tremors, Blurred vision, Incoordination., Headache, Dizziness, Weakness Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Components

Xylene

Acute toxicity

LD50 Oral - Rat - male - 3.523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

Remarks: (ECHA)

LC50 Inhalation - Rat - male - 4 h - 29,09 mg/l - vapor

(Regulation (EC) No. 440/2008, Annex, B.2)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

LD50 Dermal - Rabbit - > 1.700 mg/kg

Remarks: (RTECS)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 24 h

Remarks: (IUCLID)

Remarks: Drying-out effect resulting in rough and chapped skin.

After long-term exposure to the chemical:

Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation. - 24 h

Remarks: (RTECS)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative

Remarks: (National Toxicology Program)

Sigma- 44581 Page 9 of 16



Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 478 Species: Mouse - male and female

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Central nervous system, Liver, Kidney

Aspiration hazard

May be fatal if swallowed and enters airways.

dibutyl phthalate

Acute toxicity

LD50 Oral - Rat - male and female - 6.279 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - >= 15,68 mg/l - aerosol

Remarks: (ECHA)

LD50 Dermal - Rabbit - > 21.000 mg/kg

Remarks: (RTECS)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 72 h (OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Result: negative Remarks: (ECHA)

Sigma- 44581 Page 10 of 16

Species: Mouse Result: negative Remarks: (ECHA) Carcinogenicity No data available

Reproductive toxicity

May damage the unborn child.

May damage fertility.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

Components

Xylene

Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2,60

mg/I - 96 h

(OECD Test Guideline 203)

Sigma- 44581 Page 11 of 16

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata - 4,36 mg/l -

73 h

(OECD Test Guideline 201)

Toxicity to bacteria Remarks: (ECHA)

Toxicity to flow-through test NOEC - Oncorhynchus mykiss (rainbow trout)

fish(Chronic toxicity) - > 1,3 mg/l - 56 d

Remarks: (ECHA)

Toxicity to daphnia and other aquatic invertebrates(Chronic

NOEC - Ceriodaphnia dubia (water flea) - 0.96 mg/l - 7 d

(US-EPA)

toxicity)
dibutyl phthalate

Toxicity to fish static test LC50 - Lepomis macrochirus (Bluegill sunfish) - ca.

0,48 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - ca. 2,99 mg/l

- 48 h (US-EPA)

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata (green algae)

- 0,75 mg/l - 10 d

(US-EPA)

static test NOEC - Pseudokirchneriella subcapitata (green algae)

- 0,39 mg/l - 10 d

(US-EPA)

Toxicity to bacteria EC50 - Tetrahymena pyriformis - 2,2 mg/l - 24 h

Remarks: (ECHA)

Toxicity to

flow-through test NOEC - Oncorhynchus mykiss (rainbow trout)

fish(Chronic toxicity) - 0,1 mg/l - 99 d

(US-EPA)

Toxicity to daphnia and other aquatic invertebrates(Chronic

flow-through test NOEC - Daphnia magna (Water flea) - 0,158

mg/l - 21 d

nic (OECD Test Guideline 211)

toxicity) Remarks: (in analogy to similar products)

The value is given in analogy to the following substances:

Bis(2-ethylhexyl) phthalate

Sigma- 44581 Page 12 of 16

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

14.1 UN number

IMDG: 1993 IATA: 1993 ADR/RID: 1993

14.2 UN proper shipping name

ADR/RID: FLAMMABLE LIQUID, N.O.S. (Xylene) (Xylene) FLAMMABLE LIQUID, N.O.S. (Xylene) (Xylene) IMDG: IATA: Flammable liquid, n.o.s. (Xylene) (Xylene)

14.3 Transport hazard class(es)

IMDG: 3 IATA: 3 ADR/RID: 3

14.4 Packaging group

Canada

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Candidate List of Substances of Very : dibutyl phthalate High Concern for Authorisation (Article 59).

This product contains a substance listed on Annex XIV of the REACH Regulation (EC) Nr. 1907/2006.

Listed substance / Sunset Date : dibutyl phthalate / 21.02.2015

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

REACH - Restrictions on the manufacture, : dibutyl phthalate placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Sigma- 44581 Page 13 of 16

National legislation

Seveso III: Directive 2012/18/EU of the European : FLAMMABLE LIQUIDS Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Flammable liquid and vapor.
H319	May be fatal if swallowed and enters airways.
H332	Harmful in contact with skin or if inhaled.
H335	Causes skin irritation.
H360FD	Causes serious eye irritation.
H373	May cause respiratory irritation.
H400	May cause damage to organs (Central nervous system, Liver, Kidney)
	through prolonged or repeated exposure if inhaled.
H411	Harmful to aquatic life with long lasting effects.
H412	Causes skin irritation.

Sigma- 44581 Page 14 of 16



Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the m	Classification procedure:	
Flam. Liq.3	H226	Based on product data or assessment
Acute Tox.4	H332	Calculation method
Acute Tox.4	H312	Calculation method
Skin Irrit.2	H315	Calculation method
Eye Irrit.2	H319	Calculation method
Repr.1B	H360FD	Calculation method
STOT SE3	H335	Calculation method
STOT RE2	H373	Calculation method
Asp. Tox.1	H304	Based on product data or assessment
Aquatic Chronic3	H412	Calculation method

Sigma- 44581 Page 15 of 16



Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Sigma- 44581 Page 16 of 16

