
Algorithm 1: tGMM

Input: $x \in R^{T \times d}$: the time-series data. $\mu^0 \in R^{d \times c}$: an initial guess at the means. $\Sigma^0 \in R^{d \times d \times C}$: an initial guess at the covariances. $\pi \in R^{T \times C} : \sum_{c \in [C]} \pi[:, c] = 1$: some pi-vector indicating the contributions of each condition. $tol > 0$: the tolerance for defining convergence.**Result:** $\mu^n \in R^{d \times c}$: the tGMM estimated means. $\Sigma^n \in R^{d \times d \times c}$: the tGMM estimated true covariance matrices.

```
1  $ll = \text{loglikelihood}(x, \mu^0, \Sigma^0)$ 
2 converged = FALSE
3 while converged = FALSE do
4     // E step
5     for  $t$  in 1:T do
6          $s = \sum_{c'=1}^C \pi_{tc} \mathcal{N}(x_t | \mu'_{c'}, \Sigma'_{c'})$ 
7         for  $c$  in 1:C do
8              $\tilde{w}_{tc} = \frac{1}{s} \pi_{tc} \mathcal{N}(x_t, \mu_c \Sigma_c)$ 
9         end
10         $\tilde{w} = \sum_{c=1}^C \tilde{w}(\cdot, c)$ 
11         $w_{tc} = \tilde{w}^{-1} \tilde{w}_{tc}$ 
12         $\hat{w} = \sum_{t=1}^T \tilde{w}(t, \cdot)$  // added this line
13        // M step
14        for  $c$  in 1:C do
15             $\mu_c = \hat{w}^{-1} w_c^T x$ 
16             $\Sigma_c = \sum_{t=1}^T \hat{w}^{-1} w_{tc} (x_t - \mu_c)^T (x_t - \mu_c)$ 
17        end
18         $newll = \text{loglikelihood}(x, \mu, \Sigma)$ 
19        if  $newll - ll > tol$  then
20             $ll = newll$ 
21        else
22            converged = TRUE
23        end
24  $\text{loglikelihood}(x, \theta^i) \leftarrow \left( \sum_{i=1}^{nt} \log \left[ \sum_{c=1}^{nc} \pi_{ic} \mathcal{N}(x_i | \mu_c^i, \Sigma_c^i) \right] \right)$ 
```

generate data: C=2 d=1 T=100 sigma=1 mu=-3, 3 pi(all els) = [1,0] for the first half, [0,1] for the second half

initialize:

pi=pi mu=mu sigma=sigma

initialize some wrong way