Wire ID		Pattern A	Edge A	Cursor A	-350us	-300us CA	-250us	-200us	-150us	-100us	-50us	T+272.5us +	50us +1	00us +	150us +	+200us	+250u	+300us	+350us
				-			1 1 8	-					-	-	-				
D11	Н	×		1															
							\rightarrow						-		-	\rightarrow			
D10	Н	×		1				11 11111 1111											
D12	L	×	t	1															
D13	Н	×		1				11 11111 111											
D31	L	×		0		-													
D24	L	×		0															
D17	L	×		0															
		D11 H D10 H D12 L	D Status A	D	ID Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A	D Status A A A A A A A A A

CLK1 Freq: 0Hz

D3 Period: >100ms

Interval A->B: 485.5us

D1 Transitions A->B: 8

Test_Serial.LPF

5/3/2015 7:41:01 AM