# JUnit

CS 490MT/5555, Fall 2015, Yongjie Zheng

### **JUnit**

- An open source framework to write and run tests. JUnit features include:
  - Assertions for testing expected results
  - Annotations for identifying methods that specify a test
  - Test runners for running tests
- JUnit was written by Erich Gamma (of Design Patterns fame) and Kent Beck (creator of XP methodology)
- Available as a stand-alone application and built into Eclipse.
  - The current version of the Eclipse JDT has the JUnit plug-in built in.

### Write a Test Class with JUnit

```
public class Hello{
                                         public class HelloTest {
 public String say(){
                                           private Hello h;
  return "Hello";
                                           @Before
                                           public void setUp() {
                                            h = new Hello();
 pubic String echo(String s){
  if (s == null){
    throw new Exception();
                                           @After
                                           public void tearDown() {}
                                           @Test
  return s;
                                           public void testSay() {
                                            assertEquals("Hello", h.say());
```

# Steps to write a test case with JUnit

- Define a Test class.
- Optionally override the methods annotated with @before, @after to create or release object(s) under test.
- Define one or more public testXXX() methods (annotated with @Test). Within each method,
  - Call the method being tested and get the actual result
  - Assert what the correct result should be with one of the provided assert methods
  - These steps can be repeated as many times as necessary
- ▶ Test methods are independent of each other.

## **JUnit Annotations**

| Annotation                                    | Description  |
|---|--|
| @Test public void method()                    | The annotation @Test identifies that a method is a test method.                    |
| @Before public void method()                  | Executes the method before <b>EACH</b> test. This method sets up the test data.    |
| @After public void method()                   | Executes the method after <b>EACH</b> test. This method can cleanup the test data. |
| @BeforeClass public static void method()      | Executes the method once, before the start of <b>ALL</b> tests.                    |
| @AfterClass public static void method()       | Executes the method once, after <b>ALL</b> tests have been finished.               |
| @lgnore                                       | Ignores the test method.   |
| <pre>@Test (expected = Exception.class)</pre> | Fails, if the method does not throw the named exception.                           |
| @Test(timeout=100)                            | Fails, if the method takes too long.   |

### Test Fixtures

- A test fixture is the data (both objects and primitives)
   that are needed to run tests
  - JUnit supports sharing the setup code
- public void setUp() (annotated with @Before)
  - Sets up the test data (fixture).
  - Called before EVERY test case method.
- public void tearDown() (annotated with @After)
  - Tears down the test fixture.
  - Called after EVERY test case method.
- public static void setUpBeforeClass() (@BeforeClass)
- public static void tearDownAfterClass() (@AfterClass)

### JUnit Assert Methods

- JUnit assert is a collection of static methods defined for checking actual values against expected values
- We only used assertEquals in previous example, but there are additional assert methods
- JUnit static import
  - To use these assert methods without mentioning the class name, the static import statement is usually added at the beginning of each test class.
  - import static org.junit.Assert.\*;

### JUnit Assert Methods

| Method  | Meaning   |
|---|---|
| fail([String])                                    | Causes the test to fail.                                |
| assertsEquals([String message], expected, actual) | Test if the values are the same.                        |
| assertNull([message], object)                     | Checks if the object is null.                           |
| assertNotNull([message], object)                  | Check if the object is not null.                        |
| assertSame([String], expected, actual)            | Check if both variables refer to the same object.       |
| assertNotSame([String], expected, actual)         | Check that both variables refer not to the same object. |
| assertTrue([message], boolean condition)          | Check if the boolean condition is true.                 |
| assertFalse([message], boolean condition)         | Check if the boolean condition is false.                |

# Testing Exceptions (two different ways)

```
public void testEcho(){
    try {
        public void testEcho(){
        h.echo();
        fail("should raise an exception");
    }
} catch (Exception e){
    //expected
}
```

### Test Suite

- ▶ Test Suite is a composite of Tests, or a combination of test classes.
  - A suite usually contains a set of test classes, but a suite can contain another suite and so on.
- Most IDEs create suites for you. If you have to create suites yourself:

```
import org.junit.runners.RunWith;
import org.junit.runners.Suite;
import org.junit.runners.Suite.SuiteClasses;
@RunWith(Suite.class)
@SuiteClasses({ MyClassTest.class, MySecondClassTest.class })
public class AllTests {
}
```

### Test Runner

- Running a TestSuite will automatically run all of its subordinate Test class instances and TestSuite instances.
- Running a Test class will automatically invoke all of its annotated @Test methods. In other words, one Test class could result in multiple tests.
  - All test methods can be executed in an arbitrary order.
- For each @Test method
  - Run @Before method if defined
  - Run @Test method steps
  - Run @After method if defined

# Integration Tests With JUnit

- JUnit is primarily used for unit test.
- There is no clear line between unit test and integration test.
  - A specific method may involve the integration logic.
- Two ways to do integration tests with JUnit
  - Do unit test, as previously discussed, on a method that includes the logic of calling other objects.
  - Define a testXXX() method that tests a specific transaction, instead of a method. In this testXXX(), call related objects to check if the transaction is implemented correctly.

### Note that

- ▶ The version we are using is JUnit 4
  - The previous version is JUnit 3, which did not support annotations (@Before, @After, @Test, ...).
- Additional information
  - JUnit Pocket Guide (Search "JUnit" at <a href="http://proquest.safaribooksonline.com">http://proquest.safaribooksonline.com</a>)
  - JUnit Tutorial <a href="http://www.vogella.com/articles/JUnit/article.html">http://www.vogella.com/articles/JUnit/article.html</a>