

Problems

Status

Standings

A Bit Fun

Tags:

Time Limit: 2 s

Memory Limit: 256 MB

Submission: 46

AC: 8

Score: 99.62

Submit

Codes

AI Code Tips

Description

There are n numbers in a array, as $a_0, a_1 \dots, a_{n-1}$, and another number m . We define a function $f(i, j) = a_i | a_{i+1} | a_{i+2} | \dots | a_j$. Where " $|$ " is the bit-OR operation. ($i \leq j$)

The problem is really simple: please count the number of different pairs of (i, j) where $f(i, j) < m$.

Input

The first line has a number T ($T \leq 50$), indicating the number of test cases.

For each test case, first line contains two numbers n and m . ($1 \leq n \leq 1e5, 1 \leq m \leq 2^{30}$) Then n numbers come in the second line which is the array a , where $1 \leq a_i \leq 2^{30}$.

Output

For every case, you should output "Case # t : " at first, without quotes. The t is the case number starting from 1.

Then follows the answer.

Samples

input Copy

```
2
3 6
1 3 5
2 4
5 4
```

output Copy

```
Case #1: 4
Case #2: 0
```

Hint

HDU-4737 加强了数据

Author

PAN, Lyuzhi

Submit

Codes

HZNUOJ is based on HUSTOJ

--- [Maintainer List](#) ---

Server Time: 2025-8-26 16:03:19