

Date: 14/10/25

EXERCISE 18

Structure of 'restaurants' collection:

```
{
  "address": {
    "building": "1007",
    "coord": [ -73.856077, 40.848447 ],
    "street": "Morris Park Ave",
    "zipcode": "10462"
  },
  "borough": "Bronx",
  "cuisine": "Bakery",
  "grades": [
    { "date": { "$date": "1393804800000" }, "grade": "A", "score": 2 },
    { "date": { "$date": "1378857600000" }, "grade": "A", "score": 6 },
    { "date": { "$date": "1358985600000" }, "grade": "A", "score": 10 },
    { "date": { "$date": "1322006400000" }, "grade": "A", "score": 9 },
    { "date": { "$date": "1299715200000" }, "grade": "B", "score": 14 }
  ],
  "name": "Morris Park Bake Shop",
  "restaurant_id": "30075445"
}
```

1. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or restaurant's name begins with letter 'Wil'.

db.restaurants.find({\$or: [{name: {\$regex: /^Wil/}}, {cuisine: {\$nin: ["American", "Chinees"]}}], \$restaurant_id: 1, name: 1, borough: 1, cuisine: 1});

2. Write a MongoDB query to find the restaurant Id, name, and grades for those restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08-11T00:00:00Z" among many of survey dates..

db.restaurants.find({"grades": {\$elemMatch: {grade: "A", score: 11, date: ISODate("2014-08-11T00:00:00Z")}}}, {"restaurant_id": 1, name: 1, grades: 1});

3. Write a MongoDB query to find the restaurant Id, name and grades for those restaurants where the 2nd element of grades array contains a grade of "A" and score 9 on an ISODate "2014-08-11T00:00:00Z".

db.restaurants.find({"grades.1.grade": "A", "grades.1.score": 9, "grades.1.date": ISODate("2014-08-11T00:00:00Z")}, {"restaurant_id": 1, name: 1, grades: 1});

4. Write a MongoDB query to find the restaurant Id, name, address and geographical location for those restaurants where 2nd element of coord array contains a value

which is more than 42 and upto 52..

```
db.restaurants.find({'address.coord.1': {'$gt': 42, '$lte': 52}}, {'restaurant_id': 1, name: 1, address: 1});
```

5. Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.

```
db.restaurants.find().sort({'name': 1});
```

6. Write a MongoDB query to arrange the name of the restaurants in descending order along with all the columns.

```
db.restaurants.find().sort({'name': -1});
```

7. Write a MongoDB query to arranged the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.

```
db.restaurants.find().sort({'cuisine': 1, borough: -1});
```

8. Write a MongoDB query to know whether all the addresses contains the street or not.

```
db.restaurants.find({'address.street': {'$exists': true}});
```

9. Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.

```
db.restaurants.find({'address.street': {'$exists': true, 'type': 'double'}});
```

10. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.

```
db.restaurants.find({'grades.score': {'$mod': [7, 0]}}, {'restaurant_id': 1, name: 1, grades: 1});
```

11. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.

```
db.restaurants.find({'name': {'$regex': /'Mad/i'}}, {'name': 1, borough: 1, 'address.coord': 1, cuisine: 1});
```

12. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.


```
db.restaurants.find({name: ({name: {$regex: /^Mad/}}), $name: 1, borough: 1, "address.coord": 1, cuisine: 1});
```

13. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5.

```
db.restaurants.find({"grades.score": {$lt: 5}});
```

14. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan.

```
db.restaurants.find({borough: "Manhattan", "grades.score": {$lt: 5}});
```

15. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn.

```
db.restaurants.find({borough: {$in: ["Manhattan", "Brooklyn"]}, "grades.score": {$lt: 5}});
```

16. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

```
db.restaurants.find({borough: {$in: ["Manhattan", "Brooklyn"]}, cuisine: {$ne: "American"}, "grades.score": {$lt: 5}});
```

17. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

```
db.restaurants.find({borough: {$in: ["Manhattan", "Brooklyn"]}, cuisine: {$nin: ["American", "Chinese"]}, "grades.score": {$lt: 5}});
```

18. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6.

```
db.restaurants.find({$or: {"grades.score": {$all: [2, 6]}}});
```

19. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan.

```
db.restaurants.find({borough: "Manhattan", "grades.score": {$all: [2, 6]}});
```

20. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn.

```
db.restaurants.find({borough: {$in: ["Manhattan", "Brooklyn"]}, "grades.score": {$all: [2, 6]}});
```

21. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

db.restaurants.find(\$borough:\$in:["Manhattan", "Brooklyn"], cuisine:\$ne:"American", grades.score:\$all:[2,6]);

22. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

db.restaurants.find(\$borough:\$in:["Manhattan", "Brooklyn"], cuisine:\$nin:["American", "Chinese"], grades.score:\$all:[2,6]);

23. Write a MongoDB query to find the restaurants that have a grade with a score of 2 or a grade with a score of 6.

db.restaurants.find(\$grades.score:\$nin:[2,6]);

Sample document of 'movies' collection

```
{
  "_id": ObjectId("573a1390f29313caabcd42e8"),
  "plot": "A group of bandits stage a brazen train hold-up, only to find a determined posse hot on their heels.",
  "genres": [ 'Short', 'Western' ],
  "runtime": 11,
  "cast": [
    'A.C. Abadie',
    'Gilbert M. 'Broncho Billy' Anderson',
    'George Barnes',
    'Justus D. Barnes'
  ],
  "poster": 'https://m.media-amazon.com/images/M/MV5BMTU3NjE5NzYtYTYyNS00MDVmLWlwYjgtMmYwYWlxZDYyNzU2XkEyXkFqcGdeQXVyNzQzNzQxNzI@._V1_SY1000_SX677_AL_.jpg',
  "title": 'The Great Train Robbery',
  "fullplot": "Among the earliest existing films in American cinema - notable as the first film that presented a narrative story to tell - it depicts a group of cowboy outlaws who hold up a train and rob the passengers. They are then pursued by a Sheriff's posse. Several scenes have color included - all hand tinted."
}
```

```

languages: [ 'English' ],
released: ISODate("1903-12-01T00:00:00.000Z"),
directors: [ 'Edwin S. Porter' ],
rated: 'TV-G',
awards: { wins: 1, nominations: 0, text: '1 win.' },
lastupdated: '2015-08-13 00:27:59.177000000',
year: 1903,
imdb: { rating: 7.4, votes: 9847, id: 439 },
countries: [ 'USA' ],
type: 'movie',
tomatoes: {
viewer: { rating: 3.7, numReviews: 2559, meter: 75 },
fresh: 6,
critic: { rating: 7.6, numReviews: 6, meter: 100 },
rotten: 0,
lastUpdated: ISODate("2015-08-08T19:16:10.000Z")
}

```

1. Find all movies with full information from the 'movies' collection that released in the year 1893.

db.movies.find({year:1893})

2. Find all movies with full information from the 'movies' collection that have a runtime greater than 120 minutes.

db.movies.find({runtime:{ \$gt:120}})

3. Find all movies with full information from the 'movies' collection that have "Short" genre.

db.movies.find({genres:"Short"})

4. Retrieve all movies from the 'movies' collection that were directed by "William K.L. Dickson" and include complete information for each movie.

```
db.movies.find ({director: "William K.L. Dickson"})
```

5. Retrieve all movies from the 'movies' collection that were released in the USA and include complete information for each movie.

```
db.movies.find ({country: 'USA'})
```

6. Retrieve all movies from the 'movies' collection that have complete information and are rated as "UNRATED".

```
db.movies.find ({rated: 'UNRATED'})
```

7. Retrieve all movies from the 'movies' collection that have complete information and have received more than 1000 votes on IMDb.

```
db.movies.find ({imdb_rating: {$gt: 7}})
```

8. Retrieve all movies from the 'movies' collection that have complete information and have an IMDb rating higher than 7.

```
db.movies.find ({imdb_rating: {$gt: 4.33}})
```

9. Retrieve all movies from the 'movies' collection that have complete information and have a viewer rating higher than 4 on Tomatoes.

```
db.movies.find ({ "tomatoes.viewer.rating": {$gt: 4.33}})
```

10. Retrieve all movies from the 'movies' collection that have received an award.

```
db.movies.find ({ "awards.wins": {$gt: 0}});
```

11. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB that have at least one nomination.

```
db.movies.find ({ "awards.nominations": {$gt: 0}});
```

12. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB with cast

```
db.movies.find ({cast: "Charles Kayser", title: 1, languages: 1, released: 2008});
```


including "Charles Kayse:".

13. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that released on May 9, 1893.

```
db.movies.find ( $released: ISODate ('1893-05-09T00:00:00Z') & $title:1, languages:1, released:1 );
```

14. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that have a word "scene" in the title.

```
db.movies.find ( $title: { $regex: /scene/i } ,  
$title:1 , languages:1 , released:1 , directors:1 ,  
writers:1 , countries:1 , id=0 );
```

Evaluation Procedure	Marks awarded
PL/SQL Procedure(5)	5
Program/Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	

210