Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 12 November 2024, 7:04 AM
Duration	41 days 10 hours
Correct Marked out of	Write a program that prints a simple chessboard. Input format:
	The first line contains the number of inputs T.
	The lines after that contain a different values for size of the chessboard

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Output format:

Input:

2

5

Output:

WBW BWB WBW WBWBW VVUVVUVV

BWBWB

WBWBW

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 + {
       int v;
 4
 5
       scanf("%d",&v);
 6
       while(v>0)
7 *
8
           int x;
           scanf("%d",&x);
9
           if(x<0)
10
11 +
12
               X=-X;
13
           char a ='W';
14
           for(int i=0;i<x;i++)
15
16 .
17
               for(int j=0;j<x;j++)</pre>
18 .
                   printf("%c",a);
19
                   if(a=='W')
20
                       a='B';
21
22
                   else
                   a='W';
23
24
               printf("\n");
25
               if(x\%2==0)
26
27 +
                   if(a=='W')
28
29
                      a='B';
30
                   else
                     a='W';
31
32
33
34
           V--;
35
36 }
```

	Input	Expected	Got	
~	2	WBW	WBW	~
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests! ✓

Question 2 Let's print a chessboard! Correct Marked out of 5.00 Write a program that takes input: Flag question The first line contains T, the number of test cases Each test case contains an integer N and also the starting character of the chessboard Output Format Print the chessboard as per the given examples Sample Input / Output Input: 2 2 W 3 B Output: WB BW BWB WBW BWB

```
Answer: (penalty regime: 0 %)
```

```
1 #include<stdio.h>
2 int main()
3 + {
4
       int T,d,i,i1,i2,o,z;
 5
       char c,s;
       scanf("%d",&T);
 6
7
       for(i=0;i<T;i++)
8 +
           scanf("%d %c",&d,&s);
9
           for(i1=0;i1<d;i1++)
10
11 .
               z=(s=='W') ? 0:1;
12
13
               o=(i1%2==z) ?0:1;
14
               for(i2=0;i2<d;i2++)
15 +
                  c=(i2%2==o) ? 'W' : 'B';
16
                  printf("%c",c);
17
18
               printf("\n");
19
20
21
22
       return 0;
23 }
```

	Input	Expected	Got	
~	2	WB	WB	~
2 W 3 B	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! <

Question 3 Correct Marked out of 7.00

Flag question

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be:

10203010011012

**4050809

****607

If N= 4, then pattern will be:

1020304017018019020

**50607014015016

****809012013

*****10011

Constraints

2 <= N <= 100

Input Format

First line contains T, the number of test cases

Each test case contains a single integer N

Output

First line print Case #i where i is the test case number

```
Test Case 1
3
3
5
Output
Case #1
10203010011012
**4050809
****607
Case #2
1020304017018019020
**50607014015016
****809012013
*****10011
Case #3
102030405026027028029030
**6070809022023024025
****10011012019020021
*****13014017018
******15016
```

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2
    int main()
3 + {
 4
        int v,c=0;
 5
        scanf("%d",&v);
 6
        while(v!=0)
 7 .
 8
            C++;
 9
            int a;
10
            scanf("%d",&a);
            int s1=10,s2=(a*a*10)+10;
11
12
            printf("Case #%d\n",c);
13
            for(int i=0;i<a;i++)
14 ,
                for(int j=0;j<i;j++)
15
16 •
                   printf("**");
17
18
                for(int j=0;j<a-i;j++)
19
20 +
                   printf("%d",s1);
21
22
                    s1+=10;
23
            for(int j=0;j<a-i;j++)</pre>
24
25 +
26
                if((j+1)==(a-i))
27 +
                   printf("%d",((s2+(j*10)))/10);
28
29
30
                else
31 +
                   printf("%d",(s2+(j*10)));
32
33
34
35
            s2-=(a-i)*10;
36
            52+=10;
            printf("\n");
37
38
39
            V--;
40
41 }
```

	Input	Expected	Got	
~	3	Case #1	Case #1	~
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		******10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	
		****10011012019020021	****10011012019020021	
		******13014017018	******13014017018	
		*******15016	*******15016	

Passed all tests! 🗸

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Monday, 18 November 2024, 7:17 PM
Duration	34 days 22 hours
Correct Marked out of	The k-digit number N is an Armstrong number if and only if the k-th power of each digit sums to N. Given a positive integer N, return true if and only if it is an Armstrong number.
	Example 1: Input:
	153

Output:

Explanation:

Example 2:

Input:

123

153 is a 3-digit number, and $153 = 1^3 + 5^3 + 3^3$.

true

Output:
false
Explanation:
123 is a 3-digit number, and 123 != 1^3 + 2^3 + 3^3 = 36.
Example 3:
Input:
1634
Output:
true
Note:
1 <= N <= 10^8

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 + {
4
      int a,b=0,c,e=0;
      scanf("%d",&a);
5
 6
      if(a<0)
 7
       a=-a;
8
      c = a;
       while(c!=0)
9
10 .
          c/=10;
11
          e++;
12
13
14
       c = a;
15
       while(c!=0)
16 +
17
          int d = c%10;
          int f = 1;
18
          for(int i=0;i<e;i++)
19
20 .
             f*=d;
21
22
23
          b+=f;
          c/=10;
24
25
26
       if(a==b)
27 *
          printf("true");
28
29
30
       else
31 +
          printf("false");
32
33
       return 0;
34
35 }
```

	Input	Expected	Got	
~	153	true	true	~
~	123	false	false	~

Passed all tests! <

Question **2**Correct

Marked out of 5.00

Flag question

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
   int main()
2
3 √ {
       int rn,n,nt=0,i=0;
4
       scanf("%d",&n);
5
6 1
       do{
7
           nt = n;
8
           rn = 0;
           while(n!=0)
9
10
               rn = rn*10+n%10;
11
               n = n/10;
12
13
14
           n = nt + rn;
15
           i++;
       }while(rn!=nt || i==1);
16
       printf("%d",rn);
17
18
       return 0;
19 }
```

	Input	Expected	Got	
~	32	55	55	~
~	789	66066	66066	~

Passed all tests! <

Question **3**Correct
Marked out of 7.00

P Flag question

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:

3

Sample Output 1:

33

Explanation:

Here the lucky numbers are 3, 4, 33, 34., and the 3rd lucky number is 33.

Sample Input 2:

34

Sample Output 2:

33344

```
Answer: (penalty regime: 0 %)
```

```
1 |#include<stdio.h>
 2 int con(int a)
3 + {
 4
       int c = a;
 5
       while(c!=0)
 6 +
           int d = c%10;
 7
           if(d!=3 && d!=4)
 8
 9
             return 0;
10
           c/=10;
11
12
       return 1;
13
   int main()
14
15 + {
16
       int a , b=0;
       scanf("%d",&a);
17
18
       while(a!=0)
19 +
           b++;
20
           if(con(b))
21
22 *
23
               a--;
24
25
       printf("%d",b);
26
27
       return 0;
28 }
```

		Input	Expected	Got	
~	/	34	33344	33344	~

Passed all tests! ✓