

Document	Datasheet
Type	Ceramic Patch Antenna
Application	GPS L1
Part No.	YDRA-A18-1575
Revision	0


# DATASHEET

## Application

Navigation  
DSC

## Features

High efficiency, High directivity  
Pin type  
Pb-free Condition  
RoHS Compliant



# AMOTECH

### Notes

*The contents of this datasheet are subject to change without notice. Please confirm the specifications and delivery conditions when placing your order.*

## Revision History

Rev. No	Date	Title	Contents	Page
0	2009.06.16		First, documented	-

## Table of Content

1. Specifications	3
1.1 Electrical Specifications	3
1.2 Mechanical Specifications	3
1.3 Drawing and Marking	3
2. PCB Design for Test	4
2.1 Evaluation Board Dimension	4
3. Measurement Result	4
3.1 Typical Measurement Result (RL, Smithchart)	4
3.2 Typical Measurement Result (Gain, Radiation Pattern)	5
4. Reliability	6
5. Soldering	6
6. Packaging	6

## 1. Specifications

### 1.1 Electrical Specifications


No	Item	Spec.	Remark
1	Center Frequency(fc) [MHz]	1575.0 ± 3	
2	Return Loss [dB]	Min .15	
3	Axial Ratio @ fc	Typ. 3.0	
4	Zenith Gain@fc [dBic]	Typ. 3.0	
5	Polarization	RHCP	
6	Impedance [ $\Omega$ ]	Nominal 50	

- ✓ fc is mid point of loop/cusp in smith chart
- ✓ Measured on50x50mm FR4 ground plane

### 1.2 Mechanical Specifications

No	Item	Spec.	Remark
1	Dimensions (L x W x H)	18x18x4 mm <sup>3</sup>	
2	Unit Weight	Typ. 6.1 g	
3	Operating Temperature	-40 ~ +90 °C	

### 1.3 Drawing and Marking




- \* Note
- Unit : mm
  - X.X : ±0.2
  - All Round Both Sides Max. 0.3 Chamfer

- V : Line section
- W : Year
- XX : Month
- YY : Day
- ZZ : Serial number of daily

## 2. PCB Design for Test


### 2.1 Evaluation Board Dimension



✓ Evaluation board size ~ 50x50mm<sup>2</sup>

## 3. Measurement Result






### 3.1 Typical Measurement Result (RL, Smith chart)



✓ The results are measured on the 50x50mm<sup>2</sup> ground plane.

### 3.2 Typical Measurement Result (Gain, Radiation Pattern)

Frequency (MHz)	Peak Gain (dBic)	AR (dB)
1572.0	3.28	7.7
1575.0	3.95	1.9
1578.0	3.76	4.7



[3D Radiation Pattern]

## 4. Reliability

No	Item	Test condition	Requirement
1	Drop Test	1. Place antenna on set 2. 1.5m height 3. Drop 5 times	1. No Visible defect 2. S11 satisfy
2	Vibration Test	1. 5-55-5Hz, 1 Octave/min, Amp.=1.5mm, acceleration=2g, Crossover Freq.=18Hz, Hold time = 2H.R	1. No Visible defect 2. S11 satisfy
3	Humidity	1. 60℃, 95%RH, 96Hr	1. No Visible defect 2. S11 satisfy
4	Thermal Shock	1. +80℃(30min)→5min →-40℃ (30min) 2. 10 cycle	1. No Visible defect 2. S11 satisfy
5	High Temperature Resistance	1. +90℃, 96Hr	1. No Visible defect 2. S11 satisfy
6	Low Temperature Resistance	1. -40℃, 96Hr	1. No Visible defect 2. S11 satisfy
7	Adhesion Strength of Soldering	1. Used of pull push gauge.	1. Spec( min. 5kgf)

※ The sample must satisfy Requirement after 24 hours of test

※ Be base on IEC Climatic category (IEC68-1) -40℃ / +90℃ / 56h

## 5. Soldering

- Wettability to IEC 68-2-58 :≥75%(After Aging)
- Manual Soldering( By Iron) – Pb free
- Soldering Temperature : 300℃ ± 5℃, 5sec max. (Solder : Sn/Ag/Cu:96.5/3.0/0.5 )
- Must comply with above soldering condition to prevent from degradation of antenna performance.

## 6. Packaging

### 6.1 Packaging Quantity

Item	Quantity	Dimension
Tray	70 ea	334 * 174 (mm <sup>3</sup> )
Inner Box	700 ea (10 Tray)	370 * 195 * 130 (mm <sup>3</sup> )
Outer Box	2100 ea (3 Inner Box)	390 * 620 * 150 (mm <sup>3</sup> )