

Demo Application UI Guide (QuickRearCam)

Version 0.7.0

Display Audio

Solution Team



Release information

The following changes have been made to this document.

Change History

Date	Change
15 Nov. 2018	Applying single application framework and Using configuration file for display for v0.7.0
04 Dec. 2017	First release for v0.6.0

Proprietary Notice

Information in this document is provided solely to enable system and software implementers to use Nexell products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Nexell reserves the right to make changes without further notice to any products herein.

Nexell makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Nexell assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Nexell data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Nexell does not convey any license under its patent rights nor the rights of others. Nexell products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Nexell product could create a situation where personal injury or death may occur. Should Buyer purchase or use Nexell products for any such unintended or unauthorized application, Buyer shall indemnify and hold Nexell and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Nexell was negligent regarding the design or manufacture of the part.

Copyright© 2018 Nexell Co.,Ltd. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electric or mechanical, by photocopying, recording, or otherwise, without the prior written consent of Nexell.

Contact us

[11595] BundangYemiji Bldg. 12F, 31 Hwangsaeul-ro 258 beon gil, Bundang-gu, Sungnam-city, Gyeonggi-do, Korea.

TEL: 82-31-698-7400

FAX:82-31-698-7455

<http://www.nexell.co.kr>

Contents

Chap 1.	Overview	1
1.1	Overview.....	1
1.2	Block Diagram.....	1
1.3	Application UI.....	1
1.4	Configuration File.....	2
Chap 2.	Camera Library	3
2.1	Overview.....	3
2.2	APIs.....	3
Chap 3.	History	6
3.1	Known Issue.....	6
3.2	To do list.....	6


Chap 1. Overview

1.1 Overview

This document describes NxQuickRearCam that is demo application for Display Audio. The NxQuickRearCam is operated after taking over camera application of kernel layer. In demo application, the GPIO pin is back-gear. The application is run by GPIO pin.


1.2 Block Diagram

The NxQuickRearCam structure see as below. The application send signal to kernel for obtain control when it is started. The application is run automatically by back-gear detection.



1.3 Application UI

The Application see as below, this is displayed camera screen and parking guideline.



1.4 Configuration File

The configuration file (config.xml) includes configuration values for display. It is in the folder “/nexell/daudio/NxQuickRearCam”. If the file does not exist, the application is run by default values and the configuration file is created with default values when the application is stopped. Configuration values are crtc index and layer index for display. If crtc index is “0” and layer index is “0”, video images are displayed at video layer of 1st crtc.

The format is as in the following.

[config.xml]

```
<?xml version="1.0" encoding="UTF-8"?>
<map>
  <string name="crtc_idx">0</string>
  <string name="layer_idx">0</string>
</map>
```

Chap 2. Camera Library

2.1 Overview

The libnxrearcam provides to manage camera. This usage of library see as below.

2.2 APIs

2.2.1 NXDA_ShowRearCam()

```
int32_t NXDA_ShowRearCam(
    CAMERA_INFO *pCamInfo,
    DISPLAY_INFO *pDspInfo
);
```

Description

Show Rear Camera.

Parameter

-. pCamInfo : Camera Information
-. pDspInfo : Display Information

Return Value

Please describe return value.

2.2.2 NXDA_HideRearCam()

```
void NXDA_HideRearCam(
    void
);
```

Description

Hide Rear Camera.

Parameter

None.

Return Value

None

2.2.3 NXDA_RegRenderCallback()

```
void NXDA_RegRenderCallback(
    void *pApp
```

<pre>int32_t (callback)(void *, int32_t, void*, int32_t));</pre>	
Description	Register Rear Camera render callback.
Parameter	<pre>-. pApp : private handle. -. callback : redering callback. int32_t callback(void* pApp, int32_t type, void* data, int32_t dataSize) -. pApp : private handle. -. type : callback function type. (CB_TYPE_BUFFER, CB_TYPE_HIDE, CB_TYPE_SHOW) -. data : send data for callback. -. dataSize : size of data</pre>
Return Value	None

2.2.4 NXDA_RegControlCallback()

<pre>void NXDA_RegControlCallback(void *pApp, int32_t (callback)(void *, int32_t, void *, int32_t));</pre>	
Description	Register Rear Camera control callback.
Parameter	<pre>-. pApp : private handle. -. callback : redering callback. int32_t callback(void* pApp, int32_t type, void* data, int32_t dataSize) -. pApp : private handle. -. type : callback function type. (CB_TYPE_BUFFER, CB_TYPE_HIDE, CB_TYPE_SHOW) -. data : send data for callback. -. dataSize : size of data</pre>
Return Value	None

2.2.5 NXDA_StartBackGearDetectService()

<pre>int32_t NXDA_StartBackGearDetectService(int32_t nGpio, int32_t nChkDelay);</pre>	
Description	Start back gear detection service.
Parameter	

- . nGpio	: GPIO port number.
- . nChkDelay	: GPIO check delay (mSec)
Return Value	
Zero is returned.	

2.2.6 NXDA_StopBackGearDetectService()

<pre>void NXDA_StopBackGearDetectService(void);</pre>	
Description	
Start back gear detection service.	
Parameter	
None.	
Return Value	
None.	

2.2.7 NXDA_RegisterBackGearEventCallback()

<pre>void NXDA_RegisterBackGearEventCallback(void *pAppData, void (*callback)(void *pAppData, int32_t nOnOff));</pre>	
Description	
Please describe this function.	
Parameter	
- . pAppData	: private handle.
- . callback	: register back gear detection callback.
<pre>void (*callback)(void *pAppData, int32_t nOnOff)</pre>	
- . pAppData	: private handle.
- . nOnOff	: back gear status.
Return Value	
None.	

Chap 3. **History**

3.1 Known Issue

-. Not yet.

3.2 To do list

-. Apply to change audio focus scenario.