# Update Guide

Version 1.1.0

## Display Audio

Solution Team



#### Release information

The following changes have been make to this document.

#### **Change History**

Date	Change
07 Dec 2017	First release for v1.0.0
14 Nov 2018	Second release for v1.1.0

#### **Proprietary Notice**

Information in this document is provided solely to enable system and software implementers to use Nexell products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Nexell reserves the right to make changes without further notice to any products herein.

Nexell makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Nexell assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Nexell data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Nexell does not convey any license under its patent rights nor the rights of others. Nexell products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Nexell product could create a situation where personal injury or death may occur. Should Buyer purchase or use Nexell products for any such unintended or unauthorized application, Buyer shall indemnify and hold Nexell and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Nexell was negligent regarding the design or manufacture of the part.

Copyright© 2017 Nexell Co.,Ltd. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electric or mechanical, by photocopying, recording, or otherwise, without the prior written consent of Nexell.

#### Contact us

[11595] Bundang Yemiji Bldg. 12F, 31 Hwangsaeul-ro 258 beon gil, Bundang-gu, Sungnam-city, Gyeonggi-do, Korea.

TEL: 82-31-698-7400

FAX:82-31-698-7455

http://www.nexell.co.kr

# Table of contents

Chap 1.	Information	1
	1.1 Overview	1
Chan 2	NX update	2
Chap 2.	2.1 Make disk for updates	2
	2.2 How to update	
	2.3 Update disk priority	

# Chap 1. Information

#### 1.1 Overview

This document describes how to update firmware image.

• Tool's name : nx\_update

• Sub tools: nx\_reboot, psplash, psplash-write, blkid, sfdisk

• Operation script : update.sh, mount.sh

• Operational Prerequisites : systemd service (nxupdate.service)

• Supported devices : USB storage, SDcard



## Chap 2. NX update

### 2.1 Make disk for updates

Files needed for the update as below.

- partmap\_update.txt
- update\_cmd.txt
- Target images
- bootloader.img
- boot.img<del>(option)</del>
- rootfs.img-(option)

Description of the partmap\_update.txt (It is necessary to write)

flash=mmc,0:bootloader:boot:0x1E0200,0x100000:bootloader.img;

flash=mmc,0:env:env:0x2E0200,0x4000:;

 $flash=mmc, 0: boot: ext4: 0x400000, 0x20000000: \textcolor{red}{boot.img};$ 

flash=mmc, 0: modules: ext 4: 0x 2400000, 0x 20000000:;

flash=mmc,0:rootfs:ext4:0x46400000,0:rootfs.img;

If you do not want to update **bootloader.img**, boot.img or rootfs.img, leave the name field blank.

Description of the update\_cmd.txt (It is necessary to write)

fdisk

erase bootloader

flash bootloader

erase boot

flash boot

erase rootfs

flash rootfs

If you do not want to update  $\underline{bootloader.img}$ , boot.img or rootfs.img, remove erase  $(\underline{bootloader.img}$  or  $\underline{boot}$  boot or rootfs) and flash  $(\underline{bootloader.img}$  or  $\underline{boot}$  or rootfs) commands.



**서식 있음:** 글꼴 색: 빨강

## 2.2 How to update

#### 2.2.1 Step 1

Make disk\_ (USB storage or SDcard) for updates

#### 2.2.2 Step 2

Insert disk\_ (USB storage or SDcard)

## 2.2.3 Step 3

run nx\_reboot command.

#### 2.3 Update disk priority

First place is USB storage, second place is SDcard.

