

---

# PAC Learning with Bandit Feedback: Sharp Sample Complexity in the Realizable Setting

---

**Steve Hanneke**

Department of Computer Science  
Purdue University  
West Lafayette, IN, USA  
steve.hanneke@gmail.com

**Qinglin Meng**

Department of Computer Science  
Purdue University  
West Lafayette, IN, USA  
meng160@purdue.edu

**Shay Moran**

Faculties of Mathematics, Computer Science, and Data and Decision Sciences  
Technion – Israel Institute of Technology and Google Research  
Haifa, Israel  
smoran@technion.ac.il

**Amirreza Shaeiri**

Department of Computer Science  
Purdue University  
West Lafayette, IN, USA  
amirreza.shaeiri@gmail.com

## Abstract

We study the problem of multiclass PAC learning with bandit feedback in the realizable setting. In this framework, there is an unknown data distribution over an instance space  $\mathcal{X}$  and a label space  $\mathcal{Y}$ , as in classical multiclass PAC learning, but the learner does not observe the labels of the i.i.d. training examples. Instead, in each round, it receives an unlabeled instance, predicts its label, and receives bandit feedback indicating only whether the prediction is correct. Despite this restriction, the goal remains the same as in classical PAC learning.

We provide a general characterization of the optimal sample complexity of this problem, sharp for every concept class up to logarithmic factors. Our characterization is based on a new combinatorial dimension, termed the *bandit DS dimension*, defined via generalized combinatorial structures we call *pseudo-boxes*. These extend the pseudo-cubes underlying the DS dimension by allowing a different number of neighbors in each coordinate. In contrast to the DS dimension, which governs the full-information setting by counting the number of coordinates in the pseudo-cube, the bandit DS dimension aggregates the number of neighbors across coordinates, leading to a characterization in which the sample complexity scales with the total number of neighbors.

We also propose a general learning algorithm achieving the upper bound, based on an algorithmic principle called *ListCascade*, which connects bandit learning to list learning and may be of independent interest.

# 1 Introduction

A natural variant of multiclass PAC learning arises when the learner does not observe labels, but only receives binary feedback indicating whether its predictions are correct. This setting, known as multiclass PAC learning with bandit feedback, was introduced and studied in the PAC framework by [Daniely, Sabato, Ben-David, and Shalev-Shwartz \[2011, 2015\]](#). Formally, there is an unknown distribution  $\mathcal{D}$  over an instance space  $\mathcal{X}$  and a label space  $\mathcal{Y}$ . The training process proceeds over  $n$  rounds: in each round, a sample  $(x, y) \sim \mathcal{D}$  is drawn, the instance  $x$  is revealed, and the learner predicts a label  $\hat{y} \in \mathcal{Y}$ . Instead of observing the true label, the learner only receives bandit feedback indicating whether  $\hat{y} = y$ . The goal is to output a hypothesis  $\hat{h} : \mathcal{X} \rightarrow \mathcal{Y}$  that generalizes well to  $\mathcal{D}$ . We assume a hypothesis class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  and focus on the realizable setting, where  $\mathcal{D}$  is consistent with some  $h \in \mathcal{H}$ .

There are at least two primary motivations for studying multiclass learning under bandit feedback. First, bandit feedback is often substantially cheaper to obtain than full information. For instance, answering the question “Is this an image of a horse?” is significantly faster than selecting the correct label from a long list of possible categories. Moreover, in many real-world scenarios, this restricted form of feedback is not merely a cost-saving choice but an inherent limitation of the environment. As an illustration, imagine a pandemic caused by an unknown virus, where we aim to develop an AI model capable of accurately recommending the appropriate medication for patients drawn i.i.d. from the same underlying population. Suppose, for simplicity, that each patient responds positively to exactly one drug from a fixed set of available drugs. Due to various challenges associated with human clinical trials, including ethical and financial constraints, only a limited number of patients can be enrolled. Naturally, the only feedback we can obtain from each trial is binary—whether the drug tested was effective or not for that patient. We refer the reader to [Woodroffe \[1979\]](#), [Li et al. \[2010\]](#), [Agarwal et al. \[2016\]](#) for additional practical examples.

In this work, we study the following fundamental and naturally arising question:

*Given a concept class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$ , how many training samples are necessary and sufficient for PAC learning  $\mathcal{H}$  when the learner receives only bandit feedback?*

The work of [Daniely et al. \[2011, 2015\]](#) provided an initial result on the above question, among others. However, their upper and lower bounds have a multiplicative gap of  $K$  up to logarithmic factors, where  $K$  is the size of the effective label space. In particular, given a concept class  $\mathcal{H}$ , they showed a lower bound of  $\tilde{\Omega}(\text{ND}(\mathcal{H})/\epsilon)$  and an upper bound of  $\tilde{O}(K \text{ND}(\mathcal{H})/\epsilon)$  on the optimal sample complexity of multiclass PAC learning with bandit feedback, where  $\text{ND}(\mathcal{H})$  denotes the Natarajan dimension of  $\mathcal{H}$ , the standard multiclass analogue of the VC dimension, defined by the largest set of points that can be shattered using two candidate labels per point.

## 1.1 Overview of the Main Results

Our main contribution is a new combinatorial complexity parameter that sharply characterizes the sample complexity of PAC learning with bandit feedback. The definition is based on a natural generalization of classical combinatorial structures that underlie PAC learning theory.

We begin with a simple object. An  $N_1 \times N_2 \times \cdots \times N_d$  box is a cartesian product  $A_1 \times A_2 \times \cdots \times A_m$ , where each  $A_i \subseteq \mathcal{Y}$  has size  $N_i$ . Boxes capture independent variation across coordinates and play a central role in classical dimensions. For example, a Natarajan cube corresponds to a  $2 \times 2 \times \cdots \times 2$  box, while its natural generalization to list learning corresponds to  $(\ell + 1) \times \cdots \times (\ell + 1)$  boxes.

In our setting, however, we require a more flexible notion. We say that a finite set  $T \subseteq \mathcal{Y}^m$  is an  $N_1 \times \cdots \times N_d$  pseudo-box if every vector  $f \in T$  has at least  $N_i - 1$  “neighbors” in direction  $i$ , namely, functions in  $T$  that agree with  $f$  on all coordinates except possibly  $i$ , and collectively realize  $N_i$  distinct labels at coordinate  $i$ . Pseudo-boxes relax the rigid cartesian product structure while preserving its local combinatorial richness. In particular, pseudo-cubes (the case  $N_i = 2$ ) recover the classical structure underlying the DS dimension, while larger values of  $N_i$  correspond to its extensions used in list learning [Daniely and Shalev-Shwartz \[2014\]](#), [Brukhim et al. \[2022\]](#), [Charikar and Pabbaraju \[2023\]](#).

The key point is that such structures precisely capture the difficulty of learning. In the full-information setting, complexity is governed by the number of coordinates in a pseudo-box, leading to dimensions

such as the DS dimension. In contrast, under bandit feedback, the difficulty accumulates across coordinates: each direction contributes separately to the complexity.

Motivated by this perspective, we define the *bandit DS dimension* of a concept class  $\mathcal{H}$ , denoted  $\text{BDS}(\mathcal{H})$ , as the maximum total size  $\sum_{i=1}^m N_i$  of a pseudo-box realizable by  $\mathcal{H}$ . We refer the reader to [subsection A.2](#) for the formal definition and further discussion.

Equipped with this dimension, we establish matching upper and lower bounds on the optimal sample complexity of multiclass PAC learning with bandit feedback, resolving an open problem posed by [Daniely et al. \[2011, 2015\]](#) up to logarithmic factors.

**Theorem 1.1.** *Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class with  $\text{BDS}(\mathcal{H}) < \infty$ , and denote by  $\mathbf{m}_{\mathcal{H}}^B$  the optimal sample complexity of multiclass PAC learning with bandit feedback (see [Definition 3.3](#)). Then,*

$$\mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) \in \tilde{\Theta} \left( \frac{\text{BDS}(\mathcal{H})}{\epsilon} \right),$$

where  $\tilde{\Theta}$  hides polylogarithmic factors in  $K$ ,  $1/\epsilon$ , and  $1/\delta$ .

The upper bound in [Theorem 1.1](#) is based on a new algorithmic framework, which we call *ListCascade*. At a high level, ListCascade uses a sequence of list learners with progressively shrinking list sizes, thereby converting list learning guarantees into a bandit-feedback learner whose complexity is governed by the bandit DS dimension. A key ingredient in the analysis is a refined sample complexity bound for list PAC learning, which may also be of independent interest; see [Section 1.2](#) for more details. This leaves open whether the upper bound can be achieved with no polylogarithmic overhead beyond the bandit DS dimension.

We also place our result in the broader landscape of bandit learning. Although multiclass learning with bandit feedback can be viewed as a special case of contextual bandits, a direct reduction to this general setting misses a key structural feature of classification: the induced reward function is sparse. Recent works have exploited this sparsity to obtain sharper sample-complexity guarantees [Erez et al. \[2024b,a\]](#), [Erez and Koren \[2025\]](#), primarily for finite concept classes and in the agnostic regime. Our results show that, in the realizable PAC setting, this additional structure enables a combinatorial characterization of the near-optimal sample complexity, in contrast to general bandit learning problems where such characterizations are provably impossible [Hanneke and Yang \[2023\]](#), [Brukhim et al. \[2025\]](#).

## 1.2 Overview of the Techniques

**List learning.** Our first ingredient is list learning, which serves as the intermediate object connecting bandit feedback and multiclass prediction. In standard multiclass learning, the learner predicts a single label for each instance. In list learning, the learner is allowed to output a short list of candidate labels, and the prediction is considered correct as long as the true label is contained in the list. This relaxation is particularly useful under bandit feedback: even if the learner cannot immediately identify the correct label, it can progressively shrink the set of plausible labels while preserving the true one with high probability.

**ListCascade.** Our main algorithmic idea is a cascading procedure that repeatedly learns smaller lists from bandit feedback. This should be contrasted with the classical reduction of [Daniely et al. \[2011\]](#), which explores by predicting a uniformly random label from  $\mathcal{Y}$ . Since the correct label is revealed only with probability  $1/K$ , one needs about  $K$  bandit examples to obtain one full-information example, leading to the  $\tilde{O}(K \text{ND}(\mathcal{H})/\epsilon)$  upper bound.

ListCascade replaces this one-shot exploration by a sequence of list-learning stages. Initially, the learner considers all  $K$  labels as possible. In the first epoch, it predicts uniformly from this full list and uses the revealed examples to learn a list predictor of size roughly  $K/2$ . In the next epoch, the learner only explores within this shorter list, and then learns an even shorter list. Repeating this process, the list size is halved from  $K$  to  $K/2$ , then to  $K/4$ , and so on, until the final list has size one; this final list predictor is the returned multiclass hypothesis.

The key point is that the cost of each epoch scales with the current list size, rather than with the original number of labels  $K$ . Suppose an epoch reduces the list size from about  $2L$  to  $L$ . Uniform exploration within the current list reveals the true label with probability about  $1/(2L)$ , giving the exploration

factor  $L$ . The remaining cost is the sample complexity of learning an  $L$ -list predictor, which is governed by the  $L$ -DS dimension of  $\mathcal{H}$ , denoted by  $L\text{-DS}(\mathcal{H})$ . This is the list learning analogue of the DS dimension defined through larger pseudo-boxes. Thus each epoch costs, up to logarithmic factors,  $(L \cdot L\text{-DS}(\mathcal{H}))/\epsilon$ . Since the complexity measure  $\text{BDS}(\mathcal{H})$  dominates  $\max_L(L \cdot L\text{-DS}(\mathcal{H}))$ , summing over the logarithmically many epochs gives the desired near optimal sample complexity upper bound, up to logarithmic factors.

**Sample complexity of list learning.** It remains to establish the list-learning guarantee required in each epoch of LISTCASCADE. We use the one-inclusion list algorithm studied by Charikar and Pabbaraju [2023]. By the analysis of Hanneke et al. [2026], its sample complexity is controlled by the corresponding list exponential dimension: learning an  $L$ -list predictor requires  $\tilde{O}(L\text{-E}(\mathcal{H})/\epsilon)$  samples, where  $L\text{-E}(\mathcal{H})$  denotes the  $L$ -exponential dimension. Informally, this dimension is the list-learning analogue of the exponential dimension: it captures the largest set of points on which the class realizes exponentially many label patterns at scale  $L$ . Prior comparisons between list exponential dimension and list DS dimension yield a bound of order  $\tilde{O}(L \cdot L\text{-DS}(\mathcal{H})/\epsilon)$ . While sufficient for characterizing list learning, this extra factor  $L$  is too costly for our bandit application, since it would multiply the exploration cost in LISTCASCADE and lead to a suboptimal bound.

Our contribution is to sharpen this dimension comparison in the regime needed by the cascade. Using the optimal Sauer lemma of Hanneke et al. [2026], we show that the  $L$ -exponential dimension is controlled, up to logarithmic factors in  $K$ , by the  $\lceil L/2 \rceil$ -DS dimension. Hence the one-inclusion list algorithm learns an  $L$ -list predictor with sample complexity  $\tilde{O}(\lceil L/2 \rceil\text{-DS}(\mathcal{H})/\epsilon)$ . This removes the extraneous list-size factor and is the key ingredient that allows LISTCASCADE to achieve the near-optimal bandit sample complexity.

**Lower Bound.** The lower bound is obtained by turning the pseudo-box witnessing  $\text{BDS}(\mathcal{H})$  into a hard bandit instance. Suppose  $x_1, \dots, x_d$  are BDS-shattered with multiplicities  $N_1, \dots, N_d$ , where  $\sum_i N_i = \text{BDS}(\mathcal{H})$ . We place most of the distributional mass on one anchor point and distribute the remaining  $\Theta(\epsilon)$  mass over the other points in proportion to  $N_i$ . The target concept is then chosen uniformly from a finite subfamily witnessing the pseudo-box structure. For each point  $x_i$ , the multiplicity  $N_i$  represents the number of locally indistinguishable alternatives that differ only at  $x_i$ . Thus, unless the learner samples  $x_i$  on the order of  $N_i$  times, a constant fraction of these alternatives remain unexplored, and bandit feedback does not reveal which label is correct. With fewer than  $\Theta(\sum_i N_i/\epsilon)$  samples, this happens on enough probability mass to force error at least  $\epsilon$  with constant probability for some target concept. Therefore any bandit PAC learner requires  $\Omega(\text{BDS}(\mathcal{H})/\epsilon)$  samples, matching our upper bound up to logarithmic factors.

## 2 Related Work

**Contextual Bandit.** The bandit model occupies a central place in decision theory. Its origins trace back to the pioneering work of Thompson [1933], and the field gained prominence following Herbert Robbins' short but influential contribution Robbins [1952], which introduced the classical multi-armed bandit problem. Subsequently, Michael Woodroffe wrote the first paper on the fundamental problem of contextual bandits Woodroffe [1979]. Moreover, the literature on this topic has expanded dramatically since the landmark contributions of Auer et al. [2002a,b]. Beginning with works such as Dudik et al. [2011], Agarwal et al. [2014], a particularly influential technical idea has been the use of reduction-based approaches, which relate contextual bandits to supervised learning primitives, through importance weighting. For a comprehensive treatment of this subject, we refer the reader to Bubeck et al. [2012], Slivkins [2019], Lattimore and Szepesvári [2020], Foster et al. [2023].

Additionally, there is a recent paper on the problem studied in the current work within the framework of universal learning Hanneke et al. [2025d]. Nevertheless, in this framework, the dependence on the number of labels appears to be fundamentally different from that in the PAC learning framework. We refer the reader to Hanneke et al. [2024c, 2025d,c] for more discussion of this phenomenon.

**List Learning.** In recent years, there has been a growing body of work on list learning across both the theoretical and empirical branches of machine learning. On the theoretical side, list learners play a key role in the breakthrough result of Brukhim et al. [2022], which provides a combinatorial characterization of multiclass PAC learnability. This topic has since developed in several directions, including PAC learning Charikar and Pabbaraju [2023], Hanneke et al. [2024b, 2025a], Cohen et al.

[2026], online learning [Moran et al. \[2023\]](#), boosting [Brukhim et al. \[2023, 2024\]](#), sample compression schemes and uniform convergence [Hanneke et al. \[2024a\]](#), real-valued regression [Pabbaraju and Sarmasarkar \[2024\]](#), transductive online learning [Hanneke and Shaeiri \[2025\]](#), differentially private PAC learning [Hanneke et al. \[2025b\]](#), combinatorial semi-bandits [Erez and Koren \[2025\]](#), language generation [Charikar et al. \[2025\]](#), and SSP lemmas [Hanneke et al. \[2026\]](#). Moreover, list learning also naturally connects to the fundamental setting of list-decodable learning in statistics. For a detailed exposition on list-decodable learning, for example, refer to Chapter 5 of the recent textbook by [Diakonikolas and Kane \[2023\]](#).

### 3 Preliminaries

We consider a learning setting in which a learner is tasked with classifying objectives from a set of examples  $\mathcal{X}$  with a single label from a set of  $K$  possible labels  $\mathcal{Y} = \{1, \dots, K\}$ . A stochastic multiclass classification instance is specified by a hypothesis class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  and a joint distribution over example-label pairs over  $\mathcal{X} \times \mathcal{Y}$ .

Before describing the bandit feedback model, we introduce the necessary notions used to state the PAC guarantee. The performance of a hypothesis is measured by its expected classification error.

**Definition 3.1** (Error rate). Let  $\mathcal{D}$  be a distribution over  $\mathcal{X} \times \mathcal{Y}$  and let  $h \in \mathcal{Y}^{\mathcal{X}}$ . We define the error rate of  $h$  with respect to  $\mathcal{D}$  as follows:

$$\mathcal{L}_{\mathcal{D}}(h) = \Pr_{(x,y) \sim \mathcal{D}} [h(x) \neq y].$$

We focus on the realizable setting, where the hypothesis class contains a perfect classifier for the data distribution. Formally, we have the following definition.

**Definition 3.2** (Realizable Distribution). We say that a data distribution  $\mathcal{D}$  is realizable by a concept class  $\mathcal{H}$  if  $\inf_{h \in \mathcal{H}} \mathcal{L}_{\mathcal{D}}(h) = 0$ .

We now specify the bandit feedback learning protocol. In the bandit feedback setup, the learner does not observe the true label  $y_i$  directly; instead, it only observes whether its prediction is correct. Learning proceeds through the following protocol, over  $i = 1, 2, \dots, m$ :

1. The environment samples an instance  $(x_i, y_i)$  from  $\mathcal{D}$  and reveals  $x_i$  to the learner.
2. The learner predicts a label  $\hat{y}_i$  from  $\mathcal{Y}$ .
3. Nature reveals the feedback  $f_i = \mathbb{1}\{y_i = \hat{y}_i\}$  to the learner.

Finally, based on  $\{(x_1, \hat{y}_1, f_1), \dots, (x_m, \hat{y}_m, f_m)\}$ , the learner returns a hypothesis  $\hat{h} : \mathcal{X} \rightarrow \mathcal{Y}$ .

The goal of PAC learning is to output, with high probability, a hypothesis whose expected error is small and this requirement is formalized by the following sample complexity notion.

**Definition 3.3** (Sample complexity for realizable multiclass PAC learning with bandit feedback). For  $\epsilon, \delta \in (0, 1)$ , the realizable PAC sample complexity of  $\mathcal{H}$  with bandit feedback, denoted by  $\mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta)$ , is the smallest integer  $m$  such that there exists a learning algorithm satisfying the following: for every distribution  $\mathcal{D}$  realizable by  $\mathcal{H}$ , after  $m$  rounds of interaction with bandit feedback, the returned hypothesis  $\hat{h}$  satisfies

$$\Pr \left[ \mathcal{L}_{\mathcal{D}}(\hat{h}) > \epsilon \right] \leq \delta,$$

where the probability is over the sample  $S \sim \mathcal{D}^m$  and any internal randomness of the algorithm.

Next, we introduce list learning [\[Charikar and Pabbaraju, 2023\]](#), which will be used as an intermediate object in our analysis. In list learning, instead of predicting a single label, the learner outputs a list of candidate labels for each instance. A list predictor of size  $L$  is a mapping  $\mu : \mathcal{X} \rightarrow \{Y \subseteq \mathcal{Y} : |Y| \leq L\}$ . Its error rate is defined as  $\mathcal{L}_{\mathcal{D}}(\mu) = \Pr_{(x,y) \sim \mathcal{D}} [y \notin \mu(x)]$ .

Next, we define the majority vote over lists, which we will use later to convert hypotheses with expected-error guarantees into a single hypothesis satisfying a PAC guarantee.

**Definition 3.4** (Majority vote for lists [\[Hanneke et al., 2024b\]](#)). For  $n$  lists  $\mu_1, \dots, \mu_n$  each of size  $L$ , we define their majority vote to be  $\mu = \text{Maj}(\mu_1, \dots, \mu_n)$  with

$$\mu(x) = \text{Maj}(\mu_1, \dots, \mu_n)(x) := \{y \in \mathcal{Y} : |i \in [n] : y \in \mu_i(x)| \geq n/2\}, \forall x \in \mathcal{X}.$$

---

**Algorithm 1** LISTCASCADE: Bandit PAC Multiclass Classification via List Learners

---

**Input:** An unlabeled sample  $S = \{x_1, x_2, \dots, x_m\}$

**Output:** A multiclass classification hypothesis  $h_S$ .

- 1: Set  $\mu_0(x) = \mathcal{Y}$  for any  $x \in \mathcal{X}$ .
  - 2: **for** epoch  $t = 1, 2, \dots, \lfloor \log K \rfloor$  **do**
  - 3:   Initialize  $S_t = \emptyset$ .
  - 4:   **for**  $i = m_{t-1} + 1, m_{t-1} + 2, \dots, m_t$  **do**
  - 5:     Observe  $x_i$ , predict  $\hat{y}_i \sim \text{Unif}(\mu_{t-1}(x_i))$  and receive feedback  $\mathbb{1}\{y_i = \hat{y}_i\}$ .
  - 6:     Update  $S_t \leftarrow S_t \cup \{(x_i, y_i)\}$  if  $y_i = \hat{y}_i$ , otherwise  $S_t$  is unchanged.
  - 7:   **end for**
  - 8:   Let  $L_t = \lceil K/2^{t+1} \rceil$  and construct  $\mu_t$  from  $S_t$  according to Equation (1).
  - 9: **end for**
  - 10: Set  $h_S(x)$  to be the unique element of  $\mu_{\lfloor \log K \rfloor}(x)$  for all  $x \in \mathcal{X}$ .
- 

Note that the majority-vote list  $\mu$  has size at most  $2L - 1$ , rather than  $L$ . For notational convenience, we may pad  $\mu(x)$  with arbitrary labels from  $\mathcal{Y} \setminus \mu(x)$  so that all output lists have size exactly  $\min\{2L - 1, K\}$ . When  $L = 1$ , this definition reduces to the usual majority vote for classifiers.

## 4 Algorithm and Analysis

In this section, we present and analyze one of our main contributions: a near optimal bandit multiclass classification algorithm, detailed in Algorithm 1, which will be shown to satisfy the following realizable PAC guarantee.

**Theorem 4.1** (PAC Sample Complexity Upper Bound for Multiclass Classification with Bandit-feedback). *Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a class with bandit DS dimension  $\text{BDS}(\mathcal{H}) = d_{DS}^B < \infty$ , we have*

$$\mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) = O\left(\frac{d_{DS}^B(\log K)^3 + K \log K \log(\frac{1}{\delta})}{\epsilon}\right).$$

For comparison, we also prove the following matching lower bound up to logarithmic factors.

**Theorem 4.2** (PAC Sample Complexity Lower Bound for Multiclass Classification with Bandit-feedback). *Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a non trivial class with bandit DS dimension  $\text{BDS}(\mathcal{H}) = d_{DS}^B < \infty$ . Let  $K = |\mathcal{Y}| \geq 2$ . Then, we have*

$$\mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) = \Omega\left(\frac{d_{DS}^B + \log(\frac{1}{\delta})}{\epsilon}\right).$$

Algorithm 1 proceeds by gradually shrinking the list of candidate labels. In epoch  $t$ , the learner explores using the previous list predictor  $\mu_{t-1}$  by predicting uniformly from  $\mu_{t-1}(x)$ , and keeps an example only when the bandit feedback is positive. The retained examples form the labeled sample  $S_t$ . The list predictor used in next epoch is then defined by

$$\mu_t = \text{Maj}\left(\mu_{S_t, \leq \lceil n_t/4 \rceil}^{L_t}, \dots, \mu_{S_t, \leq n_t}^{L_t}\right), \quad (1)$$

where  $n_t = |S_t|$ , and  $\mu_{S_t, \leq n}^{L_t}$  is the output of the one-inclusion list learner of Charikar and Pabbaraju [2023], Hanneke et al. [2026] trained on the first  $n$  examples of  $S_t$  with list size  $L_t$ . The majority vote increases the list size to  $2L_t - 1$ , so with  $L_t = \lceil K/2^{t+1} \rceil$ , the effective list size remains on the order of  $K/2^t$ . Thus the algorithm reduces the candidate label set by a constant factor in each epoch. For completeness, we include the one-inclusion list learner in Algorithm 2 in the appendix. Finally, we choose  $m_t - m_{t-1} = O((L_{t-1}(d_{DS}^B)^{\lceil L_{t-1}/2 \rceil}(\log K)^2 + \log(1/\delta)) \log K / \epsilon)$ , with  $m_0 = 0$ .

### 4.1 Proof of Theorem 4.1

In this section, we will provide the analysis of Algorithm 1 and the proof of Theorem 4.1. We start with a technique lemma that upper bounds the  $L$ -exponential dimension by  $(L/2)$ -DS dimension.



**Lemma 4.3** (Controlling the  $L$ -exponential dimension by  $(L/2)$ -DS dimension). *For every  $K \geq 2$  and  $L \geq 1$ . For every concept class  $\mathcal{H} \subseteq [K]^n$  with  $\lceil L/2 \rceil$ -DS( $\mathcal{H}$ ) =  $d_{\text{DS}}^{\lceil L/2 \rceil}$  and  $L$ -E( $\mathcal{H}$ ) =  $d_E^L < \infty$ , we have  $d_E^L \leq 6d_{\text{DS}}^{\lceil L/2 \rceil} \log K$ .*

*Proof of Lemma 4.3.* Consider the set  $S$  which realizes  $d_E^L$ , so that  $|S| = d_E^L$ . By the definition of  $d_E^L$ , we have

$$|\mathcal{H}|_S \geq (L+1)^{d_E^L}.$$

On the other hand, by Theorem 1 of Hanneke et al. [2026],

$$|\mathcal{H}|_S \leq \left\lceil \frac{L}{2} \right\rceil^{d_E^L - d_{\text{DS}}^{\lceil L/2 \rceil}} \left( \frac{eK d_E^L}{d_{\text{DS}}^{\lceil L/2 \rceil}} \right)^{d_{\text{DS}}^{\lceil L/2 \rceil}}.$$

Combining the preceding two inequalities and applying Lemma A.2 of Shalev-Shwartz and Ben-David [2014] gives

$$d_E^L \leq d_{\text{DS}}^{\lceil L/2 \rceil} \left( \frac{1 + \log K + 2 \log(1/\log 2)}{\log 2} \right) \leq 6d_{\text{DS}}^{\lceil L/2 \rceil} \log K.$$

The full calculation is deferred to Section B.1.  $\square$

Based on Lemma 4.3 as well as Lemma 3.20 and Lemma 3.22 of Hanneke et al. [2026], we can upper bound the leave-one-out error of Algorithm 2 as follow.

**Lemma 4.4** (Leave-one-out error bound for list learning). *For every concept class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  with  $\lceil L/2 \rceil$ -DS( $\mathcal{H}$ ) =  $d_{\text{DS}}^{\lceil L/2 \rceil}$ , let  $\mathcal{D}$  be an  $\mathcal{H}$ -realizable distribution and let  $n > 0$  be an integer. The prediction error can be bounded as*

$$\Pr_{(S, (x, y)) \sim \mathcal{D}^{n+1}} [y \neq \mu_S^L(x)] \leq \frac{6d_{\text{DS}}^{\lceil L/2 \rceil} \log K}{n+1},$$

where  $\mu_S^L = \mathcal{A}_{\mathcal{H}}^L(S)$  is the output of Algorithm 2.

We now state and prove our list learning PAC bound, building on Lemma 4.4 and Theorem 2.1 in Aden-Ali et al. [2023].

**Lemma 4.5.** *Fix a concept class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  with  $\lceil L/2 \rceil$ -DS( $\mathcal{H}$ ) =  $d_{\text{DS}}^{\lceil L/2 \rceil}$ . Let  $\mathcal{D}$  be a  $\mathcal{H}$ -realizable distribution over  $\mathcal{X} \times \mathcal{Y}$ . There is a list hypothesis  $\mu : \mathcal{X} \rightarrow \binom{\mathcal{Y}}{2L-1}$  with list size  $2L-1$  which, for any  $\delta \in (0, 1)$ , and  $S \sim \mathcal{D}^n$ , satisfies*

$$\mathcal{L}_{\mathcal{D}}(\mu) \leq 9.64 \left( \frac{6d_{\text{DS}}^{\lceil L/2 \rceil} \log K}{n} + \frac{1}{n} \log \left( \frac{2}{\delta} \right) \right),$$

with probability at least  $1 - \delta$  over the randomness of  $S$ .

*Proof of Lemma 4.5.* Given the full training sample  $S$ , let  $(\mu_{S_{\leq t}}^L)_{t=\lceil n/4 \rceil}^{n-1}$  be the one-inclusion hypergraph predictors trained on the sequence of growing training samples  $(S_{\leq t})_{t=\lceil n/4 \rceil}^{n-1}$  output by Algorithm 2. Because these predictors are symmetric in their training sample and they have a leave-one-out error guarantee (Lemma 4.4), we can apply Theorem 2.1 in Aden-Ali et al. [2023] to the suffix of the sequence to get that

$$\frac{4}{3n} \sum_{t=\lceil n/4 \rceil}^{n-1} \mathcal{L}_{\mathcal{D}}(\mu_{S_{\leq t}}^L) \leq 4.82 \left( \frac{6d_{\text{DS}}^{\lceil L/2 \rceil} \log K}{n} + \frac{1}{n} \log \left( \frac{2}{\delta} \right) \right),$$

with probability at least  $1 - \delta$  over the randomness of  $S$ . Whenever this bound holds, the majority vote of the one-inclusion hypergraph predictors in the suffix,  $\mu = \text{Maj}(\mu_{S_{\leq \lceil n/4 \rceil}}^L, \dots, \mu_{S_{\leq n-1}}^L)$

satisfies

$$\begin{aligned}
\mathcal{L}_{\mathcal{D}}(\mu) &= \mathbb{E}_{(x,y) \sim D} [\mathbb{1}[y \notin \mu(x)]] \\
&\leq \mathbb{E}_{(x,y) \sim D} \left[ 2 \left( \frac{4}{3n} \sum_{t=\lceil n/4 \rceil}^{n-1} \mathbb{1}[y \notin \mu_{S_{\leq t}}^L(x)] \right) \right] \\
&= 2 \cdot \frac{4}{3n} \sum_{t=\lceil n/4 \rceil}^{n-1} \mathcal{L}_{\mathcal{D}}(\mu_{S_{\leq t}}^L) \\
&\leq 9.64 \left( \frac{6d_{DS}^{\lceil L/2 \rceil} \log K}{n} + \frac{1}{n} \log \left( \frac{2}{\delta} \right) \right).
\end{aligned}$$

In the first inequality above, we used the fact that no more than half the predictors can be correct when the majority vote is wrong. This completes the proof.  $\square$

The proof is given by inductively proving the following lemma.

**Lemma 4.6.** *With probability at least  $1 - (t\delta)/\log K$ , the list predictor  $\mu_t$  in Equation (1) has error rate at most  $(t\epsilon)/\log K$  for  $t \in \{0, 1, \dots, \lfloor \log K \rfloor\}$ .*

*Proof of Lemma 4.6.* For the base case, when  $t = 0$ , by definition we know that  $\mu_0(x) = \mathcal{Y}$  for any  $x \in \mathcal{X}$ , which satisfies our inductive assumption.

For the inductive step, we assume that  $\mathcal{L}_{\mathcal{D}}(\mu_{t-1}) \leq ((t-1)\epsilon)/\log K$  holds with probability at least  $1 - ((t-1)\delta)/\log K$ . According to Algorithm 1, we predict the label  $\hat{y}_i$  uniformly randomly from the list  $\mu_{t-1}(x_i)$  for each instance  $x_i$  we encountered in epoch  $t$ , we know that

$$\Pr[\hat{y}_i = y_i] \geq \frac{1}{2L_{t-1}} \left( 1 - \frac{(t-1)\epsilon}{\log K} \right).$$

Also, notice that, the number of samples we encountered in epoch  $t$  is

$$m_t - m_{t-1} = \frac{4L_{t-1}}{1 - \frac{(t-1)\epsilon}{\log(K)}} \cdot \left( 10 \frac{\left( 6d_{DS}^{\lceil L_{t-1}/2 \rceil} \log K + \log \left( \frac{2 \log K}{\delta} \right) \right) \log K}{\epsilon} + \log \left( \frac{2 \log K}{\delta} \right) \right).$$

Conditioned on the history before epoch  $t$ , the indicators  $\mathbb{1}[\hat{y}_i = y_i]$  are independent Bernoulli random variables, a multiplicative lower-tail Chernoff bound yields that, with probability at least  $1 - \delta/(2 \log K)$  we can collect a labeled sample  $S_t$  with size at least

$$n_t = 10 \frac{\left( 6d_{DS}^{\lceil L_{t-1}/2 \rceil} \log K + \log \left( \frac{2 \log K}{\delta} \right) \right) \log K}{\epsilon}.$$

Note that the samples in  $S_t$  are conditionally independent given the list  $\mu_{t-1}$ . For each epoch  $t$ , we divide the sample space  $(\mathcal{X} \times \mathcal{Y})$  into two parts according to whether  $y \in \mu_{t-1}(x)$  and denote  $(\mathcal{X} \times \mathcal{Y})_t = \{(x, y) | y \in \mu_{t-1}(x)\}$ . Let  $\mathcal{D}_t$  denote the distribution of sample  $S_t$ , its the restriction of  $\mathcal{D}$  on  $(\mathcal{X} \times \mathcal{Y})_t$ . Now we start to bound the error rate of  $\mu_t$  and, with probability at least  $1 - \delta/(2 \log K)$ , we have

$$\begin{aligned}
\mathcal{L}_{\mathcal{D}}(\mu_t) &= \mathbb{E}_{(x,y) \sim \mathcal{D}} [\mathbb{1}[y \notin \mu_t(x), y \in \mu_{t-1}(x)]] + \mathbb{E}_{(x,y) \sim \mathcal{D}} [\mathbb{1}[y \notin \mu_t(x), y \notin \mu_{t-1}(x)]] \\
&\leq \mathbb{E}_{(x,y) \sim \mathcal{D}_t} [\mathbb{1}[y \notin \mu_{t-1}(x)]] + \mathbb{E}_{(x,y) \sim \mathcal{D}} [\mathbb{1}[y \notin \mu_t(x)]] \\
&\leq 10 \left( \frac{6d_{DS}^{\lceil L_{t-1}/2 \rceil} \log K}{n_t} + \frac{1}{n_t} \log \left( \frac{2 \log K}{\delta} \right) \right) + \frac{(t-1)\epsilon}{\log K} = \frac{t\epsilon}{\log K},
\end{aligned}$$

where the second inequality follows from Lemma 4.5 and the induction hypothesis. Condition on the event from the induction hypothesis, which holds with probability at least  $1 - (t-1)\delta/\log K$ . The Chernoff step and the list-learning PAC step each fail with probability at most  $\delta/(2 \log K)$ . A union bound therefore gives the desired probability  $1 - t\delta/\log K$ .  $\square$



Now, based on Lemma 4.6, we start to prove Theorem 4.1.

*Proof of Theorem 4.1.* By Lemma 4.6, we know that with probability at least  $1 - \delta$ , the hypothesis  $h_S$  returned by Algorithm 1 has error at most  $\epsilon$ . Thus the sample complexity  $\mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta)$  can be upper bounded by the total number of samples used by Algorithm 1. Formally, we have

$$\begin{aligned} \mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) &\leq \sum_{t=1}^{\lceil \log(K) \rceil} (m_t - m_{t-1}) \\ &\leq O\left(\frac{\max_{1 \leq L \leq K-1} (L d_{DS}^L) (\log K)^3}{\epsilon} + \frac{K \log K \log\left(\frac{2 \log K}{\delta}\right)}{\epsilon}\right). \end{aligned}$$

By the definition of the Bandit-DS dimension, for any concept class  $\mathcal{H}$ ,

$$\text{BDS}(\mathcal{H}) \geq \max_{1 \leq L \leq K-1} (L \cdot \text{L-DS}(\mathcal{H})).$$

Combining the preceding inequalities proves the desired upper bound. The full calculation is deferred to Section B.2.  $\square$

## 4.2 Proof of Theorem 4.2

In this section, we prove Theorem 4.2 by constructing two hard cases.

*proof of Theorem 4.2.* We first show that we at least need  $\Omega(\text{BDS}(\mathcal{H})/\epsilon)$  samples. For a concept class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$ , let  $\text{BDS}(\mathcal{H}) = d_{DS}^B < \infty$ . Let  $\mathcal{Z} = \{x_1, x_2, \dots, x_d\} \in \mathcal{X}^d$  and  $N \in \mathbb{N}^d$  is BDS-shattered by  $\mathcal{H}$  and  $\sum_{i=1}^d N_i = d_{DS}^B$ . Without loss of generality, we assume  $N_i$ 's are in ascending order. We consider the distribution  $\mathcal{D}$  over  $\mathcal{X}$  as follows

$$p(x) = \begin{cases} 1 - 16\epsilon, & \text{if } x = x_1 \\ \frac{16N_i\epsilon}{\sum_{i=2}^d N_i}, & \text{if } x \in \{x_2, \dots, x_d\} \end{cases}$$

We choose  $c^*$  uniform randomly from  $\mathcal{F} \subseteq \mathcal{H}, |\mathcal{F}| < \infty$  such that for all  $f \in \mathcal{F}|_{\mathcal{Z}}$  and for all  $i \in [d]$ ,  $f$  has at least  $N_i$   $i$ -neighbor in  $\mathcal{F}|_{\mathcal{Z}}$ . For simplicity, let  $\mathcal{Z}' = \{x_2, \dots, x_d\}$ . Let  $m = (\sum_{i=2}^d N_i)/(64\epsilon)$  and  $\mathcal{A}$  be any algorithm that uses an i.i.d. sample  $S$  with size at most  $m$  before picking a hypothesis. For ease of presentation, we define  $\mathcal{L}'_{\mathcal{D}}(h) = \Pr[c^*(x) \neq h(x) \mid x \in \mathcal{Z}']$ . In expectation, for each point  $x_i \in \mathcal{Z}'$ , there will be  $N_i/4$  samples sampled from  $x_i$ . By Markov inequality, with probability at most  $1/2$ , there will be more than  $N_i/2$  sample sampled from  $x_i$ . Let  $A_i$  be the event that no more than  $N_i/2$  samples sampled from  $x_i$ . In other words, we have  $\Pr_S[A_i] \geq 1/2$ . For a uniformly chosen  $c^* \in \mathcal{F}$ ,

$$\begin{aligned} \mathbb{E}_{c^*, S} [\mathcal{L}'_{\mathcal{D}}(h)] &= \sum_{i=2}^d \Pr[x = x_i] \Pr_{c^*, S}[h(x_i) \neq y_i] \\ &\geq \sum_{i=2}^d \Pr[x = x_i] \Pr_{c^*, S}[h(x_i) \neq y_i | A_i] \Pr_S[A_i] \\ &\geq \frac{1}{4} \sum_{i=2}^d \frac{16N_i\epsilon}{\sum_{i=2}^d N_i} = 4\epsilon. \end{aligned}$$

The first inequality is based on law of total probability. The second inequality follows because, assuming  $c^* \in \mathcal{F}$  is selected uniformly at random,  $h$  predicts the label uniform randomly from the  $N_i$   $i$ -neighbors, and the event  $A_i$  implies that at least  $N_i/2$   $i$ -neighbor has not been explored. Consequently, the probability of an incorrect prediction is at least  $1/2$ . This implies that there is some  $c^* \in \mathcal{H}$  such that  $\mathbb{E}_S [\mathcal{L}'_{\mathcal{D}}(h)] \geq 4\epsilon$ . For the reminder of the proof, consider this  $c^*$ . Note that, by definition, we have  $\mathcal{L}'_{\mathcal{D}}(h) \leq \Pr[x \in \mathcal{Z}'] = 16\epsilon$ . Let  $q = \Pr[\mathcal{L}'_{\mathcal{D}}(h) \geq \epsilon]$ . We have

$$4\epsilon \leq \mathbb{E}_S [\mathcal{L}'_{\mathcal{D}}(h)] \leq 16\epsilon q + \epsilon(1 - q) = \epsilon + 15\epsilon q,$$

which implies  $q \geq 3/15$  and further implies  $\Pr[\mathcal{L}_{\mathcal{D}}(h) \geq \epsilon] \geq 3/15$ . This construction shows that there exist a distribution  $\mathcal{D}$  over  $\mathcal{X}$  and a concept  $c^* \in \mathcal{H}$  such that for any algorithm that uses an i.i.d. sample with size at most  $m = (\sum_{i=2}^d N_i)/(64\epsilon)$ , the hypothesis output by this algorithm has error rate at least  $3/15$ .

Then, we show that at least  $\Omega(\log(1/\delta)/\epsilon)$  samples are necessary. Following the proof technique of [Blumer et al. \[1989\]](#), we provide the argument here for completeness. For a concept class  $\mathcal{H}$ , assume there are two points  $x_1$  and  $x_2$  and two hypothesis  $h_1, h_2 \in \mathcal{H}$ . We assume  $h_1, h_2$  agree on  $x_1$  but disagree on  $x_2$ . We consider the distribution  $\mathcal{D}$  over  $\mathcal{X}$  as follows

$$p(x) = \begin{cases} 1 - 2\epsilon, & \text{if } x = x_1 \\ 2\epsilon, & \text{if } x = x_2. \end{cases}$$

Let  $m$  be the sample size and  $\mathcal{A}$  be any algorithm that uses an i.i.d. sample  $S$  with size at most  $m$  before picking a hypothesis. Let  $B$  be the event that  $m$  samples do not sampled from  $x_2$ . Thus, we have

$$\Pr_S[\mathcal{L}_{\mathcal{D}}(h) \geq \epsilon] \geq \Pr[B] = (1 - 2\epsilon)^m.$$

The inequality follows from that if event  $B$  happens, any predictor would have  $1/2$  probability predict wrong on  $x_2$ . If we want  $(1 - 2\epsilon)^m < \delta$ ,  $m$  has to be at least  $(\log(1/\delta))/2\epsilon$ .  $\square$

## 5 Conclusion and Future Directions

In this work, we introduce the bandit DS dimension, a new combinatorial complexity measure for multiclass PAC learning with bandit feedback. In terms of this dimension, we establish a near-optimal characterization of the realizable sample complexity, resolving, up to logarithmic factors, a longstanding open question posed by [Daniely et al. \[2011\]](#). Our upper bound is obtained via LISTCASCADE, a new algorithmic framework that connects bandit learning with list learning by using list learners as intermediate predictors in a cascade, progressively reducing the ambiguity in the candidate labels until a single-label predictor is obtained. Along the way, we also prove a refined sample complexity bound for list PAC learning, which may be of independent interest. Two natural directions are particularly important: extending the approach to the agnostic setting, and determining whether the remaining logarithmic factors are necessary. In particular, it remains open whether every concept class  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  with  $\text{BDS}(\mathcal{H}) < \infty$  admits a bandit-feedback PAC learner with sample complexity  $O((\text{BDS}(\mathcal{H}) + \log(1/\delta))/\epsilon)$ .

## Acknowledgments and Disclosure of Funding

Steve Hanneke acknowledges support by grant no. 2024243 from the United States - Israel Binational Science Foundation (BSF). Shay Moran is a Robert J. Shillman Fellow; he acknowledges support by Israel PBC-VATAT, by the Technion Center for Machine Learning and Intelligent Systems (MLIS), and by the European Union (ERC, GENERALIZATION, 101039692). Views and opinions expressed are, however, those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Council Executive Agency. Neither the European Union nor the granting authority can be held responsible for them.

## References

- Ishaq Aden-Ali, Yeshwanth Cherapanamjeri, Abhishek Shetty, and Nikita Zhivotovskiy. Optimal pac bounds without uniform convergence. In *2023 IEEE 64th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 1203–1223. IEEE, 2023.
- Alekh Agarwal, Daniel Hsu, Satyen Kale, John Langford, Lihong Li, and Robert Schapire. Taming the monster: A fast and simple algorithm for contextual bandits. In Eric P. Xing and Tony Jebara, editors, *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pages 1638–1646, Beijing, China, 22–24 Jun 2014. PMLR.
- Alekh Agarwal, Sarah Bird, Markus Cozowicz, Luong Hoang, John Langford, Stephen Lee, Jiaji Li, Daniel R. Melamed, Gal Oshri, Oswaldo Ribas, Siddhartha Sen, and Alex Slivkins. Making contextual decisions with low technical debt. *arXiv: Learning*, 2016.
- Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47:235–256, 2002a.
- Peter Auer, Nicolo Cesa-Bianchi, Yoav Freund, and Robert E Schapire. The nonstochastic multiarmed bandit problem. *SIAM journal on computing*, 32(1):48–77, 2002b.
- Anselm Blumer, Andrzej Ehrenfeucht, David Haussler, and Manfred K Warmuth. Learnability and the vapnik-chervonenkis dimension. *Journal of the ACM (JACM)*, 36(4):929–965, 1989.
- Nataly Brukhim, Daniel Carmon, Irit Dinur, Shay Moran, and Amir Yehudayoff. A characterization of multiclass learnability. In *2022 IEEE 63rd Annual Symposium on Foundations of Computer Science (FOCS)*, pages 943–955. IEEE, 2022.
- Nataly Brukhim, Steve Hanneke, and Shay Moran. Improper multiclass boosting. In Gergely Neu and Lorenzo Rosasco, editors, *Proceedings of Thirty Sixth Conference on Learning Theory*, volume 195 of *Proceedings of Machine Learning Research*, pages 5433–5452. PMLR, 12–15 Jul 2023.
- Nataly Brukhim, Amit Daniely, Yishay Mansour, and Shay Moran. Multiclass boosting: simple and intuitive weak learning criteria. *Advances in Neural Information Processing Systems*, 36, 2024.
- Nataly Brukhim, Aldo Pacchiano, Miroslav Dudik, and Robert Schapire. On the hardness of bandit learning, 2025.
- Sébastien Bubeck, Nicolo Cesa-Bianchi, et al. *Regret analysis of stochastic and nonstochastic multi-armed bandit problems*. Now Publishers, Inc., 2012.
- Moses Charikar and Chirag Pabbaraju. A characterization of list learnability. In *Proceedings of the 55th Annual ACM Symposium on Theory of Computing*, pages 1713–1726, 2023.
- Moses Charikar, Chirag Pabbaraju, and Ambuj Tewari. A characterization of list language identification in the limit, 2025.
- Alon Cohen, Liad Erez, Steve Hanneke, Tomer Koren, Yishay Mansour, Shay Moran, and Qian Zhang. Sample complexity of agnostic multiclass classification: Natarajan dimension strikes back. In *Proceedings of the 58th Annual ACM Symposium on Theory of Computing (STOC 2026)*, 2026. To appear.
- Amit Daniely and Shai Shalev-Shwartz. Optimal learners for multiclass problems. In *Conference on Learning Theory*, pages 287–316. PMLR, 2014.
- Amit Daniely, Sivan Sabato, Shai Ben-David, and Shai Shalev-Shwartz. Multiclass learnability and the erm principle. In *Proceedings of the 24th Annual Conference on Learning Theory*, pages 207–232. JMLR Workshop and Conference Proceedings, 2011.
- Amit Daniely, Sivan Sabato, Shai Ben-David, and Shai Shalev-Shwartz. Multiclass learnability and the erm principle. *J. Mach. Learn. Res.*, 16(1):2377–2404, 2015.
- Ilias Diakonikolas and Daniel M Kane. *Algorithmic high-dimensional robust statistics*. Cambridge university press, 2023.

- Miroslav Dudík, Daniel Hsu, Satyen Kale, Nikos Karampatziakis, John Langford, Lev Reyzin, and Tong Zhang. Efficient optimal learning for contextual bandits. *arXiv preprint arXiv:1106.2369*, 2011.
- Liad Erez and Tomer Koren. From contextual combinatorial semi-bandits to bandit list classification: Improved sample complexity with sparse rewards. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.
- Liad Erez, Alon Cohen, Tomer Koren, Yishay Mansour, and Shay Moran. Fast rates for bandit PAC multiclass classification. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024a.
- Liad Erez, Alon Cohen, Tomer Koren, Yishay Mansour, and Shay Moran. The real price of bandit information in multiclass classification. In *Annual Conference Computational Learning Theory*, 2024b.
- Dylan J. Foster, Sham M. Kakade, Jian Qian, and Alexander Rakhlin. The statistical complexity of interactive decision making, 2023.
- Steve Hanneke and Amirreza Shaeiri. A trichotomy for list transductive online learning. In *Forty-second International Conference on Machine Learning*, 2025.
- Steve Hanneke and Liu Yang. Bandit learnability can be undecidable. In Gergely Neu and Lorenzo Rosasco, editors, *Proceedings of Thirty Sixth Conference on Learning Theory*, volume 195 of *Proceedings of Machine Learning Research*, pages 5813–5849. PMLR, 12–15 Jul 2023.
- Steve Hanneke, Shay Moran, and Waknine Tom. List sample compression and uniform convergence. In *The Thirty Seventh Annual Conference on Learning Theory*, pages 2360–2388. PMLR, 2024a.
- Steve Hanneke, Shay Moran, and Qian Zhang. Improved sample complexity for multiclass PAC learning. *Advances in Neural Information Processing Systems*, 37:42798–42839, 2024b.
- Steve Hanneke, Amirreza Shaeiri, and Hongao Wang. For universal multiclass online learning, bandit feedback and full supervision are equivalent. In *36th International Conference on Algorithmic Learning Theory*, 2024c.
- Steve Hanneke, Qinglin Meng, and Amirreza Shaeiri. Representation preserving multiclass agnostic to realizable reduction. In *Forty-second International Conference on Machine Learning*, 2025a.
- Steve Hanneke, Shay Moran, Hilla Scheffler, and Iska Tsubari. Private list learnability vs. online list learnability. In Nika Haghtalab and Ankur Moitra, editors, *Proceedings of Thirty Eighth Conference on Learning Theory*, volume 291 of *Proceedings of Machine Learning Research*, pages 5173–5213. PMLR, 30 Jun–04 Jul 2025b.
- Steve Hanneke, Amirreza Shaeiri, and Hongao Wang. Non-uniform multiclass learning with bandit feedback. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025c.
- Steve Hanneke, Amirreza Shaeiri, and Qian Zhang. Universal rates for multiclass learning with bandit feedback. *Proceedings of Machine Learning Research vol*, 291:1–53, 2025d.
- Steve Hanneke, Qinglin Meng, Shay Moran, and Amirreza Shaeiri. An optimal sauer lemma over  $k$ -ary alphabets, 2026. URL <https://arxiv.org/abs/2604.12952>.
- David Haussler, Nick Littlestone, and Manfred K Warmuth. Predicting  $\{0, 1\}$ -functions on randomly drawn points. *Information and Computation*, 115(2):248–292, 1994.
- Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.
- Lihong Li, Wei Chu, John Langford, and Robert E Schapire. A contextual-bandit approach to personalized news article recommendation. In *Proceedings of the 19th international conference on World wide web*, pages 661–670, 2010.
- Shay Moran, Ohad Sharon, Iska Tsubari, and Sivan Yosebashvili. List online classification. In *The Thirty Sixth Annual Conference on Learning Theory*, pages 1885–1913. PMLR, 2023.

- Chirag Pabbaraju and Sahasrajit Sarma Sarkar. A characterization of list regression, 2024.
- Herbert E. Robbins. Some aspects of the sequential design of experiments. *Bulletin of the American Mathematical Society*, 58:527–535, 1952.
- Benjamin Rubinstein, Peter Bartlett, and J Rubinstein. Shifting, one-inclusion mistake bounds and tight multiclass expected risk bounds. *Advances in Neural Information Processing Systems*, 19, 2006.
- Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.
- Aleksandrs Slivkins. Introduction to multi-armed bandits. *Foundations and Trends® in Machine Learning*, 12(1-2):1–286, 2019. ISSN 1935-8237. doi: 10.1561/22000000068.
- William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 1933.
- Michael Woodroofe. A one-armed bandit problem with a concomitant variable. *Journal of the American Statistical Association*, 74(368):799–806, 1979.

## A Definitions

In this section, we provide the auxiliary formal definitions that will be used in our paper. We start from the notations.

### A.1 Notations

In this subsection, we present the basic notation used in the paper; all of it is standard in the literature and is included for completeness. Let  $\mathbb{N}$  and  $\mathbb{R}$  stand for the set of natural numbers and real numbers, respectively. We denote by  $\bar{\mathbb{N}}$  the extended natural number system defined as  $\bar{\mathbb{N}} := \mathbb{N} \cup \{+\infty\}$ . In addition, for a given  $n \in \mathbb{N}$ , we use  $[n]$  to denote  $\{1, 2, \dots, n\}$ . Next, given  $n \in \mathbb{N}$ , for any sequence of size  $n$  or  $n$ -tuple  $v$ , and any  $i \in [n]$ , let us use  $v_i$  to denote the  $i$ -th element in  $v$ . Afterward, we denote by  $A \times B$  the Cartesian product of two arbitrary sets  $A$  and  $B$ . In addition, for any set  $A$  and any  $n \in \mathbb{N}$ , we let  $A^n$  indicate  $n$  times the Cartesian product of  $A$  with itself. Note that for any set  $A$ , we define  $A^0 := \emptyset$ . Also, given a set  $A$ , we denote by  $A^*$  the set of all finite sequences of members of  $A$ ; more formally,  $A^* := \bigcup_{T=0}^{\infty} A^T$ . Then, for arbitrary sets  $X$  and  $Y$ , we use  $Y^X$  to denote the space of all functions from  $X$  to  $Y$ . Additionally, let  $\mathcal{F} \subseteq Y^X$  for the arbitrary sets  $X$  and  $Y$ . Given a subset  $S \subseteq X$ , we define  $\mathcal{F}|_S$  as follows:  $\mathcal{F}|_S := \{g \mid g \in Y^S, \exists f \in \mathcal{F} \forall x \in S g(x) = f(x)\}$ . Similarly, give a sequence  $S \in X^*$ , we define  $\mathcal{F}|_S$  as follows:  $\mathcal{F}|_S := \{g \mid g \in Y^{|S|}, \exists f \in \mathcal{F} \forall i \in [|S|] g_i = f(S_i)\}$ . Going further, let  $e$  and  $\log(\cdot)$  stand for Euler's number and the Logarithm function in the base 2, respectively. Finally, we use  $\mathcal{O}(\cdot)$ ,  $\Omega(\cdot)$ , and  $\Theta(\cdot)$  to denote the standard asymptotic notation in theoretical computer science. Furthermore, we use  $\tilde{\mathcal{O}}(\cdot)$ ,  $\tilde{\Omega}(\cdot)$ , and  $\tilde{\Theta}(\cdot)$  to hide poly-logarithmic factors.

### A.2 Combinatorial Complexity Parameters

In this subsection, we present the combinatorial complexity parameters considered in this work. For each parameter, we begin by defining the associated notion of a shattered sequence or shattered set, and then define the parameter itself in terms of that notion. Before proceeding, we state the following definition.

**Definition A.1** ( $i$ -neighbor). Let  $\mathcal{Y}$  be a non-empty set. Let  $f, g \in \mathcal{Y}^d$  for some  $d \in \mathbb{N}$ . For every  $i \in [d]$ , we say that  $f$  and  $g$  are  $i$ -neighbors if  $f_i \neq g_i$  and  $\forall j \in [d] \setminus \{i\} f_j = g_j$ .

Next, we formally state the definition of the bandit DS dimension.

**Definition A.2** (BDS-shattered sequence). Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class. Let  $S \in \mathcal{X}^d$  be a sequence of instances for some  $d \in \mathbb{N}$ . Also, let  $N \in \mathbb{N}^d$ . We say that  $S$  and  $N$  is BDS-shattered by  $\mathcal{H}$ , if there exists  $F \subseteq \mathcal{H}$ ,  $|F| < \infty$  such that for all  $f \in F_S$  and for all  $i \in [d]$ ,  $f$  has at least  $N_i$  distinct  $i$ -neighbor in  $F_S$ .

**Definition A.3** (Bandit DS dimension). Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class. The *Bandit DS dimension* of  $\mathcal{H}$ , denoted by  $\text{BDS}(\mathcal{H}) \in \bar{\mathbb{N}} \cup \{0\}$ , is defined as the  $\sup_{d \in \mathbb{N} \cup \{0\}}$  such that there exist a sequence of instances  $S \in \mathcal{X}^{d'}$  for some  $d' \in \mathbb{N}$  and  $N \in \mathbb{N}^{d'}$  such that  $\sum_{i=1}^{d'} N_i = d$  that is BDS-shattered by  $\mathcal{H}$ .

Next, we define combinatorial complexity parameters related to list PAC learning. Notably, when the list size is equal to one, each of these dimensions coincides with its corresponding counterpart in the multiclass setting. We begin with the definition of the  $\text{DS}_L$  dimension.

**Definition A.4** ( $\text{DS}_L$ -shattered sequence). Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class, and  $L \in \mathbb{N}$ . Let  $S \in \mathcal{X}^d$  be a sequence of instances for some  $d \in \mathbb{N}$ . We say that  $S$  is  $\text{DS}_L$ -shattered by  $\mathcal{H}$ , if there exists  $F \subseteq \mathcal{H}$ ,  $|F| < \infty$  such that for all  $f \in F_S$  and for all  $i \in [d]$ ,  $f$  has at least  $L$  distinct  $i$ -neighbor in  $F_S$ .

**Definition A.5** ( $\text{DS}_L$  dimension [Charikar and Pabbaraju \[2023\]](#)). Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class, and  $L \in \mathbb{N}$ . The  $\text{DS}_L$  dimension of  $\mathcal{H}$ , denoted by  $\text{DS}_L(\mathcal{H}) \in \bar{\mathbb{N}} \cup \{0\}$ , is defined as the  $\sup_{d \in \mathbb{N} \cup \{0\}}$  such that there exists a sequence of instances  $S \in \mathcal{X}^d$  that is  $\text{DS}_L$ -shattered by  $\mathcal{H}$ .

Next, we introduce the  $L$ -Exponential dimension. This combinatorial complexity parameter is particularly useful in shifting arguments.



**Definition A.6** ( $E_L$ -shattered set). Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class, and  $L \in \mathbb{N}$ . Let  $S \subseteq \mathcal{X}$  be a set of instances of size  $d$  for some  $d \in \mathbb{N}$ . We say that  $S$  is  $E_L$ -shattered by  $\mathcal{H}$ , if  $|\mathcal{H}|_S| \geq (L+1)^d$ .

**Definition A.7** (L-Exponential dimension [Charikar and Pabbaraju \[2023\]](#)). Let  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  be a concept class, and  $L \in \mathbb{N}$ . The L-Exponential dimension of  $\mathcal{H}$ , denoted by  $E_L(\mathcal{H}) \in \mathbb{N} \cup \{0\}$ , is defined as the  $\sup_{d \in \mathbb{N} \cup \{0\}}$  such that there exists a set of instances  $S \subseteq \mathcal{X}$  of size  $d$  that is  $E_L$ -shattered by  $\mathcal{H}$ .

### A.3 Multiclass Learning with Bandit Feedback Algorithms

To improve readability, we use a comma to separate indices when multiple indices are involved. For example, let  $v$  be a sequence of length 5 whose elements are 2-tuples. We denote by  $v_{5,1}$  the first component of the 5-th element of  $v$ . In addition, letting  $m, n \in \mathbb{N}$  be such that  $m \leq n$ , we write  $\left[ (x_i, y_i, z_i) \right]_{i=m}^n$  to denote  $((x_m, y_m, z_m), (x_{m+1}, y_{m+1}, z_{m+1}), \dots, (x_n, y_n, z_n))$ . This section is similar in spirit to [Hanneke et al. \[2025d\]](#).

Let  $\mathbf{A}$  be a multiclass PAC learning with bandit feedback algorithm. For any  $u \in (\mathcal{X} \times \Sigma)^*$  and any  $x \in \mathcal{X}$ , let us write  $\mathbf{A}_1(x; u)$  to denote  $\mathbf{A}_1((u, x))$ . Also, for every finite sequence of examples  $S \in \mathcal{Z}^n = (\mathcal{X} \times \mathcal{Y})^n$  of size  $n$  for some  $n \in \mathbb{N}$ , we denote by  $\mathbf{B}_{\mathbf{A}}(S)$  the random variable taking values in  $(\mathcal{X} \times \Sigma)^n$  representing the first part of the input of  $\mathbf{A}_1$  in round  $n+1$  when the choices of nature are obtained according to  $S$ , which is recursively defined as follows:

$$\begin{aligned} \mathbf{B}_{\mathbf{A}}(S)_{i,1} &:= S_{i,1}, \quad 1 \leq i \leq n \\ \mathbf{B}_{\mathbf{A}}(S)_{i,2} &:= \begin{cases} y \sim \mathbf{A}_1(S_{1,1}; \emptyset), & i = 1 \\ y \sim \mathbf{A}_1(S_{i,1}; [\mathbf{B}_{\mathbf{A}}(S)_{j,1}, \mathbf{B}_{\mathbf{A}}(S)_{j,2}, \mathbf{B}_{\mathbf{A}}(S)_{j,3}]_{j=1}^{i-1}), & 1 < i \leq n \end{cases} \\ \mathbf{B}_{\mathbf{A}}(S)_{i,3} &:= \mathbb{1}\{\mathbf{B}_{\mathbf{A}}(S)_{i,2} \neq S_{i,2}\}, \quad 1 \leq i \leq n \end{aligned}$$

Building upon that, for every finite sequence of examples  $S \in \mathcal{Z}^n = (\mathcal{X} \times \mathcal{Y})^n$  of size  $n$  for some  $n \in \mathbb{N}$ , we denote by  $\hat{h}_{\mathbf{A}}^S$  the random function taking values in  $\mathcal{Y}^{\mathcal{X}}$  such that for every  $x \in \mathcal{X}$ , we have:  $\hat{h}_{\mathbf{A}}^S(x) = \hat{y}$ , where  $\hat{y} \sim \mathbf{A}_2((\mathbf{B}_{\mathbf{A}}(S), x))$ .

### A.4 One-inclusion Graphs

We now introduce an important combinatorial object associated with a hypothesis class, namely, the one-inclusion hypergraph.

**Definition A.8** (One-inclusion hypergraph [Haussler et al. \[1994\]](#), [Rubinstein et al. \[2006\]](#)). The one-inclusion hypergraph of  $\mathcal{H} \subseteq \mathcal{Y}^m$  for some  $m \in \mathbb{N}$  is a hypergraph  $G(\mathcal{H}) = (V, E)$  that is defined as follows. The vertex set is  $V = \mathcal{H}$ . For each  $i \in [m]$  and  $f : [m] \setminus \{i\} \rightarrow \mathcal{Y}$ , let  $e_{i,f}$  be the set of all  $h \in \mathcal{H}$  that agree with  $f$  on  $[m] \setminus \{i\}$ . The edge set is defined as follows:

$$E = \{e_{i,f} \mid i \in [m], f : [m] \setminus \{i\} \rightarrow \mathcal{Y}, e_{i,f} \neq \emptyset\}.$$

Moreover, we say that the edge  $e_{i,f} \in E$  is in the direction  $i$ , and is adjacent to the hypothesis/vertex  $h$  if  $h \in e_{i,f}$ . In addition, every vertex  $h \in V$  is adjacent to exactly  $m$  edges. Further, the size of the edge  $e_{i,f}$  is the size of the set  $|e_{i,f}|$ .

For the one-inclusion hypergraph, we study the degrees of its vertices and its average degree.

**Definition A.9** (L-degree [Charikar and Pabbaraju \[2023\]](#)). Let  $G(\mathcal{H}) = (V, E)$  be the one-inclusion hypergraph of  $\mathcal{H} \subseteq \mathcal{Y}^m$  for some  $m \in \mathbb{N}$ . The L-degree of a vertex  $v \in V$  is defined as follows:

$$\deg^L(L) = |\{e \in E : v \in e, |e| > L\}|.$$

**Definition A.10** (Average L-degree [Charikar and Pabbaraju \[2023\]](#)). Let  $G(\mathcal{H}) = (V, E)$  be the one-inclusion hypergraph of  $\mathcal{H} \subseteq \mathcal{Y}^m$  for some  $m \in \mathbb{N}$ . The average L-degree of  $\mathcal{H}$  is defined as follows:

$$\text{avd}^L(\mathcal{H}) := \frac{1}{|V|} \sum_{v \in V} \deg^L(v) = \frac{1}{|V|} \sum_{e \in E : |e| > L} |e|.$$

Next, we restate the definition of a list orientation of the one-inclusion hypergraph from [Charikar and Pabbaraju \[2023\]](#). This notion captures the behavior of a deterministic learning algorithm that receives a labeled sample together with an unlabeled test point and outputs a prediction for that test point.

**Definition A.11** (List Orientation [Charikar and Pabbaraju \[2023\]](#)). Let  $G(\mathcal{H}) = (V, E)$  be the one-inclusion hypergraph of  $\mathcal{H} \subseteq \mathcal{Y}^m$  for some  $m \in \mathbb{N}$ . A list orientation  $\sigma^L$  of  $G(\mathcal{H}) = (V, E)$  having list size  $L$  is a mapping  $\sigma^L : E \rightarrow \{V' \subseteq V : |V'| \leq L\}$  such that for each edge  $e \in E$ ,  $\sigma^L(e) \subseteq e$ .

For a list orientation, we define its  $L$ -outdegree.

**Definition A.12** ( $L$ -outdegree of a list orientation [Charikar and Pabbaraju \[2023\]](#)). Let  $G(\mathcal{H}) = (V, E)$  be the one-inclusion hypergraph of  $\mathcal{H} \subseteq \mathcal{Y}^m$  for some  $m \in \mathbb{N}$ , and let  $\sigma^L$  be a  $L$ -list orientation of it. The  $L$ -outdegree of  $v \in V$  in  $\sigma^L$  is defined as follows:

$$\text{outdeg}^L(v; \sigma^L) := |\{e : v \in e, v \notin \sigma^L(e)\}|.$$

The maximum  $L$ -outdegree of  $\sigma^L$  is

$$\text{outdeg}^L(\sigma^L) := \sup_{v \in V} \text{outdeg}^L(v; \sigma^L).$$

## B Deferred Proofs

Next, we present Algorithm 2, which is the subroutine of Algorithm 1, corresponding to the one-inclusion list learners in [Charikar and Pabbaraju \[2023\]](#), [Hanneke et al. \[2026\]](#). For the sake of completeness, we restate the algorithm below.

---

**Algorithm 2** The one-inclusion list algorithm  $\mathcal{A}_{\mathcal{H}}^L$  for  $\mathcal{H} \subseteq \mathcal{Y}^{\mathcal{X}}$  of list size  $L$ .

---

**Input:** A sample  $S = ((x_1, y_1), \dots, (x_m, y_m))$  realizable by  $\mathcal{H}$  and list size  $L$ .

**Output:** A  $L$ -list hypothesis  $\mathcal{A}_{\mathcal{H}}^L(S) = \mu_S^L : \mathcal{X} \rightarrow \{Y \subseteq \mathcal{Y} : |Y| \leq L\}$ .

---

For each  $x \in \mathcal{X}$ , the  $L$ -list  $\mu_S^L(x)$  is computed as follows.

- 1: Consider the class  $\mathcal{H}' \subseteq \mathcal{Y}^{m+1}$  of all patterns over the *unlabeled data* that are realizable by  $\mathcal{H}$ .
- 2: Find a  $L$ -list orientation  $\sigma^L$  of  $G(\mathcal{H}')$  that *minimizes* the *maximum*  $L$ -outdegree.
- 3: Consider the edge in direction  $m+1$  defined by  $S$ :

$$e = \{h \in \mathcal{H}' : \forall i \in [m] \ h(i) = y_i\}.$$

- 4: Set  $\mu_S^L(x) = \{h(m+1) : h \in \sigma^L(e)\}$ .
- 

Next we show the complete calculation in the proof of Lemma 4.3 and Theorem 4.1

### B.1 Complete calculation in the proof of Lemma 4.3

*Proof of Lemma 4.3.* Consider the set  $S$  which realizes  $d_{\mathcal{E}}^L$ , so that  $|S| = d_{\mathcal{E}}^L$ . Then we have that

$$|\mathcal{H}|_S \geq (L+1)^{d_{\mathcal{E}}^L}.$$

On the other hand, by Theorem 1 of [Hanneke et al. \[2026\]](#), we know that

$$|\mathcal{H}|_S \leq \left\lceil \frac{L}{2} \right\rceil^{d_{\mathcal{E}}^L - d_{\text{DS}}^{\lceil L/2 \rceil}} \left( \frac{eK d_{\mathcal{E}}^L}{d_{\text{DS}}^{\lceil L/2 \rceil}} \right)^{d_{\text{DS}}^{\lceil L/2 \rceil}}.$$

Combining the above two inequalities, we have

$$(L+1)^{d_{\mathcal{E}}^L} \leq \left\lceil \frac{L}{2} \right\rceil^{d_{\mathcal{E}}^L - d_{\text{DS}}^{\lceil L/2 \rceil}} \left( \frac{eK d_{\mathcal{E}}^L}{d_{\text{DS}}^{\lceil L/2 \rceil}} \right)^{d_{\text{DS}}^{\lceil L/2 \rceil}}.$$

Note that  $\lceil L/2 \rceil \leq \frac{L+1}{2}$ .

$$(L+1)^{d_E^L} \leq \left( \frac{L+1}{2} \right)^{d_E^L - d_{DS}^{\lceil L/2 \rceil}} \left( \frac{eK d_E^L}{d_{DS}^{\lceil L/2 \rceil}} \right)^{d_{DS}^{\lceil L/2 \rceil}}.$$

By rearranging the term, we have

$$\left( \frac{2L+2}{L+1} \right)^{d_E^L} \leq \left( \frac{2eK d_E^L}{(L+1) d_{DS}^{\lceil L/2 \rceil}} \right)^{d_{DS}^{\lceil L/2 \rceil}}.$$

Taking the logarithm of both sides and rearranging the terms, we get

$$\frac{d_E^L}{d_{DS}^{\lceil L/2 \rceil}} \leq \frac{\log \left( \frac{2eK d_E^L}{(L+1) d_{DS}^{\lceil L/2 \rceil}} \right)}{\log(2)}.$$

Thus, we have

$$\frac{d_E^L}{d_{DS}^{\lceil L/2 \rceil}} \leq \frac{1}{\log(2)} \log \left( \frac{2eK}{L+1} \right) + \frac{1}{\log(2)} \log \left( \frac{d_E^L}{d_{DS}^{\lceil L/2 \rceil}} \right).$$

Leveraging Lemma A.2. in [Shalev-Shwartz and Ben-David \[2014\]](#), we have

$$\frac{d_E^L}{d_{DS}^{\lceil L/2 \rceil}} \leq \frac{1}{\log(2)} \log \left( \frac{2eK}{L+1} \right) + 2 \frac{1}{\log(2)} \log \left( \frac{1}{\log(2)} \right).$$

Since  $L \geq 1$ ,

$$\frac{d_E^L}{d_{DS}^{\lceil L/2 \rceil}} \leq \frac{1 + \log K + 2 \log(1/\log 2)}{\log 2}.$$

For  $K \geq 2$ , this implies

$$d_E^L \leq 5.05 d_{DS}^{\lceil L/2 \rceil} \log K \leq 6 d_{DS}^{\lceil L/2 \rceil} \log K.$$

□

## B.2 Complete calculation in the proof of Theorem 4.1

*Proof of Theorem 4.1.* Based on Lemma 4.6, we know that with probability at least  $1 - \delta$ , the hypothesis  $h_S$  returned by Algorithm 1 has error rate at most  $\epsilon$ . Thus the sample complexity  $\mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta)$  can be upper bounded by the sample size of Algorithm 1. Formally, we have

$$\begin{aligned} \mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) &\leq \sum_{t=1}^{\lfloor \log(K) \rfloor} (m_t - m_{t-1}) \\ &= \sum_{t=1}^{\lfloor \log(K) \rfloor} \frac{4L_{t-1}}{1 - \frac{(t-1)\epsilon}{\log(K)}} \cdot \left( 10 \frac{\left( 6d_{DS}^{\lceil L_{t-1}/2 \rceil} \log K + \log \left( \frac{2 \log K}{\delta} \right) \right) \log K}{\epsilon} \right. \\ &\quad \left. + \log \left( \frac{2 \log K}{\delta} \right) \right) \\ &\leq \frac{240 \max_{1 \leq t \leq \lfloor \log(K) \rfloor} \left( L_{t-1} d_{DS}^{\lceil L_{t-1}/2 \rceil} \right) (\log K)^2}{\epsilon(1-\epsilon)} \\ &\quad + \frac{40K \log \left( \frac{2 \log K}{\delta} \right) (\log K)}{\epsilon(1-\epsilon)} + \frac{K \log \left( \frac{2 \log K}{\delta} \right)}{1-\epsilon} \end{aligned}$$

When  $\epsilon \in (0, 0.1)$ , we have

$$\begin{aligned} \mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) &\leq 276 \frac{\max_{1 \leq t \leq \lfloor \log(K) \rfloor} \left( L_{t-1} d_{DS}^{\lceil L_{t-1}/2 \rceil} \right) (\log K)^3}{\epsilon} \\ &\quad + 46 \frac{K \log K \log \left( \frac{2 \log K}{\delta} \right)}{\epsilon} + 4K \log \left( \frac{2 \log K}{\delta} \right). \end{aligned}$$

Replacing  $L_t$  by its definition in the above inequality, we have:

$$\begin{aligned} \mathbf{m}_{\mathcal{H}}^B(\epsilon, \delta) &\leq 552 \frac{\max_{1 \leq L \leq K-1} (L d_{DS}^L) (\log K)^3}{\epsilon} \\ &\quad + 46 \frac{K \log K \log \left( \frac{2 \log K}{\delta} \right)}{\epsilon} + 4K \log \left( \frac{2 \log K}{\delta} \right), \end{aligned}$$

which finishes the proof.  $\square$

## C Concentration Inequalities

This section collects standard concentration inequalities for sums of independent random variables, which are used throughout our analysis for the reader's convenience.

**Lemma C.1** (Chernoff Bound). *Let  $(X_1, X_2, \dots, X_n)$  be a sequence of  $n$  independent Bernoulli random variables for some  $n \in \mathbb{N}$ , and define  $X := \sum_{i=1}^n X_i$ . Moreover, let  $\mu = \mathbb{E}[X]$ . Then, the following inequalities hold.*

1. (**Upper Tail**) For any  $\delta > 0$ , we have:

$$\mathbb{P}[X \geq (1 + \delta)\mu] \leq \exp \left( -\frac{\delta^2 \mu}{2 + \delta} \right).$$

2. (**Lower Tail**) For any  $0 < \delta < 1$ , we have:

$$\mathbb{P}[X \leq (1 - \delta)\mu] \leq \exp \left( -\frac{\delta^2 \mu}{2} \right).$$

**Lemma C.2** (Bernstein's Inequality). *Let  $(X_1, X_2, \dots, X_n)$  be a sequence of  $n$  independent real-valued random variables with zero mean (i.e., for every  $i \in [n]$ , we have:  $\mathbb{E}[X_i] = 0$ ). Suppose that there exists a constant  $M \in \mathbb{R}^+$  such that for every  $i \in [n]$ , we have:  $|X_i| \leq M$  almost surely. Moreover, define  $S_n := \sum_{i=1}^n X_i$ , and  $\sigma^2 := \sum_{i=1}^n \mathbb{E}[X_i^2]$ . Then for any  $t > 0$ , the following holds.*

$$\mathbb{P}[S_n \geq t] \leq \exp \left( -\frac{t^2}{2\sigma^2 + \frac{2}{3}Mt} \right).$$

Furthermore, applying the same bound to both  $S_n$  and  $-S_n$  yields the two-sided inequality below.

$$\mathbb{P}[|S_n| \geq t] \leq 2 \exp \left( -\frac{t^2}{2\sigma^2 + \frac{2}{3}Mt} \right).$$