

Accessories

SMART CONTROL PANELS



Type	1Ph CSR / CSCR & 3Ph D.O.L
Power Range	0.75kW - 15kW
Voltage	230V - 380V - 50Hz
Enclosure	FRP
Protection	IP 54
Features	Previous 5 fault record display, remote monitor, accumulative running time display & sound alarm for fault, over load protection, dry run protection, under & over voltage protection, phase unbalance protection, phase reversal protection & open phase protection

VFD INVERTERS

VFD XS SERIES

Power Range	1Ph - 0.75 - 2.2kW / 1.0 - 3.0HP 3Ph - 4.0 - 7.5kW / 5.5 - 10HP
Input Voltage	220VAC or 380VAC 380VAC
Input Frequency	50 & 60Hz
Protection	MS Powder Coated / Plastic
Pressure Sensor Range	10bar / 16bar / 25bar
Self-starting Pressure	Pre set pressure value 0.3 bar
System Configuration Requirement	fit with 4L or above pressure tank on the pipe line. (the inflation pressure = 60% setting)
Ambient Temperature	(-10~+40)C



TIWN BOOSTER CONTROL

VFD TB SERIES



Type	TB - 01	TB - 03
Working Voltage	AC220V / 50Hz / 60Hz	AC380V / 50Hz / 60Hz
Rated Output Power	0.37-2.2KW	0.75-4KW/5.5-7.5KW/11KW/15KW
Under/Over Voltage Recovery Time	5 minutes	
Low-voltage Cut-Off	AC 176V	AC 304V
High-voltage Cut-Off	AC 253V	AC 437V
Locked - Rotor Cut - Off Time	1 seconds	
Dry-Running Cut-Off Time	10 seconds / 3seconds / 5 minutes optional	
Distance For Signal Transmll	200m	
Adaptive Presure Sensor	DC5V/0.5-4.5V, 0.1.0mpa, 0-2.5mpa,DC5V working voltage/0.5-4.5V signal output type, range 0-1.0mpa, 0-1.6mpa, 0-2.5mpa can be selected	