

1. READ IN CONJUNCTION WITH CONCRETE SPECIFICATION
2. ALL CONCRETE TO BE GRADE C28/35 UNLESS NOTED OTHERWISE
3. SEE DRG. S001 FOR COVER TO REINFORCEMENT
4. USE 75MM LEAN MIX CONCRETE BLINDING ON COMPACTED FORMATION TO ALL FOUNDATIONS
5. ALL REINFORCING STEEL TO BE HIGH YIELD 460-500/SQ.MM
6. ALL CONCRETE TO BE FULLY VIBRATED TO ENSURE NO HONEYCOMBING
7. ALL FORMWORK TO BE MADE WITH SHUTTERING PLYWOOD PROPPED AND BRACED AS NECESSARY

1. DO NOT SCALE FROM THIS DRAWING
2. ALL DIMENSIONS ARE IN MM UNLESS NOTED OTHERWISE
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT ENGINEERS DRAWINGS, SPECIFICATIONS AND CONTRACT DOCUMENTS
4. ALL WORKS ARE TO BE IN ACCORDANCE WITH THE RELEVANT AND CURRENT HEALTH AND SAFETY LEGISLATION
5. SPECIFICATION OF THE WORKS TO BE TO THE APPROPRIATE EURO STANDARD OR THE EQUIVALENT BRITISH STANDARD
6. EXCAVATIONS FOR FOUNDATIONS TO BE INSPECTED BY THE ENGINEER PRIOR TO POURING OF THE FOUNDATIONS

TOC	STRUCTURAL FLOOR LEVEL
TOT	TOP LEVEL OF STRUCTURAL CONCRETE
TFS	TOP LEVEL OF STEEL BEAM/COLUMN
TOF	FINISHED FLOOR LEVEL
RF	REINFORCED CONCRETE
PC	PRE-CAST
BM	BEAM/IS
COL	COLUMN/IS
CONC.	CONECRETE
	GRID LINE / CENTRE LINE
IJ	ISOLATION JOINT
LJ	LONGITUDINAL JOINT
TJ	TRANSVERSE JOINT
MJ	MOVEMENT JOINT
T.L	TOP LEVEL
THK	THICK
HDG	HOT DIPPED GALVANIZED

	DEMOLITION EXISTING BLOCK WALL 215mm
	DEMOLITION EXISTING STONE WALL 500-600mm
	NEW SOLID 7.5N BLOCKWORK WALL
	NEW STONE FACING REFER TO ARCH
	215x 65dp PRESTRESSED LINTEL 225mm BEARING
	100x 65dp PRESTRESSED LINTEL 225mm BEARING
	215x 215dp STONE LINTEL 225mm BEARING
	120x120x12 RSA ANGLE HOT DIP GALV 450mm BEARING
	RIISING CONCRETE OUTLINES
	SPLAY/EDGE UNDER FLOOR SLAB
	VOID IN CONCRETE
	DETAILED SECTION 1-1 SHOW ON DRG. T4988-S002
	MEANS REFER TO DRAWING T4988-S003 FOR DETAIL ENLARGED DETAIL '1'
	DIRECTION OF SPAN OF SLAB

STEEL S275 JO UNO

STEEL S275 JO UNO
C1 203x133ub
C2 152x127RSJ37 with
350x350 rc surround
C3 203uc46
C4 254uc73
C5 350x700 RC column
C6 350x1150 RC column
C7 305uc97
C8 152uc37 (S355)
C9 152uc44 (S355)

PAD FOUNDATION LEGEND
 B16-150 ctrs EW T&B
 P1 2x2x0.45m dp
 P2 1.8x1.4x0.45m dp
 P3 1.8x1.5x0.45 dp
 P4 ex. 2.5x2x0.45m dp
 P5 ex. 1.8x1.5x0.45m dp
 P6 ex. 1.4x1.4x0.45m dp
 P7 2x2x0.45 dp RC Basement Slab

SLABS C28/35 (20mm)
S1 450mm dp B20 150 EW T&B
S2 190dp Comflor 60 with A393
S3 450mm dp B20 150 EW T&B
S4 200-275 Comflor 60 with A393
S5 18mm OSB on 225x44 c16 JOISTS

-	CF	CF	TENDER ISSUE	28.04.26
REV	REV BY	APPRD	DESCRIPTION	DATE

JA
Gorman
consulting engineers
project managers

Forest Park,
Mullingar, Co. Westmeath.
Tel: 044-9347338 / 9347341
Fax: 044-9347400
Email: info@jagorman.ie
Web: www.jagorman.ie

CLIENT: CARROLLS IRISH GIFTS

PROJECT TITLE:

IMMERSIVE EXPERIENCE
TALBOT STREET DUBLIN

DRAWING TITLE:

PROPOSED FOUNDATION PLAN
STRUCTURE

PLOT SIZE: A1	PLOT SCALE: As Shown	DRAWN BY: CF	CHECKED BY: CF
APPROVED BY: JG	PROJECT No: 4988	DRAWING No: T4988-S006	REV: -

Copyright © J.A. Gorman Consulting Engineers Ltd. Unauthorized reproduction prohibited.

