

1. DO NOT SCALE FROM THIS DRAWING
2. ALL DIMENSIONS ARE IN MM UNLESS NOTED OTHERWISE
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT ENGINEERS DRAWINGS, SPECIFICATIONS AND CONTRACT DOCUMENTS
4. ALL WORKS ARE TO BE IN ACCORDANCE WITH THE RELEVANT AND CURRENT HEALTH AND SAFETY LEGISLATION
5. SPECIFICATION OF THE WORKS TO BE TO THE APPROPRIATE EURO STANDARD OR THE EQUIVALENT BRITISH STANDARD
6. EXCAVATIONS FOR FOUNDATIONS TO BE INSPECTED BY THE ENGINEER PRIOR TO POURING OF THE FOUNDATIONS

LEGEND:

	DEMOLITION EXISTING BLOCK WALL 215mm
	DEMOLITION EXISTING STONE WALL 500-600mm
	NEW SOLID 7.5N BLOCKWORK WALL
	NEW STONE FACING REFER TO ARCH
	215x 65dp PRESTRESSED LINTEL 225mm BEARING
	100x 65dp PRESTRESSED LINTEL 225mm BEARING
	215x 215dp STONE LINTEL 225mm BEARING
	120x120x12 RSA ANGLE HOT DIP GALV 450mm BEARING
	RIISING CONCRETE OUTLINES
	SPLAY/EDGE UNDER FLOOR SLAB
	VOID IN CONCRETE
	DETAILED SECTION 1-1 SHOW ON DRG. T4030-S002
	MEANS REFER TO DRAWING T4030-S003 FOR DETAIL ENLARGED DETAIL '1'
	DIRECTION OF SPAN OF SLAB

TENDER ISSUE

JA Gorman
consulting engineers
project managers

Forest Park,
Mullingar, Co. Westmeath.
Tel: 044-9347338 / 9347341
Fax: 044-9347400
Email: info@jagorman.ie
Web: www.jagorman.ie

PROJECT TITLE:

IMMERSIVE EXPERIENCE
TALBOT STREET DUBLIN

PLOT SIZE: A1	PLOT SCALE: 1:50	DRAWN BY: CF	CHECKED BY: CF
APPROVED BY: JG	PROJECT No: 4988	DRAWING No: T4988-S010	REV: 1

4

5

6

GCP Green Roof
100mm seedum subsoil on 25mm Hydroduct 550RS
drainage layer on 80mm kingspan greenguard
insulation on Integritank 2 part epoxy waterproof
on 200mm RC Composite Slab comflor 60 A393 mesh
C28/35 10mm aggregate laid to fall on new
305x165UB40 beams

TOP +8.55

B10
New RC Slab Level 200mm RC
Composite Slab comflor 60 A393 mesh
C28/35 10mm aggregate supported by
200x90PFC channels fixed 150mm
ctrs to blockwall

B10

FF+4.05

New RC Stairs 175mm
waist C28/35 Concrete
allow 150 kg/m3 rebar B16
& B12 at 150 ctrs

New RC Slab Level
200mm RC Composite Slab
comflor 60 A393 mesh
C28/35 10mm aggregate
supported by 200x90PFC
channels fixed 150mm ctrs
to blockwall

New RC Slab
450mm RC Slab C28/35
allow 250 kg /m3
waterproofing to include
water bar and GCP
prepruffe waterproofing
membrane by specialist

GF+0.00

-2.40

New 150mm Ground B
Slab A393 mesh on 80
greenguard insulation
radon membrane provi
50mm edge insulation
150mm compacted CL

SECTION A-A

Proposed

SCALE 1:50