

Dell Technologies APEX Data Storage Services vs. Amazon EBS io2 Block Express storage: Oracle database I/O load generator performance and cost analysis

Principled Technologies tested two solutions that enable companies to get enterprise-level storage without purchasing storage arrays

The cost of ownership for an enterprise-class storage solution can be quite expensive, leading some organizations to consider the alternative of cloud service providers such as Amazon Web Services (AWS). However, we found that APEX Data Storage Services, an on-premises Storage as-a-Service solution from Dell Technologies, performed comparably to similar cloud storage from AWS in a synthetic I/O workload while having a significantly lower monthly cost.

At Principled Technologies, we compared the I/O performance and monthly cost of two solutions:

- APEX Data Storage Services (50TB Balanced-tier block storage)
- Amazon EBS io2 Block Express (16 x 3TB volumes with 21,916 provisioned IOPS each)

We found that similarly configured storage from each company had comparable I/O performance and offered sub-millisecond database sequential read latency. However, Dell Technologies APEX Data Storage Services delivered significant cost savings—up to 81 percent of the monthly subscription costs of the Amazon EBS io Block Express Storage solution.

*APEX Data Storage Services vs. 16 x 3TB volumes of Amazon EBS io2 Block Express storage with a provisioned IOPS rate of 21,916 each.



More costeffective

Up to 81% cost savings vs. Amazon EBS io2 Block Express cloud subscription





Comparable IOPS and storage throughput performance*





Sub-millisecond database sequential read latency

0.96ms latency provides fast response times for database queries

What is APEX Data Storage Services?

APEX Data Storage Services is a Storage as-a-Service offering from Dell Technologies. It enables customers to subscribe to hardware, infrastructure maintenance, and elastic capacity that they can manage via the APEX Console.

APEX Data Storage Services can deliver on-premises block and file storage at several performance tiers. We tested a solution with 50TB of block storage in the Balanced performance tier, which is the middle performance tier of the APEX Data Storage Services offering. According to the website, Dell Technologies has a defined time-to-value objective of as little as 14 days for their APEX Data Storage Services offerings. In a recent Principled Technologies study, we purchased, received, and activated an APEX Data Storage Services solution in just 13 days.²

To learn more, visit www.DellTechnologies.com/APEX-Storage.

How we tested

The hardware/software we tested

The Dell Technologies solution comprised an APEX Balanced-tier block storage system connected to four Dell EMC PowerEdge™ R640 servers powered by Intel® Xeon® Gold 6248R processors. All hardware ran within a Dell Technologies data center, with remote access for the Principled Technologies (PT) team to conduct testing. Dell set up the hardware and connectivity between servers and storage. Additionally, Dell configured the four servers in a cluster with VMware vSphere 7 Update 2. The PT team verified the configuration and had exclusive access to the test environment for the duration of testing.

We configured four test VMs (one per server), each containing 48 vCPUs and 384 GB of RAM. For the storage, we created 16 x 3TB volumes for each of the VMs and attached the volumes to the VMs via raw device mapping (RDM).

The Amazon solution comprised 16 x 3TB Amazon EBS io2 Block Express volumes attached to four Amazon EC2 r5b series instances (r5b.12xlarge), with four volumes per instance. We chose io2 Block Express because it is the latest offering from Amazon, with the best specs. For provisioned IOPS beyond 32,000 per volume, io2 is also less expensive than io1. We chose a provisioned IOPS rate of 21,916 for each storage volume in order to match the performance of the APEX Data Storage Services solution we tested. The r5b instances each contained 48 vCPUs, 384 GB of RAM, and ran in the East US 2 region. We selected the R5b instance type because at the time of testing, it was the only instance type that supported io2 Block Express. The default EBS service quotas for io2 are 100,000 provisioned IOPS and 20 TB storage capacity. In preparation for testing, we used the AWS UI to request a service quota increase to 360,000 provisioned IOPS and 70 TB of storage capacity.

Each solution's VMs/instances ran Oracle[®] Linux 7.9 and Oracle Database 19c with Oracle ASM configured at the file system level for the Oracle Database.

The load generator we used

We tested each solution with a synthetic load generator for Oracle Database (Silly Little Oracle Benchmark³). To simulate the I/O profile of a common online transaction processing workload, we ran the SLOB workload on each VM at a 70:30 read/write ratio. Additionally, we configured the workload with 24 schemas at a 48GB scale to target an active dataset of about 1 TB per volume, or 4 TB total. To generate a high level of IOPS, we ran the workload at 0 think time. We collected system resource usage data with the iostat Linux command and captured database performance using Oracle AWR reports.

Results

IOPS and throughput

Storage admins can configure Amazon EBS io 2 Block Express volumes with specific IOPS maximums. To determine the rate of provisioned IOPS to set for each io 2 Block Express volume, we first determined the average per-volume IOPS rate APEX Data Storage Services solution was capable of while still achieving sub-millisecond database sequential read latency with our 16 database volumes. In our case, the average IOPS was 350,661 (21,916 per volume). This gave us comparable IOPS specs for each solution.

We found that the APEX Data Storage Services solution and the Amazon EBS io 2 solution had comparable performance in both IOPS and storage throughput. For IOPS, the two solutions were within 0.51 percent of each other's performance. The percent difference for storage throughput was 0.43. Figures 1 and 2 illustrate these results.

Database sequential read latency and average wait

The two solutions also achieved comparable latency results. Both solutions had sub-millisecond database sequential read latency (Figure 3), which is an important metric to hit for an enterprise-level storage system, as your company's databases need to handle potentially billions of lookups each day. Additionally, the APEX Data Storage Services solution achieved a shorter average wait latency than the Amazon EBS io2 solution (Figure 4). Average wait (or 'await,' as it appears in iostat) is the measure of time required for the system to issue, process, and respond to I/O requests.



Higher is better

Dell Technologies APEX Data Storage Services

350,661 IOPS

Amazon EBS io 2 Block Express

348,862 IOPS

Figure 1: Average input/output operations per second (IOPS) for the Dell Technologies APEX Data Storage Services and Amazon EBS io2 Block Express solutions. Source: Principled Technologies.

Database sequential read latency

Lower is better

Dell Technologies APEX Data Storage Services

0.96 ms

Amazon EBS io 2 Block Express

0.92 ms

Figure 3: Average database sequential read latency (in milliseconds) for the Dell Technologies APEX Data Storage Services and Amazon EBS io Block Express solutions. Source: Principled Technologies.



Higher is better

Dell Technologies APEX Data Storage Services

2,822.50 MB/s

Amazon EBS io 2 Block Express

2,810.20 MB/s

Figure 2: Average data throughput (in megabytes per second) achieved by the Dell Technologies APEX Data Storage Services and Amazon EBS io 2 Block Express solutions. Source: Principled Technologies.

Average wait (await) latency

Lower is better

Dell Technologies APEX Data Storage Services

1.37 ms

Amazon EBS io 2 Block Express

3.45 ms

Figure 4: Average wait time (in milliseconds) for the Dell Technologies APEX Data Storage Services and Amazon EBS io 2 Block Express solutions.

Source: Principled Technologies.

Cost analysis

After determining that the Dell and Amazon solutions could achieve comparable I/O performance, we wanted to gauge which solution would be more cost-effective. We researched the monthly cost to run each solution using the capacity and performance levels consistent with our test results. We found that the APEX Data Storage Services solution had a significantly lower monthly cost than the Amazon EBS io 2 Block Express solution.

Table 1 shows a breakdown of costs associated with the Amazon EBS solution we tested provisioned for a 730-hour month. Amazon EBS io2 Block Express has a rate of \$0.125 per GB per month for storage and \$0.065 per provisioned IOPS per month for up to 32,000 IOPS. To get the 16 Amazon EBS io2 Block Express volumes to perform comparably to the APEX Data Storage Services solution (~350K IOPS) would cost \$28,936.64 in total monthly storage costs—much less than purchasing a million-dollar storage solution outright, but still a significant amount for a monthly expenditure.⁴

By subscribing to on-premises Storage as-a-Service from Dell Technologies, a company could save up to 81.6 percent of these costs. Table 2 shows the breakdown in costs for the APEX Data Storage Services solution: A one-year subscription to APEX Data Storage Services capable of the same amount of work as the Amazon EBS io Block Express solution would cost a company just \$6,918.00 per month. A company that chooses a three-year subscription for the same solution would pay just \$5,322.00 per month. Figure 5 illustrates the total monthly cost of each solution.

Table 1: Breakdown of total monthly cost to run $16 \times 3TB$ Amazon EBS io 2 Block Express volumes, each with an average performance rate of 21,916 provisioned IOPS assuming a 730-hour month. Cost info current as of November 7, 2021. Source: Principled Technologies.

Amazon EBS io2 Block Express Storage cost analysis				
	Monthly rate	Per volume	Total usage (16 volumes)	Monthly cost
Storage	\$0.125/GB	3,072 GB	49,152 GB	\$6,144.00
Provisioned IOPS	\$0.065/IOPS	21,916 IOPS	350,656 IOPS	\$22,792.64
Total monthly cost				\$28,936.64

Table 2: Breakdown of total monthly cost for 1- and 3-year subscriptions to a Dell Technologies APEX Data Storage Services solution with 50TB of Balanced-tier block storage assuming a 730-hour month. Cost info current as of November 7, 2021. Source: Principled Technologies.

APEX cost analysis	
APEX Data Storage Services monthly cost (50TB)	
1 year subscription (Total monthly rate)	\$6,918.00
3 year subscription (Total monthly rate)	\$5,322.00



Monthly cost

Lower is better

Dell Technologies APEX Data Storage Services (with 3-year subscription) \$5,322.00

Amazon EBS io 2 Block Express

\$28,936.64

Figure 5: Comparison of the monthly costs assuming a 730-hour month for a 3-year, 50TB, Balanced-tier block storage plan for APEX Data Storage Services vs. 16 x 3TB Amazon EBS io 2 Block Express volumes at 21,916 IOPS each. Source:

Up to 81.6% saved monthly

How thin provisioning affects data charges

In our tests, Oracle databases consumed 48TB of storage space on each service. We subscribed to 50TB of base capacity with APEX Data Storage Services, which begs the question: How would billing work if you needed additional storage resources? With APEX Data Storage Services' thin provisioning, allocated but unused capacity does not affect billing. Thus, you wouldn't be charged an on-demand rate until you wrote more data to disk than your base capacity. Amazon EBS io2 Block Express, on the other thand, charges its on-demand rate for the entire capacity of each volume you provision, regardless of how much data you write to each volume. This difference could potentially have a significant effect on storage costs at scale.



Conclusion

Owning a comprehensive enterprise-class storage solution can be a multimillion-dollar investment that leads some companies to instead consider public cloud storage solutions. However, our tests with Dell Technologies APEX Data Storage Services demonstrate that companies can achieve an on-premises cloud storage solution that performs comparably to a similarly configured Amazon EBS io Block Express solution in an Oracle Database I/O generator workload for significantly less monthly cost. Whereas the Amazon solution we tested cost \$28,936.64 per month, one- and three-year subscriptions to a comparably performing APEX Data Storage Services solution cost \$6,918.00 and \$5,322.00 per month respectively.

Companies who would benefit from an on-premises storage solution could save considerable cost by subscribing to APEX Data Storage Services instead of paying for monthly public cloud resources. To learn more about Dell Technologies APEX Data Storage Services, visit www.DellTechnologies.com/APEX-Storage.

- 1 "APEX Data Storage Services," accessed November 4, 2021, https://www.delltechnologies.com/en-us/apex/data-storage-services.htm.
- 2 "Get up and running faster with Dell Technologies APEX Data Storage Services," accessed November 8, 2021, https://www.principledtechnologies.com/Dell/APEX-HPE-Greenlake-procurement-1121.pdf.
- 3 Kevin Closson, "Introducing SLOB The Simple Database I/O Testing Toolkit for Oracle Database," accessed November 4, 2021, https://kevinclosson.net/2012/02/06/introducing-slob-the-silly-little-oracle-benchmark/.
- 4 "Amazon EBS Provisioned IOPS Volume," accessed November 4, 2021, https://aws.amazon.com/ebs/provisioned-iops/.
- 5 Cost figures accurate as of November 4, 2021. To obtain this pricing information, we used the publicly available cost caclulator on the Dell Technologies APEX Data Storage Services website and configured 50TB of Block storage with Balanced performance for one- and three-year subscriptions: https://www.delltechnologies.com/en-us/apex/data-storage-services.htm.

The science behind the report

The following sections describe what we tested, how we tested, and what we found.

We concluded our hands-on testing on October 28, 2021. The results in this report reflect configurations that we finalized on October 22, 2021 or earlier. Unavoidably, these configurations may not represent the latest versions available when this report appears.

Our results

To learn more about how we have calculated the wins in this report, go to http://facts.pt/calculating-and-highlighting-wins. Unless we state otherwise, we have followed the rules and principles we outline in that document.

Table 3: Results of our testing. We compared a Dell Technologies APEX Data Storage Services solution configured with 50 TB of balanced-performance block storage to 16 3TB Amazon EBS io 2 Block Express volumes with a provisioned IOPS rate of 21,916.

	Dell Technologies APEX Data Storage Services	Amazon EBS io2 Block Express
Database sequential latency (ms)		
VM1	0.92	0.92
VM2	0.94	0.92
VM3	0.99	0.92
VM4	0.99	0.91
Total	0.96	0.92
Wait (await) latency (ms)		
VM1	1.36	3.35
VM2	1.40	3.40
VM3	1.39	3.49
VM4	1.34	3.54
Total	1.37	3.45
IOPS		
VM1	92,114	87,221
VM2	89,441	87,223
VM3	84,337	87,213
VM4	84,768	87,205
Total	350,661	348,862
Throughput (MB/s)		
VM1	741.30	702.60
VM2	720.50	702.60
VM3	678.60	702.60
VM4	682.10	702.50
Total	2,822.50	2,810.20

Table 4: Breakdown of total monthly cost to run 16 3TB Amazon EBS io 2 Block Express volumes, each with an average performance rate of 21,916 provisioned IOPS assuming a 730-hour month. Cost info current as of November 7, 2021.

Amazon EBS io2 Block Express monthly cost breakdown				
	Monthly rate	Per volume io2	Total usage	Monthly cost
Storage	\$0.125/GB	3,072 GB	49,152 GB	\$6,144.00
Provisioned IOPS	\$0.065/IOPS	21,916 IOPS	350,656 IOPS	\$22,792.64
Total monthly cost			\$28,936.64	

Table 5: Breakdown of total monthly cost for 1- and 3-year subscriptions to a Dell Technologies APEX Data Storage Services solution with 50TB of balanced-tier block storage assuming a 730-hour month. Cost info current as of November 7, 2021.

APEX Data Storage Services monthly cost (50TB balanced block storage)	
1 year subscription (Total monthly rate)	\$6,918.00
3 year subscription (Total monthly rate)	\$5,322.00

System configuration information

Table 6: Detailed configuration information for the servers under test.

BIOS name and version Dell 2.9.4 Non-default BIOS settings None Operating system name and version/build number Date of last OS updates/patches applied 10/25/21 Power management policy Balanced Processor Number of processors 1 Vendor and model Intel® Xeon® Gold 6248R Core count (per processor) 24 Core frequency (GHz) 3.00 Stepping B1 Memory module 1 Total memory in system (GB) Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 44 Vendor and model Dell Hynix HMA84GR7CJR4N-XN Size (GB) 3.20 Speed (MHz) 3.200 Speed running in the server (MHz) 3.200 Speed running in the server (MHz) 3.200 Speed running in the server (MHz) 3.200 Speed (MHz) 3.200 Speed running in the server (MHz) 3.200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	System configuration information	4 x Dell EMC PowerEdge R640
Operating system name and version/build number Date of last OS updates/patches applied 10/25/21 Power management policy Balanced Processor Number of processors 1 Vendor and model Core count (per processor) 24 Core frequency (GHz) 3.00 Stepping B1 Memory module 1 Total memory in system (GB) Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 44 Core (MHz) 3,200 Speed (MHz) 3,200 Memory modules 6 Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) Speed (MHz) 3,200 Speed (MHz) 3,200 Speed (MHz) Size (GB) 32 Type PC4-25600 Speed (MHz) Size (GB) 32 Speed (MHz) Size (GB) Dell HBA330 Mini Vendor and model Dell HBA330 Mini Cache size (GB) None	BIOS name and version	Dell 2.9.4
Date of last OS updates/patches applied Power management policy Balanced Processor Number of processors 1 Vendor and model Core count (per processor) Stepping B1 Memory module 1 Total memory in system (GB) Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) Speed (MHz) Speed running in the server (MHz) Size (GB) 32 Type PC4-25600 Speed running in the server (MHz) Size (GB) 32 Type PC4-25600 Speed (MHz) Size (GB) Dell HBA330 Mini Cache size (GB) None	Non-default BIOS settings	None
Processor Number of processors Vendor and model Core count (per processor) 1 Vendor and model Core frequency (GHz) Stepping B1 Memory module 1 Total memory in system (GB) Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) Speed (MHz) Speed running in the server (MHz) Size (GB) 32 Type PC4-25600 Speed running in the server (MHz) Size (GB) 32 Type PC4-25600 Speed (MHz) Size (GB) 32 Type PC4-25600 Speed (MHz) Size (GB) 32 Type PC4-25600 Speed (MHz) Size (GB) Dell HBA330 Mini Cache size (GB) None	Operating system name and version/build number	VMware ESXi®, 7.0.2, 17867351
Processor Number of processors 1 Vendor and model Intel® Xeon® Gold 6248R Core count (per processor) 24 Core frequency (GHz) 3.00 Stepping B1 Memory module 1 Total memory in system (GB) Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Number of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Date of last OS updates/patches applied	10/25/21
Number of processors 1 Vendor and model Intel® Xeon® Gold 6248R Core count (per processor) 24 Core frequency (GHz) 3.00 Stepping B1 Memory module 1 Total memory in system (GB) Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Number of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Power management policy	Balanced
Vendor and model Intel® Xeon® Gold 6248R Core count (per processor) 24 Core frequency (GHz) 3.00 Stepping B1 Memory module 1 Total memory in system (GB) Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Wendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Processor	
Core count (per processor) 24 Core frequency (GHz) 3.00 Stepping B1 Memory module 1	Number of processors	1
Core frequency (GHz) 3.00 Stepping B1 Memory module 1 576 Total memory in system (GB) 576 Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Wendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Vendor and model	Intel® Xeon® Gold 6248R
Stepping B1 Memory module 1 576 Total memory in system (GB) 576 Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Wendor and model Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Core count (per processor)	24
Memory module 1 Total memory in system (GB) 576 Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Number of memory modules 6 Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Speed (MHz) 3,200 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Core frequency (GHz)	3.00
Total memory in system (GB) 576 Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Winder of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Stepping	В1
Number of memory modules 6 Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Number of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Memory module 1	
Vendor and model Hynix HMAA8GR7CJR4N-XN Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Number of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Total memory in system (GB)	576
Size (GB) 64 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 6 Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Number of memory modules	6
Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Memory module 2 Number of memory modules 6 Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Vendor and model	Hynix HMAA8GR7CJR4N-XN
Speed (MHz) Speed running in the server (MHz) Memory module 2 Number of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) Speed running in the server (MHz) Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Size (GB)	64
Speed running in the server (MHz) Memory module 2 Number of memory modules 6 Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Туре	PC4-25600
Memory module 2 Number of memory modules Vendor and model Hynix HMA84GR7CJR4N-XN Size (GB) 32 Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB)	Speed (MHz)	3,200
Number of memory modules6Vendor and modelHynix HMA84GR7CJR4N-XNSize (GB)32TypePC4-25600Speed (MHz)3,200Speed running in the server (MHz)3,200Storage controllerVendor and modelDell HBA330 MiniCache size (GB)None	Speed running in the server (MHz)	3,200
Vendor and modelHynix HMA84GR7CJR4N-XNSize (GB)32TypePC4-25600Speed (MHz)3,200Speed running in the server (MHz)3,200Storage controllerVendor and modelDell HBA330 MiniCache size (GB)None	Memory module 2	
Size (GB) Type PC4-25600 Speed (MHz) Speed running in the server (MHz) Storage controller Vendor and model Cache size (GB) Dell HBA330 Mini None	Number of memory modules	6
Type PC4-25600 Speed (MHz) 3,200 Speed running in the server (MHz) 3,200 Storage controller Vendor and model Dell HBA330 Mini Cache size (GB) None	Vendor and model	Hynix HMA84GR7CJR4N-XN
Speed (MHz) Speed running in the server (MHz) Storage controller Vendor and model Cache size (GB) Storage Controller Dell HBA330 Mini None	Size (GB)	32
Speed running in the server (MHz) Storage controller Vendor and model Cache size (GB) Dell HBA330 Mini None	Туре	PC4-25600
Storage controller Vendor and model Cache size (GB) Dell HBA330 Mini None	Speed (MHz)	3,200
Vendor and model Cache size (GB) Dell HBA330 Mini None	Speed running in the server (MHz)	3,200
Cache size (GB) None	Storage controller	
	Vendor and model	Dell HBA330 Mini
Firmware version 2.5.13.3024	Cache size (GB)	None
	Firmware version	2.5.13.3024

System configuration information	4 x Dell EMC PowerEdge R640	
Local storage	·	
Number of drives	2	
Drive vendor and model	Micron MTFDDAV240TDU	
Drive size (GB)	240	
Drive information (speed, interface, type)	SSD, 6Gb SATA, HDD	
Network adapter		
Vendor and model	Mellanox ConnectX-4 LX	
Number and type of ports	4 x 25GbE	
Cooling fans		
Vendor and model	Dell	
Number of cooling fans	5	
Power supplies		
Vendor and model	Dell 0CMPGMA03	
Number of power supplies	2	
Wattage of each (W)	1,100	

Table 7: Detailed configuration information for the storage solution.

Storage configuration information	Dell Technologies APEX Data Storage Services
Controller firmware revision	1.0
Performance tier	Balanced
Number of storage controllers	2
Number of storage shelves	1
Number of drives per shelf	12
Drive vendor and model number	Dell 005053081
Drive size (GB)	7,000
Drive information (speed, interface, type)	NVMe™ SSD

Table 8: Detailed configuration information for the server under test.

System configuration information	48vCPU Cascade Lake VM
Tested by	Principled Technologies
Test date	10/27/2021
CSP / Region	East US 2
Workload & version	Silly Little Oracle® Benchmark (SLOB) 2.5.4.0
WL specific parameters	24 Users
Iterations and result choice	3 runs, median
Instance type and size	r5b.12xlarge
Number of instances	4
Operating system name and version/build number	Oracle Linux 7.9
Date of last OS updates/patches applied	10/27/2021
Local storage	
OS	
Number of drives	1
Drive size (GB)	100
Drive information (speed, interface, type)	gp2 Standard SSD (180 IOPS)
Oracle	
Number of drives	4
Drive size (GB)	3,072
Drive information (speed, interface, type)	io2 BE (21,916 IOPS)

How we tested

Creating the VM on AWS

- Log into AWS and navigate to the AWS Management Console.
- 2. Click EC2.
- 3. Click Launch instance. In the dropdown menu, to open the Launch Instance wizard, click Launch Instance.
- 4. In the search window, type Oracle Linux 7 update 9 for x86 64 HVM and press Enter.
- On the Choose AMI tab, next to Oracle Linux 7 update 9 for x86_64 HVM, click the Select button.
- On the Choose Instance Type tab, select r5b.12xlarge, and click Next: Configure Instance Details.
- 7. On the Configure Instance tab, set the following:
 - Number of instances: 4
 - Purchasing option: Leave unchecked
 - Network: Default VPC
 - Subnet: [Choose your region]
- Click Next: Add Storage.
- On the Add Storage tab, set the following:
 - Size: 3,072 GB
 - Volume Type: io2
- 10. Click Next: Add Tags.

- Delete on Termination: Checked

• Auto-assign Public IP: Enable.

• Capacity Reservation: Open

• Placement Group: [Leave unchecked]

- Domain join directory: No Directory
- IOPs limit: 21,916
- Encryption: Not Encrypted

• Shutdown behavior: Stop

• IAM role: None

- 11. On the Add Tags tab, set any tags, and click Next: Configure Security Group.
- 12. On the Configure Security Group tab, keep defaults and click Review and Launch.
- 13. On the Review Tab, click Launch.
- 14. Choose the appropriate option for the key pair, then click Launch Instances.

Creating the RDM LUNs on APEX

- Log into the APEX Block Storage Service management UI.
- From the APEX Block Storage Service management UI, select the Storage dropdown menu, and click Volumes.
- Under Volumes, click Create.
- For Properties, provide a name for the volume, set the Quantity to 16, set the size to 3 TB, and click Next.
- For Host Mappings, select all four hosts, and click Next.
- Review the Summary, and click Create.

Creating the VM for the APEX environment

- In VMware vCenter, navigate to Virtual Machines.
- To create a new VM, click the icon. 2.
- Leave Create a new virtual machine selected, and click Next.
- 4. Enter a name for the virtual machine, and click Next.
- 5. Place the VM on the desired host with available CPUs, and click Next.
- Select the datastore to host the VM, and click Next.
- Select the appropriate guest OS, and click Next.
- In the Customize Hardware section, use the following settings:
 - Set the vCPU count to 48.
- For OS, add 1x 100GB VMDK.
- Set the Memory to 384GB.
- Add 4x 3TB RDM LUN.
- 9. Create three additional VMware Paravirtual SCSI controllers, and assign each RDM to a different controller.
- 10. Attach the installation ISO to the CD/DVD drive.
- 11. Click Next.
- 12. Click Finish.

Installing Oracle Linux 7.9

- 1. Boot to the Oracle Linux 7.9 installation media.
- 2. Select Install or upgrade an existing system.
- 3. Choose English, and click Continue.
- 4. Under Installation Destination, to install the OS, select the desired disk.
- 5. Under Other Storage Options, select I will configure partitioning, and click Done.
- 6. Select Click here to create them automatically.
- 7. Expand the swap partition to 20 GB.
- 8. Assign all remaining free space to the / partition.
- 9. Click Done.
- 10. Click Accept Changes.
- 11. Select kdump.
- 12. Uncheck Enable kdump, and click Done.
- 13. Select Network & Hostname.
- 14. Enter the desired hostname for the system.
- 15. Turn on the desired network ports, and click Configure.
- 16. On the General tab, select Automatically connect to this network when it is available.
- 17. On the IPv4 Settings tab, choose the dropdown named Method, and select Manual.
- 18. Under Addresses, click Add, and enter the static IP information for the server.
- 19. Enter the DNS information.
- 20. Click Save, and click Done.
- 21. Click Software Selection
- 22. Choose the Base Environment of Minimal.
- 23. Click Done.
- 24. Click Begin Installation.
- 25. Select Root Password.
- 26. Enter the desired root password, and click Done.
- 27. When the installation completes, to restart the server, select Reboot.

Configuring Oracle Linux 7.9

- 1. Log onto the server as root.
- 2. Change the default kernel:

```
grub2-set-default 1
grub2-mkconfig -o /boot/grub2/grub.cfg
```

3. Disable the firewall:

```
systemctl stop firewalld
systemctl disable firewalld
```

4. Disable auditd:

```
systemctl disable auditd
```

5. Disable SELinux:

```
vi /etc/selinux/config
SELINUX=disabled
```

6. Use visudo to add the following to the end of /etc/sudoers:

```
username ALL=(ALL) NOPASSWD:ALL
```

- 7. From the following URL, download and install OracleASM support and lib packages: https://access.redhat.com/solutions/315643.
- 8. Navigate to the directory to which you downloaded the OracleASM packages, and install them:

```
yum -y localinstall oracleasm*
```

9. Install the Oracle Database 19c pre-install:

```
yum -y install oracle-database-preinstall-19c xhost xorg-x11-apps kmod-oracleasm
```

10. Update the host:

```
yum -y update
```

- 11. Using passwd, create passwords for the oracle account.
- 12. Using fdisk, create a partition on all disks.
- 13. Edit /etc/sysconfig/oracleasm by changing the following:

```
ORACLEASM_ENABLED=true
ORACLEASM_UID=oracle
ORACLEASM_GID=oinstall
```

14. Initialize oracleasm:

```
oracleasm init
oracleasm createdisk DATA1 /dev/sdb1
oracleasm createdisk DATA2 /dev/sdc1
oracleasm createdisk DATA3 /dev/sdd1
oracleasm createdisk DATA4 /dev/sde1
```

15. Reboot the host.

Preparing the Linux for Oracle Database 19c installation

- 1. Log onto the server as root.
- 2. Create the following directories, and assign the following permissions:

```
mkdir -p /u01/app/oracle/product/19.0.0/dbhome_1
mkdir -p /u01/app/grid
mkdir -p /u02/oradata
chown -R oracle:oinstall /u01 /u02
chmod -R 775 /u01 /u02
mkdir /home/oracle/scripts
```

3. Create the environment variable script setEnv.sh:

```
export TMP=/tmp
export TMPDIR=$TMP
export ORACLE HOSTNAME=localhost.localdomain
export ORACLE UNQNAME=orcl
export ORACLE BASE=/u01/app/oracle
export GRID HOME=/u01/app/19.0.0/grid
export DB HOME=$ORACLE BASE/product/19.0.0/dbhome 1
export ORACLE HOME=$DB HOME
export ORACLE SID=orcl
export ORACLE_TERM=xterm
export BASE PATH=/usr/sbin:$PATH
export PATH=$ORACLE_HOME/bin:$BASE_PATH
export LD LIBRARY PATH=$ORACLE HOME/lib:/lib:/usr/lib
export CLASSPATH=$ORACLE HOME/JRE:$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib
alias grid env='. /home/oracle/grid env'
alias db env='. /home/oracle/db env'
```

4. At the end of the oracle user's bash profile, reference setEnv.sh:

```
echo ". /home/oracle/scripts/setEnv.sh" >> /home/oracle/.bash_profile
```

5. In the oracle home folder, create the following files:

```
grid_env
export ORACLE_SID=+ASM
export ORACLE_HOME=$GRID_HOME
export PATH=$ORACLE_HOME/bin:$BASE_PATH
export LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib
export CLASSPATH=$ORACLE_HOME/JRE:$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib
db_env
export ORACLE_SID=orcl
export PATH=$ORACLE_HOME/bin:$BASE_PATH
export LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib
export CLASSPATH=$ORACLE_HOME/JRE:$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib
```

Installing Oracle Grid 19c

If you are connecting to the test environment via SSH, your SSH client must have X11 forwarding enabled in order to successfully complete this installation. In our setup, we used the PuTTY SSH client to log into the VMs. We used XMing to configure PuTTY with X11 forwarding.

- 1. Log onto the server as oracle.
- 2. To set the Oracle grid environment, type grid env
- Change directory to \$ORACLE HOME
- 4. Extract the Oracle Grid 19c installation files:

```
unzip -oq /media/directory/LINUX.X64 193000 grid home.zip
```

5. Install dependency:

```
rpm -iv /u01/app/grid/cv/rpm/cvuqdisk-1.0.10-1.rpm
```

6. Run the Oracle Grid 19c installer:

```
./gridSetup.sh
```

- 7. At the Select Installation Option screen, select Install and Configure Grid Infrastructure for a Standalone Server, and click Next.
- 8. At the Create ASM Disk Group screen, choose the Disk Group Name (DATA), and change redundancy to External.
- 9. Change Allocation Unit Size to 8 MB.
- 10. Change Disk Discovery Path to the following:

```
/dev/oracleasm/disks
```

- 11. Select the DATA disks, and click Next.
- 12. At the Specify ASM Password screen, choose Use same password for these accounts, type the passwords for the ASM users, and click Next.
- 13. At the Management Options screen, click Next.
- 14. Leave the default Operating System Groups, and click Next.
- 15. Leave the default installation, and click Next.
- 16. Leave the default inventory location, and click Next.
- 17. Under Root script execution, leave the defaults, and click Next.
- 18. At the Prerequisite Checks screen, make sure that there are no errors.
- 19. At the Summary screen, verify that everything is correct. To install Oracle Grid Infrastructure, click Finish.
- 20. The installation will prompt you to execute two configuration scripts as root. Follow the instructions to run the scripts.
- 21. At the Finish screen, click Close.

Installing Oracle Database 19c

- 1. Log into the server as oracle.
- 2. To set the Oracle grid environment, type db env
- 3. Change directory to \$ORACLE HOME
- 4. Extract the Oracle Database 19c installation files:

```
unzip -oq /media/directory/LINUX.X64 193000 db home.zip
```

5. Run the Oracle Database 19c installer:

```
./runInstaller
```

- 6. Wait for the GUI installer to load.
- 7. At tje Select Configuration Option screen, select Install software only, and click Next.
- 8. At the Database Installation Options screen, click Next.
- 9. At the Database Edition screen, leave Enterprise Edition selected, and click Next.
- 10. At the Installation Location screen, click Next.
- 11. At the Operating System Groups screen, click Next.
- 12. At the Root script execution screen, click Next.
- 13. Allow the prerequisite checker to complete.
- 14. If you are required to make any adjustments, follow the instructions on screen.
- 15. At the Summary screen click Install.
- 16. Once the installer completes, click Close.

Creating and configuring the database

- 1. To open the Database configuration assistant, type dbca and press Enter.
- 2. At the Database Operation screen, select Create Database, and click Next.
- 3. Under Creation Mode select Advanced configuration, and click Next.
- 4. At the Deployment Type screen, select General Purpose or Transaction Processing, and click Next.
- 5. At the Database Identification screen, uncheck Create as Container database, and click Next.
- 6. At the storage option screen, select Use following for the database storage attributes, and click Next.
- 7. At the Fast Recovery Option screen, check Specify Fast Recovery Location, and click Next.
- 8. At the Network Configuration screen, select the listener, and click Next.
- 9. At the Data Vault Option screen, click Next.
- 10. At the Configuration Options screen, set the SGA size to 8 GB and the PGA size to 8 GB. Click Next.
- 11. At the Management Options screen, click Next.
- 12. At the User Credentials screen, select Use the same administrative password for all accounts. Enter and confirm manager as the password, and click Next.
- 13. At the Creation Options, select Create Database, and click Next.
- 14. At the summary screen, click Finish.
- 15. Close the Database Configuration Assistant.
- 16. Alter the log files and tablespaces as follows:

```
sqlplus '/ as sysdba'
ALTER DATABASE ADD LOGFILE GROUP 11 ( '/tmp/temp1.log' ) SIZE 50M;
ALTER DATABASE ADD LOGFILE GROUP 12 ( '/tmp/temp2.log' ) SIZE 50M;

ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM CHECKPOINT;
ALTER DATABASE DROP LOGFILE GROUP 1;
ALTER DATABASE DROP LOGFILE GROUP 2;
ALTER DATABASE DROP LOGFILE GROUP 3;
ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM CHECKPOINT;
ALTER SYSTEM SET "_disk_sector_size_override"=TRUE SCOPE=BOTH;
ALTER DATABASE ADD LOGFILE GROUP 1 ( '+DATA/logfile1.log' ) SIZE 8G BLOCKSIZE 4K;
```

```
ALTER DATABASE ADD LOGFILE GROUP 2 ( '+DATA/logfile2.log' ) SIZE 8G BLOCKSIZE 4K;
ALTER DATABASE ADD LOGFILE GROUP 3 ( '+DATA/logfile3.log' ) SIZE 8G BLOCKSIZE 4K;
ALTER DATABASE ADD LOGFILE GROUP 4 ( '+DATA/logfile4.log' ) SIZE 8G BLOCKSIZE 4K;
ALTER DATABASE ADD LOGFILE GROUP 5 ( '+DATA/logfile5.log' ) SIZE 8G BLOCKSIZE 4K;
ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM SWITCH LOGFILE;
ALTER SYSTEM CHECKPOINT;
ALTER DATABASE DROP LOGFILE GROUP 11;
ALTER DATABASE DROP LOGFILE GROUP 12;
SHUTDOWN;
STARTUP;
HOST rm -f /tmp/temp*.log;
CREATE BIGFILE TABLESPACE SLOB DATAFILE '+DATA/SLOB.dbf' SIZE 3000G AUTOEXTEND ON NEXT 1G BLOCKSIZE 8K;
```

Installing SLOB and populating the database

- 1. From the following URL, download the SLOB kit: http://kevinclosson.net/slob/.
- 2. Copy and untar the kit's files to /home/oracle/SLOB.
- 3. Edit the slob.conf file to match the section below titled Benchmark parameters.
- 4. To switch to the database environment, type db_env
- 5. Enter SQLPlus:

```
sqlplus '/ as sysdba'
```

6. Start the database:

```
startup
```

- 7. Once the database is up, type exit
- 8. Start the population process:

```
./setup.sh SLOB 24
```

- 9. When the setup is complete, the database is populated.
- 10. Create the wait_kit:

```
cd wait_kit
make all
cd ..
```

Running SLOB

- 1. Log in as the oracle user.
- 2. Start the database.
- 3. Navigate to /home/oracle/SLOB.
- 4. Start the test:

```
./runit.sh 24
```

- 5. Once the test is finished, collect the results.
- 6. Repeat the test twice more for a total of three test runs.

Benchmark parameters

```
#### SLOB 2.5.4.0 slob.conf
UPDATE PCT=30
SCAN PCT=0
RUN TIME=1800
WORK_LOOP=0
SCALE=48G
SCAN TABLE SZ=10M
WORK UNIT=64
REDO STRESS=LITE
LOAD_PARALLEL_DEGREE=1
THREADS PER SCHEMA=1
DATABASE STATISTICS TYPE=awr # Permitted values: [statspack|awr]
#### Settings for SQL*Net connectivity:
#### Uncomment the following if needed:
#ADMIN_SQLNET_SERVICE="if needed, replace with a valid thsnames.ora service"
#SQLNET SERVICE BASE="if needed, replace with a valid tnsnames.ora service"
#SQLNET SERVICE MAX="if needed, replace with a non-zero integer"
#### Note: Admin connections to the instance are, by default, made as SYSTEM
          with the default password of "manager". If you wish to use another
          privileged account (as would be the case with most DBaaS), then
          change DBA PRIV USER and SYSDBA PASSWD accordingly.
#### Uncomment the following if needed:
#DBA PRIV USER="system"
#SYSDBA PASSWD="manager"
##########################
#### Advanced settings:
#### The following are Hot Spot related parameters.
#### By default Hot Spot functionality is disabled (DO HOTSPOT=FALSE).
DO HOTSPOT=FALSE
HOTSPOT MB=8
HOTSPOT OFFSET MB=16
HOTSPOT FREQUENCY=3
#### The following controls operations on Hot Schema
#### Default Value: 0. Default setting disables Hot Schema
HOT SCHEMA FREQUENCY=0
\#\#\# The following parameters control think time between SLOB
#### operations (SQL Executions).
\#\#\# Setting the frequency to 0 disables think time.
THINK TM FREQUENCY=0
THINK TM MIN=.1
THINK TM MAX=.1
```

Oracle SPFILE parameters

```
orcl.__data_transfer_cache_size=0
orcl.__db_cache size=6996099072
orcl.__inmemory_ext_roarea=0
orcl. inmemory ext rwarea=0
orcl. java pool size=0
orcl. large pool size=83886080
orcl. oracle base='/u01/app/oracle'#ORACLE BASE set from environment
orcl.__pga_aggregate_target=8589934592
orcl.__sga_target=8589934592
orcl. shared io pool size=134217728
orcl.__shared_pool_size=1342177280
orcl. _streams_pool_size=0
orcl. unified pga pool size=0
*. disk sector size override=TRUE
*.audit file dest='/u01/app/oracle/admin/orcl/adump'
*.audit trail='db'
*.compatible='19.0.0'
*.control files='+DATA/ORCL/CONTROLFILE/current.262.1086873187','+DATA/ORCL/CONTROLFILE/
   current.261.1086873187'
*.db block size=8192
*.db create file dest='+DATA'
*.db name='orcl'
*.db recovery file dest='+DATA'
*.db recovery file dest size=8256m
*.diagnostic dest='/u01/app/oracle'
*.dispatchers='(PROTOCOL=TCP) (SERVICE=orclXDB)'
*.local listener='LISTENER ORCL'
*.nls language='AMERICAN'
*.nls territory='AMERICA'
*.open cursors=300
*.pga aggregate target=8g
*.processes=3840
*.remote login passwordfile='EXCLUSIVE'
*.sga target=8g
*.undo tablespace='UNDOTBS1'
```

This project was commissioned by Dell Technologies.



Facts matter.°

Principled Technologies is a registered trademark of Principled Technologies, Inc. All other product names are the trademarks of their respective owners.

DISCLAIMER OF WARRANTIES; LIMITATION OF LIABILITY:

Principled Technologies, Inc. has made reasonable efforts to ensure the accuracy and validity of its testing, however, Principled Technologies, Inc. specifically disclaims any warranty, expressed or implied, relating to the test results and analysis, their accuracy, completeness or quality, including any implied warranty of fitness for any particular purpose. All persons or entities relying on the results of any testing do so at their own risk, and agree that Principled Technologies, Inc., its employees and its subcontractors shall have no liability whatsoever from any claim of loss or damage on account of any alleged error or defect in any testing procedure or result.

In no event shall Principled Technologies, Inc. be liable for indirect, special, incidental, or consequential damages in connection with its testing, even if advised of the possibility of such damages. In no event shall Principled Technologies, Inc.'s liability, including for direct damages, exceed the amounts paid in connection with Principled Technologies, Inc.'s testing. Customer's sole and exclusive remedies are as set forth herein.