

<u>Help</u> shengtatng ✓

<u>Course</u> <u>Progress</u> <u>Dates</u> <u>Discussion</u> <u>Notes</u> <u>Calendar</u>



()



Exercise 1

□ Bookmark this page

Lecture Sequence due Dec 15, 2022 07:30 +08 Completed

Exercise 1

10.0/10.0 points (graded)

Here is the <u>lecture from 6.00.1x on generators</u>. Additionally, you can also take a look at Chapter 8.3 in the textbook.

For the following problem, consider the following way to write a power set generator. The number of possible combinations to put n items into one bag is 2^n . Here, items is a Python list. If need be, also check out the <u>docs on bitwise operators</u> (<<, >>, &, |, \sim , $^\circ$).

As above, suppose we have a generator that returns every combination of objects in one bag. We can represent this as a list of 1s and 0s denoting whether each item is in the bag or not.

Write a generator that returns every arrangement of items such that each is in one or none of two different bags. Each combination should be given as a tuple of two lists, the first being the items in bag1, and the second being the items in bag2.

```
def yieldAllCombos(items):
    """
    Generates all combinations of N items into two bags, whereby each
    item is in one or zero bags.

    Yields a tuple, (bag1, bag2), where each bag is represented as
    a list of which item(s) are in each bag.
"""
```


Note this generator should be pretty similar to the powerSet generator above.

We mentioned that the number of possible combinations for N items into one bag is 2^n . How many possible combinations exist when there are two bags? Think about this for a few minutes, then click the following hint to confirm if your guess is correct. Remember that a given item can only be in bag1, bag2, or neither bag -- it is not possible for an item to be present in both bags!

```
How many possible combinations exist for N items into two bags?
 1 def yieldAllCombos(items):
 3
          Generates all combinations of N items into two bags, whereby each
 4
           item is in one or zero bags.
 5
 6
           Yields a tuple, (bag1, bag2), where each bag is represented as a list
 7
           of which item(s) are in each bag.
 8
      # Your code here
 9
10
      N = len(items)
11
       # Enumerate the 3**N possible combinations
12
       for i in range(3**N):
13
           bag1 = []
14
           bag2 = []
15
           for j in range(N):
```

Press ESC then TAB or click outside of the code editor to exit

Correct





edX

About

Affiliates

edX for Business

Open edX

<u>Careers</u>

News

Legal

Terms of Service & Honor Code

Privacy Policy

Accessibility Policy

Trademark Policy

<u>Sitemap</u>

Connect

<u>Blog</u>

Contact Us

Help Center

<u>Security</u>

Media Kit















© 2022 edX LLC. All rights reserved.

深圳市恒宇博科技有限公司 <u>粤ICP备17044299号-2</u>