



< Previous



Next >

Problem 3

Bookmark this page

Problem 3

0.7692307692307693/1 point (ungraded)

For this problem, the graders will use our implementation of the `Message` and `PlaintextMessage` classes, so don't worry if you did not get the previous parts correct.

Given an encrypted message, if you know the shift used to encode the message, decoding it is trivial. If `message` is the encrypted message, and `s` is the shift used to encrypt the message, then `apply_shift(message, 26-s)` gives you the original plaintext message. Do you see why?

The problem, of course, is that you don't know the shift. But our encryption method only has 26 distinct possible values for the shift! We know English is the main language of these emails, so if we can write a program that tries each shift and maximizes the number of English words in the decoded message, we can decrypt their cipher! A simple indication of whether or not the correct shift has been found is if most of the words obtained after a shift are valid words. Note that this only means that most of the words obtained are actual words. It is possible to have a message that can be decoded by two separate shifts into different sets of words. While there are various strategies for deciding between ambiguous decryptions, for this problem we are only looking for a simple solution.

Fill in the methods in the class `CiphertextMessage` according to the specifications in `ps6.py`. The methods you should fill in are:

- `__init__(self, text)`: Use the parent class constructor to make your code more concise.
- `decrypt_message(self)`: You may find the helper function `is_word(wordlist, word)` and the string `method` `split()` useful. Note that `is_word` will ignore punctuation and other special characters when considering whether a word is valid.

Hints

[Using string.split](#)

Paste your implementation of the entire `CiphertextMessage` class in the box below.

```
1 class CiphertextMessage(Message):
2     def __init__(self, text):
3         '''
4         Initializes a CiphertextMessage object
5
6         text (string): the message's text
7         a CiphertextMessage object has two attributes:
8             self.message_text (string, determined by input text)
9             self.valid_words (list, determined using helper function load_words)
10        '''
11        self.message_text = text
12        self.valid_words = load_words(WORDLIST_FILENAME)
13
14
15    def decrypt_message(self):
```

Press ESC then TAB or click outside of the code editor to exit

Incorrect

Test results

INCORRECT

[See full output](#)

[See full output](#)

Submit

PSET5: Problem 3

Topic: Sandbox / PSET5: Problem 3

Hide Discussion

Add a Post

Show all posts



by recent activity



There are no posts in this topic yet.



< Previous

Next >

© All Rights Reserved



edX

[About](#)

[Affiliates](#)

[edX for Business](#)

[Open edX](#)

[Careers](#)

[News](#)

Legal

[Terms of Service & Honor Code](#)

[Privacy Policy](#)

[Accessibility Policy](#)

[Trademark Policy](#)

[Sitemap](#)

Connect

[Blog](#)

[Contact Us](#)

[Help Center](#)

[Media Kit](#)



© 2022 edX LLC. All rights reserved.

深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)

Hide Notes

