



Exercise 4

Bookmark this page

Exercise 4

1/1 point (graded)

ESTIMATED TIME TO COMPLETE: 5 minutes

Here is some code for linear search that uses the fact that a set of elements is sorted in increasing order:

```
def search(L, e):
    for i in range(len(L)):
        if L[i] == e:
            return True
        if L[i] > e:
            return False
    return False
```

Consider the following code, which is an alternative version of `search`.

```
def search3(L, e):
    if L[0] == e:
        return True
    elif L[0] > e:
        return False
    else:
        return search3(L[1:], e)
```

Which of the following statements is correct? You may assume that each function is tested with a list `L` whose elements are sorted in increasing order. For simplicity, assume `L` is a list of integers.

- ☐ `search` and `search3` return the same answers.
- ☐ `search` and `search3` return the same answers provided `L` is non-empty.
- ☒ `search` and `search3` return the same answers provided `L` is non-empty and `e` is in `L`.
- ☐ `search` and `search3` do not return the same answers.
- ☐ `search` and `search3` return the same answers for lists of length 0 and 1 only.



Submit

Exercise 4

Topic: Lecture 12 / Exercise 4

Hide Discussion

Add a Post

Show all posts

by recent activity

? SPOILER

SPOILER search(L = [1,2,3,4], 0) == search3(L = [1,2,3,4], 0) # AND search(L = [1,3,4], 2) == search3(L = [1,3,4], 2) Given the ...

3

< Previous

Next >

Hide Notes



edX

- [About](#)
- [Affiliates](#)
- [edX for Business](#)
- [Open edX](#)
- [Careers](#)
- [News](#)

Legal

- [Terms of Service & Honor Code](#)
- [Privacy Policy](#)
- [Accessibility Policy](#)
- [Trademark Policy](#)
- [Sitemap](#)

Connect

- [Blog](#)
- [Contact Us](#)
- [Help Center](#)
- [Media Kit](#)

