



Exercise 1

Bookmark this page

Exercise 1

11/11 points (graded)

ESTIMATED TIME TO COMPLETE: 12 minutes

In this problem, we'll examine how indirection works. Consider the following definitions:

```
a = [1, 2, 3, 4, 0]
b = [3, 0, 2, 4, 1]
c = [3, 2, 4, 1, 5]
```

1. What is the value of the following expressions? If you think there will be an error, please type in 'error' (without quotes) in the input box.

1. `a[0]`



2. `b[1]`



3. `a[a[1]]`



4. `b[b[2]]`



5. `a[b[2]]`



6. `c[a[b[3]]]`



7. `a[c[a[b[0]]]]`



8. `a[c[a[b[3]]]]`



2. Assume we have defined the following function:

```
def foo(L):
    val = L[0]
    while (True):
        val = L[val]
```

Which of the following statement(s) will result in an infinite loop?

☒ foo(a)

☒ foo(b)

☐ foo(c)



3. Consider the following code:

```
num = ???  
L = [5, 0, 2, 4, 6, 3, 1]  
val = 0  
for i in range(0, num):  
    val = L[L[val]]  
  
print(val)
```

1. What is the smallest value that `num` can be such that the number 3 is printed?

☐ 0

☒ 1

☐ 3

☐ 5

☐ Impossible



2. Now, we redefine `L` to be:

`L = [2, 0, 1, 5, 3, 4]`

What is the smallest value that `num` can be such that the number 3 is printed?

☐ 0

☐ 3

☐ 5

☒ Impossible



Submit

Exercise 1

Topic: Lecture 12 / Exercise 1

Hide Discussion

A Hide Notes

Show all posts

by recent activity

There are no posts in this topic yet.

✕

< Previous

Next >

© All Rights Reserved



edX

[About](#)

[Affiliates](#)

[edX for Business](#)

[Open edX](#)

[Careers](#)

[News](#)

Legal

[Terms of Service & Honor Code](#)

[Privacy Policy](#)

[Accessibility Policy](#)

[Trademark Policy](#)

[Sitemap](#)

Connect

[Blog](#)

[Contact Us](#)

[Help Center](#)

[Media Kit](#)



© 2022 edX LLC. All rights reserved.

深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)

Hide Notes