



< Previous



Exercise 1

🔖 Bookmark this page



Hide Notes

Exercise 1

5/5 points (graded)

ESTIMATED TIME TO COMPLETE: 10 minutes

Here is some code from lecture:

```
def linearSearch(L, x):  
    for e in L:  
        if e == x:  
            return True  
    return False
```

Choose which of the following inputs to `linearSearch` would give the best case, average case, or worst case run time.

1. Best Case Run Time

☐ `linearSearch([14, 15, 6, 27, 13, 16, 25, 11, 7], 15)`

☐ `linearSearch([21, 1, 25, 22, 30, 13, 7, 24, 12], 24)`

☒ `linearSearch([20, 10, 1, 7, 4, 22, 25, 12, 31], 20)`

☐ `linearSearch([9, 3, 12, 24, 7, 8, 23, 11, 19], 8)`

☐ `linearSearch([4, 12, 20, 17, 9, 14, 7, 24, 6], 7)`

☐ `linearSearch([13, 9, 22, 3, 10, 17, 11, 2, 12], 26)`



2. Worst Case Run Time

☐ `linearSearch([14, 15, 6, 27, 13, 16, 25, 11, 7], 15)`

☐ `linearSearch([21, 1, 25, 22, 30, 13, 7, 24, 12], 24)`

☐ `linearSearch([20, 10, 1, 7, 4, 22, 25, 12, 31], 20)`

☐ `linearSearch([9, 3, 12, 24, 7, 8, 23, 11, 19], 8)`

☐ `linearSearch([4, 12, 20, 17, 9, 14, 7, 24, 6], 7)`

☒ `linearSearch([13, 9, 22, 3, 10, 17, 11, 2, 12], 26)`



3. Average Case Run Time

☐ `linearSearch([14, 15, 6, 27, 13, 16, 25, 11, 7], 15)`

☐ `linearSearch([21, 1, 25, 22, 30, 13, 7, 24, 12], 24)`

☐ `linearSearch([20, 10, 1, 7, 4, 22, 25, 12, 31], 20)`

☒ `linearSearch([9, 3, 12, 24, 7, 8, 23, 11, 19], 8)`

linearSearch([4, 12, 20, 17, 9, 14, 7, 24, 6], 7)

linearSearch([13, 9, 22, 3, 10, 17, 11, 2, 12], 26)

4. What is the number of steps it will take to run `linearSearch` in the best case? Express your answer in terms of n , the number of elements in the list `L`.

Indicate addition and multiplication explicitly, with `+` and `*` symbols. Indicate exponentiation with the caret (`^`) symbol.

1

1

5. What is the number of steps it will take to run `linearSearch` in the worst case? Express your answer in terms of n , the number of elements in the list `L`.

Indicate addition and multiplication explicitly, with `+` and `*` symbols. Indicate exponentiation with the caret (`^`) symbol.

2*n+1

$2 \cdot n + 1$

Reminder: You do not lose points for trying a problem multiple times, nor do you lose points if you hit "Show Answer". If this problem has you stumped after you've tried it a few times, feel free to reveal the solution.

Click the "Reset" button to clear your answers.

Submit

Exercise 1

Hide Discussion

Topic: Lecture 11 / Exercise 1

Add a Post

Show all posts	by recent activity
<div>Professor Grimson doesn't count returns in lecture</div>	2
<div>? is the definition of the function counted as one operation? just what the title says</div>	2
<div>✓ Spoiler. Why does the worst case $2 \cdot n + 1$ not $2 \cdot n$?</div>	5



edX

- [About](#)
- [Affiliates](#)
- [edX for Business](#)
- [Open edX](#)
- [Careers](#)
- [News](#)

Legal

- [Terms of Service & Honor Code](#)
- [Privacy Policy](#)
- [Accessibility Policy](#)
- [Trademark Policy](#)
- [Sitemap](#)

Connect

- [Blog](#)
- [Contact Us](#)
- [Help Center](#)
- [Media Kit](#)



© 2022 edX LLC. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)