



✓ [Xâu Ký Tự Cơ Bản]. Bài 32. Tần suất của từ

[C++ CB NC](#)[C++ NC](#)[DSA](#)[JAVA OOP](#)[View
as PDF](#)

Cho xâu **S** gồm các từ các nhau 1 vài dấu cách, bạn hãy đếm xem mỗi từ xuất hiện bao nhiêu lần và liệt kê theo **thứ tự từ điển tăng dần** ?

[Submit solution](#)

Đầu vào

Dòng duy nhất chứa xâu **S**

Giới hạn

$1 \leq \text{len}(S) \leq 100000$

S chứa kí tự là chữ cái và dấu cách

Đầu ra

In ra các từ khác nhau xuất hiện trong xâu kèm theo tần suất với thứ tự tăng dần về từ điển.

Ví dụ :

Input 01

```
cpp elon 28tech 28tech 28tech fruit orange elon orange el
```

[Copy](#)

Output 01

[Copy](#)[My submissions](#)[All submissions](#)[Best submissions](#)

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

🖨️ **Input:** stdin

🖨️ **Output:** stdout

📝 **Problem source:**
28Tech

➤ **Problem type**

▼ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



```
cpp 1
elon 3
fruit 1
orange 2
```

Comments

[Report an issue](#)

Please read the [guidelines](#) before commenting.

0



ichingu

commented 7:59:25 pm, 23/01/2026



code mảng đánh dấu full AC

include <bits/stdc++.h>

```
using namespace std; string s; vector<string> v; bool a[1000011]; int
main() { getline(cin,s); stringstream ss(s); string tmp; while(ss>>tmp){
v.push_back(tmp); } sort(v.begin(),v.end()); for(int i=0;i<v.size();i++){
a[i]=true; } for(int i=0;i<v.size();i++){ int cnt=0; if(a[i]==true){
a[i]=false; cnt++; for(int j=i+1;j<v.size();j++){ if(v[i]==v[j]){ cnt++;
a[j]=false; } } cout<<v[i]<<" "<<cnt<
```

1



Huyen

commented 6:24:15 pm, 03/11/2025



include <bits/stdc++.h>

```
using namespace std;
```

```
int main() { map < string, int > mp;
string s; while (cin >> s) { mp[s]++;
} for (auto x : mp) { cout << x.first << " " << x.second << "\n"; }
return 0; }
```



Hello, Nguyễn Bảo Toàn.

1
▼

Huyen

include <bits/stdc++.h>

using namespace std;

```
int main() { map<string, int> mp;
string s; while (cin >> s) { mp[s]++; } for (auto x : mp) { cout <<
x.first << " " << x.second << "\n"; } return 0; }
```

^
0
▼

commented 8:04:43 pm, 13/09/2025

quanphan475

← edit 4



full ac

```
#include <bits/stdc++.h>
using namespace std;
int main() {
    map <string, int> mp;
    string s;
    while (cin >> s) {
        mp[s]++;
    }
    for (auto x : mp) {
        cout << x.first << " " << x.second << "\n";
    }
    return 0;
}
```

Copy

&lt; = <



Hello, Nguyễn Bảo Toàn.

Post!

Được phát triển bởi **28TECH.COM.VN**