





✓ [Xâu Ký Tự Cơ Bản]. Bài 5. Chèn dấu phẩy

[View
as PDF](#)

Khi viết 1 số nguyên dương quá lớn, người ta thường thêm các dấu phẩy vào giữa các chữ số cho dễ đọc

Ví dụ : số **N = 123456789** được viết thành **123,456,789**, **N = 12345** được viết thành **12,345**. Nhiệm vụ của bạn là thêm dấu phẩy vào số **N**

Gợi ý : Duyệt từ cuối của xâu **N** về và nối các kí tự của **N** vào xâu kết quả, dùng thêm biến đếm nếu cứ đếm được 3 kí tự thì nối thêm 1 dấu phẩy vào xâu kết quả.

Đầu vào

Dòng duy nhất chứa số nguyên dương **N**

Giới hạn

$1 \leq N \leq 10^{18}$

Đầu ra

In ra **N** sau khi thêm dấu phẩy.

Ví dụ :

Input 01

999970094

[Copy](#)

Output 01

[Copy](#)[Submit solution](#)[My submissions](#)[All submissions](#)[Best submissions](#)

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

🖨️ **Input:** stdin

🖨️ **Output:** stdout

📄 **Problem source:**
28Tech

➤ **Problem type**

✓ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



Comments

[Report an issue](#)

Please read the [guidelines](#) before commenting.



TanLoc11a1

commented 8:08:58 pm, 28/01/2026

**include <bits/stdc++.h>**

```
using namespace std; const int MOD=1e9+7; int
a[1000005],dp[1000005]; int main(){
```

```
ios_base::sync_with_stdio(0);
cin.tie(0);
cout.tie(0);
string s; cin>>s;
int cnt=1;
for (int i=s.size()-1;i>0;i--){
    if (cnt==3){
        s.insert(i,1,',');
        cnt=0;
    }
    cnt++;
}
```

Copy

```
} cout<<s; }
```



lmnlmnlmn

commented 4:03:39 pm, 17/01/2026



ae tham khảo nhé 1 vòng lặp ko cần duyệt ngược

```
'#include <bits/stdc++.h> using namespace std;
```



```

    if(i%3==d){ if(i>0) cout<<' '; cout<<str[i]; } else cout<<str[i]; } return
    0; }

```



commented 6:23:24 pm, 10/09/2025

bengokyeuanh99



Full AC

```

include <iostream>
include <string>
include <algorithm>

```

```

namespace formatter { const char separator = ','; const int groupSize
= 3;

```

```

std::string addThousandsSeparators(const
std::string& rawInput) {
    std::string formattedOutput;
    formattedOutput.reserve(rawInput.size() +
rawInput.size() / groupSize);

    int digitCounter = 0;
    for (int i = static_cast<int>(rawInput.size()) -
1; i >= 0; --i) {
        formattedOutput.push_back(rawInput[i]);
        digitCounter++;

        if (digitCounter % groupSize == 0 && i > 0)
        {
            formattedOutput.push_back(separator);
        }
    }

    std::reverse(formattedOutput.begin(),
formattedOutput.end());
    return formattedOutput;
}

```

Copy



```
int main() { std::ios::syncwithstdio(false); std::cin.tie(nullptr);
```


```
    std::string rawInput;
    std::cin >> rawInput;

    auto outputNumber =
    formatter::addThousandsSeparators(rawInput);
    std::cout << outputNumber << "\n";

    return 0;
```

Copy

```
}
```



commented 6:31:07 am, 31/03/2025



Kaybe

```
include <stdio.h>
include <stdlib.h>
include <string.h>
include <ctype.h>
```

```
void solve(char c[]){ char res[10005]; int index = 0; int cnt = 0; for(int
i = strlen(c) - 1; i >= 0; i--){ ++cnt; res[index] = c[i]; ++index; if(cnt %
3 == 0 && i != 0){ res[index] = ','; ++index; } } for(int i = index - 1; i
>= 0; i--){ printf("%c", res[i]); } } int main(){ char c[10005]; scanf("%s",
c); solve(c); }
```



Hello, Nguyễn Bảo Toàn.

Post!

Được phát triển bởi **28TECH.COM.VN**